

## ACRYLIC-BASED HIGH TEMPERATURE ADHESIVE HFS80IHT



### PRODUCT CHARACTERISTICS

- Solvent-free
- Fibre-reinforced
- Quick and strong initial tack
- Frost sensitive
- Acrylic-based
- Perfect dimensional stability
- No waiting, immediate installation
- Suitable for all LVT flooring

### PRODUCT CHARACTERISTICS

Product Code	HFS80IHT
Product Range	Hardwood Floor Store Accessories
Weight	15kg
Underfloor Heating	Yes

<b>kg / m<sup>2</sup></b> 0,2-0,4	 OPEN TIME 20-30min	 3-5 hours	 >10°C
--------------------------------------	--	--	--

### INSTALLATION & MAINTENANCE

Fibre-reinforced acrylic-based and solvent-free, high temperature adhesive, suitable for LVT flooring, with very quick and strong initial tack, excellent adhesive properties and a perfect dimensional stability.

**APPLICATION:** The subfloor has to be uniformly dry, absorbent and smooth, mechanically resistant and clean.

On non-absorbent subfloors, eg. ceramic tiles, first apply a 2 mm levelling compound to ensure a strong bond.

You have to let the flooring acclimatise before starting the laying.

Mix carefully before using and spread the adhesive using a suitable notched trowel.

Follow Plusfloor's instructions concerning the laying technique.

This adhesive can be used in areas subject to high temperatures. However not if a floor covering is being installed in areas with temperatures that exceed 35 degrees c, for example a south facing building with large windows which could magnify the temperature.


In order to avoid air bubbles, treat the floor carefully. After a few minutes, roll it again. Use water to clean your tools.

Contains: Reaction product: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7];

May produce an allergic reaction.



MADE IN ITALY



**15 kg**

### INSTALLATION AND WARRANTY

All Plusfloor floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Plusfloor's warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by The Hardwood Floor Store Limited, Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

#### Plusfloor

Unit 11,  
Carnforth Business Park,  
Oakwood Way  
Carnforth, LA5 9FD

T. +44(0)1524 481 118  
F. +44(0)1524 481 171

info@plusfloor.com  
www.plusfloor.com