

TECHNICAL DATA SHEET

PRODUCT DETAILS

Product Code HF508
Product Range Kahrs

Construction Engineered

Specie Oak Pattern 1-Strip

Design Features Brushed, Handscraped,

Smoked

Finish Nature Oiled
Joint Fold Down

Edge Profile 4-Sided Micro Bevelled

Wear Layer Material Hardwood
Wear Layer Thickness 2.5mm (3/32in)

Core Material Pine/Spruce lamella

Grade Dynamic

Width 190mm
Length 1900mm
Thickness 14mm

Weight per Package 22kg
Area per Package (m²) 2.9m

Package Info Packages may contain

start and stop boards.

KAHRS

HF508 BREATON



INSTALLATION METHODS

Origin Europe
Brinell Value 3.7
Floor Heating Yes
Surface Treatment Oil

This floor should be oiled immediately after installation.

INSTALLATION AND WARRANTY

All Hardwood Floor Store floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Hardwood Floor Store's warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by HFSco Limited, Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior no-tice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

HFSco Limited

Unit 11, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD