


# Formation Herringbone

## Glue Down Vinyl Herringbone

**Contact**  
 +44 (0) 1524 481 118  
 info@plusfloor.com  
 plusfloor.com



**Herringbone**  
 630 x 160 x 2.5mm

**Glacial Heather**  
 PLF4272GH

**Italian Lime**  
 PLF4280GH

**Pastel Blanc**  
 PLF4252GH

### Product

Fixing	Glue Down	
Finish	TrueGrain embossing	
Profile	Butt Joint	
Edge	Bevelled	
Wear Layer	0.55mm	
Pack Size	2.4m <sup>2</sup>	24 planks per box




**French Loft**  
 PLF4254GH

**Pure Oyster**  
 PLF4260GH



### Technical

Slip Resistance	36+PTV / R10*	DIN 51130
Water Resistance		
Stain Resistance	Resistant	EN ISO 26987
Scratch Resistance	Class T	EN ISO 660-2
Underfloor Heating	Suitable, max. 27°C	EN 12524
Inflammability	Bfl-S1	EN 13501
Squareness	≤ 0.35mm	EN ISO 24342
Straightness	≤ 0.35mm	EN ISO 24342
Residual Indentation	≤ 0.10mm	EN ISO 24343-1
Curling	≤ 2mm	EN ISO 23999
Dimensional Stability	Norm: ≤ 0.25mm%	EN ISO 23999
Thermal Resistance R	0.0100m <sup>2</sup> K/W	EN 12664
Formaldehyde Group	E1	EN 717-1
Castor Chair Resistance	Resistant	EN ISO 4918
Light Fastness	≥ 6	EN ISO 105-B02
Warranty (Years)	20 (Residential)	10 (Commercial)



**Silvery Clay**  
 PLF4262GH

**Prairie Jute**  
 PLF4274GH



**Burnt Cocoa**  
 PLF4268GH

**Pitted Magma**  
 PLF4278GH

#### Installation and Warranty

All **PlusFloor** floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. **PlusFloor's** warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by **PlusFloor**, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD. At the time of writing and publication of this document, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

\*Glacial Heather, Prairie Jute, Pitted Magma and Italian Lime have a slip resistance rating of R10