

TECHNICAL DATA SHEET

PRODUCT INFORMATION

High density polyethylene underlay with antislip layer designed for LVT floors with Click system, offering very good floor heating compatibility.

- Closed cells UHD polyethylene foam used for installation of class 2 LVT floors in residential buildings (according to MMFA).
- · Antislip surface for locking system protection.
- Perfect for floor heating highly exceeds minimum heat conduction value recommended by MMFA.
- · Very high material density. MMFA recommended
- · 100 % recyclable, CFC and HCFC free.
- · Ecologically friendly.

HIGH DENSITY UNDERLAY | 15M2 PLF0011



TECHNICAL DETAILS

Thickness 1.2mm EN823
Length 15,000mm EN822
Width 1000mm EN822

 Area Weight
 0,21kg/m2
 EN ISO 23997:2012

 Density
 130kg/m2
 EN ISO 23996:2012

Reflected Walking Sound 8% IHD-W431

Impact Sound Reduction16dBEN ISO10140, ISO717-2Temporary Loads Resistance200kPaEN 826:2013+A: FU1:2019

Static Loads (Furniture) Resistance>50kPaEN1606Dynamic Loads (Walking) Resistance>100000 cyclesEN13793Local Unevenness Compensation0,95mmEN-ISO868

Thermal Insulation 0,024m2K/W EN12667:2002 at 24 C

Protection Against Moisture <75m EN12086

Protection Against Falling Objects 800mm EN13329, EN438

Reaction To Fire --- EN ISO11925-2,PN-EN13501-1

INSTALLATION & WARRANTY

All Hardwood Floor Store floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Hardwood Floor Store's warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Hardwood Floor Store, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD. At the time of writing and publication of this folder, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.