

# plusfloor

## TECHNICAL DATA SHEET

### Formation Herringbone

PLF4264GH Blanched Carbon



#### PRODUCT DETAILS

Product Range	Formation	
	Herringbone	
Product Codes	PLF4230GH – PLF4268GH	
Pattern	Herringbone	EN ISO 24342
Finish	Truegrain	
Profile	Butt Joint	
Edge Profile	Bevelled Edge	
Thickness	2.5mm	EN ISO 24346
Width	158mm	±0.10mm
Length	632mm	
Wear Layer	0.55mm	EN ISO 24340
Pack Size	2.40m <sup>2</sup> /box	24pcs/box
Weight	4.059	EN ISO 23997

#### INSTALLATION & MAINTENANCE

Fully Bonded	Yes
Nailed	No

#### INSTALLATION AND WARRANTY

All Plusfloor floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Plusfloor's warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by The Hardwood Floor Store Limited, Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

#### TECHNICAL CRITERIA

Origin	Europe	
Level of use	EN ISO 10874	23 – 33 – 42
Inflamability	EN 13501	Bfl-S1
Scratch resistance	EN ISO 660-2	Class T
Squareness & straightness	EN ISO 24342b	≤ 0,35 mm
Residual indentation	EN ISO 24343-1	≤ 0,10 mm
Furniture leg resistance	EN ISO 16581	
Curling	EN ISO 23999	≤ 2 mm
Electrical resistance	EN 1081	≤ 10 <sup>9</sup> Ohm
Dimensional stability	EN ISO 23999	
Slip Rating	36+ PTV	
Heat insulation	EN ISO 10456	0,25 w/(m.K)
Thermal resistance R	EN 12664	0,0100 m <sup>2</sup> .K/W
Electrostatic performance	EN 1815	< 2 kV
Formaldehyde group	EN 717-1	E1
Acoustic insulation	EN ISO 717-2	4 dB
Castor chair resistance	EN ISO 4918	
Stain resistance	EN ISO 26987	Very good
Light fastness	EN ISO 105-B02	≥6
Underfloor heating	EN 12524	Suitable, max 27°C
LRV Rating		12
Warranty (year)	30 Residential	10 Commercial

*The warranty covers manufacturing defects and premature wear in the event of normal use.*

#### Plusfloor

Unit 11,  
Carnforth Business Park,  
Oakwood Way  
Carnforth, LA5 9FD

T. +44(0)1524 481 118  
F. +44(0)1524 481 171

info@plusfloor.com  
www.plusfloor.com