

plusfloor

TECHNICAL DATA SHEET

CONTRACT FOAM UNDERLAY PLF0010-50

TECHNICAL CRITERIA

Tensile Stress	(N)	GB/T 528	MD:3.5 TD:3
Tensile Strength	(Mpa)	GB/T 528	MD:0.6 TD:0.5
Elongation	(%)	GB/T 528	MD:100 TD:100
Thickness	(mm)		0.9-1.1
Magnification	(Times)		14-7
Hardness		Shore C/1S	30-40

PRODUCT DETAILS

Product Code	PLF0010-50
Product Range	Plusfloor Accessories
Construction	IXPE Foam
Roll Size	50m ²
Thickness	1mm
Width	1m

Remarks: There is a ±10% for mass production

INSTALLATION AND WARRANTY

All Plusfloor floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Plusfloor's warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Plusfloor, Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

Plusfloor,
Units 11,
Carnforth Business Park,
Oakwood Way, Carnforth,
LA5 9FD

T. +44(0)1524 481 118
F. +44(0)1524 481 171

info@plusfloor.co.uk

www.plusfloor.co.uk