

# plusfloor

## Silver Rubber Foil Backed Underlay 3mm

Code	-
Size	1m x 10m (10m <sup>2</sup> )
Thickness	3mm

Heavy  
Traffic

Wood



### All the stability you need

The high density, fleece-backed natural rubber is extremely stable and prevents movement in your flooring, reducing wear and tear.

### Shhh! Underlay at work

This is an underlay with real acoustic performance thanks to its thick materials, cutting down noise levels to make any room more comfortable.

### Dry as a bone

Don't worry about moisture rising up from the sub-floor – the silver vapour barrier film protects your floor covering against damp.



### Technical Data

Properties	Unit	Value	Method
Density	kg/m <sup>3</sup>	950 ± 50	internal
Weight per square metre	kg/m <sup>2</sup>	2.8 ± 0.28	internal
Impact Sound Reduction	dB	≈ 21	BS EN ISO 717-2
Thermal Resistance	Tog	0.37	BS 4745:2005
Maximum Compression Load	kN/m <sup>2</sup>	2-5	DIN EN 1606
Flammability	Pass	Low radius of effect	Hot Metal Nut Test

\*Suitable for hotels and public buildings

### Plusfloor

Unit 11, Carnforth Business Park,  
Oakwood Way Carnforth, LA5 9FD

Tel: 01524 481 118

Fax: 01524 481 171

Email: [sinfo@plusfloor.com](mailto:sinfo@plusfloor.com)

[www.plusfloor.com](http://www.plusfloor.com)

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.