

VETRO

LUXURY TILES

PRODUCT INFORMATION

VT2528

CODE: VT2528
REFERENCE: CELINA ARTISAN SILVER
SIZE: 7.5x30cm
THICKNESS: 9.5mm
FINISH:
BODY TYPE: Wall Tile - Group BIII

INDICATIVE IMAGE:



WATER ABSORPTION

WATER ABSORPTION EN ISO- 10545 - 3 > 10%

DIMENSIONAL CHARACTERISTICS

SURFACE QUALITY EN ISO- 10545 - 2 > 95%
CURVATURE FLATNESS EN ISO- 10545 - 2 0.5/-0.3% 2.0/-1.5mm
THICKNESS EN ISO- 10545 - 2 $\pm 10\%$ / $\pm 0.5\text{mm}$
LENGTH & WIDTH EN ISO- 10545 - 2 $\pm 0.5\%$ / $\pm 2.0\text{mm}$
RECTANGULARITY EN ISO- 10545 - 2 $\pm 0.5\%$ / $\pm 2.0\text{mm}$
STRAIGHTNESS OF SIDES EN ISO- 10545 - 2 $\pm 0.3\%$ / $\pm 1.5\text{mm}$

MECHANICAL CHARACTERISTICS

CRAZING RESISTANCE EN ISO- 10545 - 11 Pass
THERMAL SHOCK RESISTANCE EN ISO- 10545 - 9 Pass
BREAKING STRENGTH EN ISO- 10545 - 4 > 600N
MODULUS OF RUPTURE EN ISO- 10545 - 4 > 12 N/mm²

SURFACE CHARACTERISTICS

VISIBLE FAILURE AT NO. OF REVOLUTIONS EN ISO- 10545 - 7 -
SURFACE SCRATCH RESISTANCE EN- 101 3

CHEMICAL CHARACTERISTICS

HIGH CONCENTRATIONS OF ACIDS & ALKALIS EN ISO- 10545 - 13 GHA/GHA/GHA
LOW CONCENTRATIONS OF ACIDS & ALKALIS EN ISO- 10545 - 13 GLA/GLA/GLA
HOUSEHOLD CHEMICALS & SWIMMING POOL SALTS EN ISO- 10545 - 13 GA/GA
STAIN RESISTANCE EN ISO- 10545 - 14 5/-/5/5

NON-SLIP CHARACTERISTICS

CRITICAL ANGLE (FOOTWEAR) DIN- 51130 -

CE MARKING

CE DECLARATION OF PERFORMANCE:  004CPR2017-08-01

DISCLAIMER

Before laying tiles, check the shade, size and quality. No claims will be accepted once the tiles have been laid. Leave a tile joint of at least 0.5mm in the case of rectified tiles and 1.5mm for non-rectified ones. The tile colour shown in this data sheet is merely indicative and it might differ from the real tile colour. This document is purely for sales purposes and it cannot be used in any legal or administrative proceedings without the permission of Vetro Global Pty Ltd.

T: +61 1300 770 770
www.vetroglobal.com

Vetro Global Pty Ltd
info.au@vetroglobal.com

LONDON

NEW YORK

SYDNEY