

LUXURY TILES

PRODUCT INFORMATION VT2567

CODE: VT2567

REFERENCE: MANDRA PURE POLISHED

SIZE: 60x120cm THICKNESS: 12mm FINISH: Ecopulido

BODY TYPE: Porcelain - Group Bla

INDICATIVE IMAGE:



WATER ABSORPTION

WATER ABSORPTION EN ISO-10545 - 3 <0.5%

DIMENSIONAL CHARACTERISTICS

SURFACE QUALITY	EN ISO-10545 - 2	>95%
CURVATURE FLATNESS	EN ISO-10545 - 2	± 0.5% / ± 2.0mm
THICKNESS	EN ISO-10545 - 2	± 5% / ± 0.5mm
LENGTH & WIDTH	EN ISO-10545 - 2	± 0.6% / ± 2.0mm
RECTANGULARITY	EN ISO-10545 - 2	± 0.5% / ± 2.0mm
STRAIGHTNESS OF SIDES	EN ISO-10545 - 2	± 0.5% / ± 1.5mm

MECHANICAL CHARACTERISTICS

CRAZING RESISTANCE	EN ISO-10545 - 11	Pass
FROST RESISTANCE	EN ISO-10545 - 12	Pass
THERMAL SHOCK RESISTANCE	EN ISO-10545 - 9	Pass
BREAKING STRENGTH	EN ISO-10545 - 4	> 1300N
MODULUS OF RUPTURE	EN ISO-10545 - 4	> 35N/mm²

SURFACE CHARACTERISTICS

VISIBLE FAILURE AT NO. OF REVOLUTIONS	EN ISO- 10545 - 7	-
SURFACE SCRATCH RESISTANCE	EN-101	0

CHEMICAL CHARACTERISTICS

HIGH CONCENTRATIONS OF ACIDS & ALKALIS	EN ISO-10545 - 13	GHB/GHB/GHB
LOW CONCENTRATIONS OF ACIDS & ALKALIS	EN ISO-10545 - 13	GLB/GLB/GLB
HOUSEHOLD CHEMICALS & SWIMMING POOL SALTS	EN ISO-10545 - 13	GA/GA
STAIN RESISTANCE	EN ISO- 10545 - 14	5/-/5/5

NON-SLIP CHARACTERISTICS

CRITICAL ANGLE (FOOTWEAR)	DIN- 51130	_

CE MARKING

CE DECLARATION OF PERFORMANCE:	(E 001CPR2017-08-01

DISCLAIMER

Before laying tiles, check the shade, size and quality. No claims will be accepted once the tiles have been laid. Leave a tile joint of at least 0.5mm in the case of rectified tiles and 1.5mm for non-rectified ones. The tile colour shown in this data sheet is merely indicative and it might differ from the real tile colour. This document is purely for sales purposes and it cannot be used in any legal or administrative proceedings without the permission of Vetro Global Pty Ltd.

T: +61 1300 770 770 www.vetroglobal.com Vetro Global Pty Ltd info.au@vetroglobal.com