

PRODUCT INFORMATION

VT2205

CODE: VT2205
 REFERENCE: RISANARE LUCILLE
 SIZE: 9.8x59.3cm
 THICKNESS: 9.5mm
 FINISH:
 BODY TYPE: Porcelain - Group Bla

INDICATIVE IMAGE:



MECHANICAL CHARACTERISTICS

CRAZING RESISTANCE	EN ISO- 10545 - 11	Pass
FROST RESISTANCE	EN ISO- 10545 - 11	Pass
THERMAL SHOCK RESISTANCE	EN ISO- 10545 - 9	Pass

SURFACE CHARACTERISTICS

SURFACE ABRASION RESISTANCE	EN ISO- 10545 - 7	4
VISIBLE FAILURE AT NO. OF REVOLUTIONS	EN ISO- 10545 - 7	2100 rev.
SURFACE SCRATCH RESISTANCE	EN- 101	7

CHEMICAL CHARACTERISTICS

HIGH CONCENTRATIONS OF ACIDS & ALKALIS	EN ISO- 10545 - 13	GHA/GHA/GHA
LOW CONCENTRATIONS OF ACIDS & ALKALIS	EN ISO- 10545 - 13	GLA/GLA/GLA
HOUSEHOLD CHEMICALS & SWIMMING POOL SALTS	EN ISO- 10545 - 13	GA/GA
STAIN RESISTANCE	EN ISO- 10545 - 14	5/-/5/5

NON-SLIP CHARACTERISTICS

DYNAMIC COEFFICIENT OF FRICTION (DCOF)	ANSI A137	>0.42
SLIP RESISTANCE TEST (PTV) - WET CONDITIONS	BS- 7976	+36
CRITICAL ANGLE (FOOTWEAR)	DIN- 51130	R-11
SLIP RESISTANCE (PENDULUM TEST)	UNE-ENV-12633	2

CE MARKING

CE DECLARATION OF PERFORMANCE:



DISCLAIMER

Before laying tiles, check the shade, size and quality. No claims will be accepted once the tiles have been laid. Leave a tile joint of at least 0.5mm in the case of rectified tiles and 1.5mm for non-rectified ones. The tile colour shown in this data sheet is merely indicative and it might differ from the real tile colour. This document is purely for sales purposes and it cannot be used in any legal or administrative proceedings without the permission of Vetro Global Pty Ltd.