

Sponsor: Jeremy Briggs Luosh USA, LLC 1061 Triad Ct., Ste. 4 Marietta, GA 30062

Bacterial Filtration Efficiency (BFE) Final Report

Test Article: 11062020-1 Study Number: 1361722-S01 Study Received Date: 10 Nov 2020

> Testing Facility: Nelson Laboratories, LLC

6280 S. Redwood Rd. Salt Lake City, UT 84123 U.S.A.

Test Procedure(s): Standard Test Protocol (STP) Number: STP0004 Rev 18

Deviation(s):

Summary: The BFE test is performed to determine the filtration efficiency of test articles by comparing the bacterial counts upstream of the test article to the bacterial counts downstream. A suspension of Staphylococcus aureus was aerosolized using a nebulizer and delivered to the test article at a constant flow rate and fixed air pressure. The challenge delivery was maintained at 1.7 - 3.0 x 10³ colony forming units (CFU) with a mean particle size (MPS) of $3.0 \pm 0.3 \mu m$. The aerosols were drawn through a sixstage, viable particle, Andersen sampler for collection. This test method complies with ASTM F2101-19 and EN 14683:2019, Annex B.

All test method acceptance criteria were met. Testing was performed in compliance with US FDA good manufacturing practice (GMP) regulations 21 CFR Parts 210, 211 and 820.

> Test Side: Inside \sim 40 cm² BFE Test Area:

BFE Flow Rate: 28.3 Liters per minute (L/min)

Conditioning Parameters: 85 ± 5% relative humidity (RH) and 21 ± 5°C for a minimum of 4 hours

Test Article Dimensions: ~175 mm x ~157 mm

Positive Control Average: 2.7×10^{3} CFU <1 CFU Negative Monitor Count:

MPS: 2.9 µm





David Brown electronically approved for

Mikell Goldsberry

15 Dec 2020 05:05 (+00:00)

Study Completion Date and Time

801-290-7500

Study Director

nelsonlabs.com sales@nelsonlabs.com

FRT0004-0001 Rev 22 Page 1 of 2



Results:

Test Article Number	Percent BFE (%)	
1	>99.9	
2	>99.9	
3	99.9	
4	>99.9	
5	>99.9 ^a	

^a There were no detected colonies on any of the Andersen sampler plates for this test article.

The filtration efficiency percentages were calculated using the following equation:

$$\% BFE = \frac{C - T}{C} \times 100$$

C = Positive control average

T = Plate count total recovered downstream of the test article Note: The plate count total is available upon request