

Version 9.7	Revision Date: 04/18/2022	•	DS Number: 349484-00049	Date of last issue: 08/16/2021 Date of first issue: 02/27/2017	
SECTIO	ON 1. IDENTIFICATION				
Pro	oduct name	:	Opteon™ XP40 (R-449A) Refrigerant	
Pro	oduct code	:	D15437193		
SE	S-Identcode	:	130000133420		
Ма	nufacturer or supplier's	det	ails		
Co	Company name of supplier		The Chemours Company FC, LLC		
Ad	dress	:	1007 Market Stre Wilmington, DE 1	et 9801 United States of America (USA)	
Те	Telephone		1-844-773-CHEM (outside the U.S. 1-302-773-1000)		
En	Emergency telephone		Medical emergency: 1-866-595-1473 (outside the U.S. 1-30, 773-2000) ; Transport emergency: +1-800-424-9300 (outsi the U.S. +1-703-527-3887)		
Re	commended use of the o	cher	nical and restricti	ons on use	
Re	commended use	:	Refrigerant		
Re	strictions on use	:	Consumer use, F	or professional users only.	

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)						
Gases under pressure	:	Liquefied gas				
Simple Asphyxiant						
GHS label elements						
Hazard pictograms	:					
Signal Word	:	Warning				
Hazard Statements	:	H280 Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation.				
Precautionary Statements	:	Storage: P410 + P403 Protect from sunlight. Store in a well-ventilated place.				



Opteon[™] XP40 (R-449A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 08/16/2021
9.7	04/18/2022	1349484-00049	Date of first issue: 02/27/2017

Other hazards

Vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
1,1,1,2-Tetrafluoroethane#	811-97-2	25.7
2,3,3,3-Tetrafluoropropene#	754-12-1	25.3
Pentafluoroethane#	354-33-6	24.7
Difluoromethane#	75-10-5	24.3

Voluntarily-disclosed substance

SECTION 4. FIRST AID MEASURES

General advice	:	In the case of accident or if you feel unwell, seek medical ad- vice immediately. When symptoms persist or in all cases of doubt seek medical advice.
If inhaled	:	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
In case of skin contact	:	Thaw frosted parts with lukewarm water. Do not rub affected area. Get medical attention immediately.
In case of eye contact	:	Get medical attention immediately.
If swallowed	:	Ingestion is not considered a potential route of exposure.
Most important symptoms and effects, both acute and delayed	:	May cause cardiac arrhythmia. Other symptoms potentially related to misuse or inhalation abuse are Cardiac sensitization Anaesthetic effects Light-headedness Dizziness confusion Lack of coordination Drowsiness Unconsciousness Skin contact may provoke the following symptoms: Irritation Swelling of tissue Itching



Vers 9.7	sion	Revision Date: 04/18/2022		DS Number: 49484-00049	Date of last issue: 08/16/2021 Date of first issue: 02/27/2017
				tearing Redness Discomfort Gas reduces oxyg	provoke the following symptoms gen available for breathing. d or refrigerated gas can cause cold burns
	Protect	ion of first-aiders	:	No special precau	utions are necessary for first aid responders.
	Notes t	o physician	:	techolamine drug	ble disturbances of cardiac rhythm, ca- s, such as epinephrine, that may be used in rgency life support should be used with spe-
SEC	TION 5	. FIRE-FIGHTING ME	ASL	JRES	
	Suitable	e extinguishing media	:	Not applicable Will not burn	
	Unsuita media	able extinguishing	:	Not applicable Will not burn	
	Specific fighting	c hazards during fire	:		bustion products may be a hazard to health. The rises there is danger of the vessels bursting apor pressure.
	Hazard ucts	ous combustion prod-	:	Hydrogen fluoride carbonyl fluoride Carbon oxides Fluorine compour	
	Specific ods	c extinguishing meth-	:	cumstances and f Fight fire remotely Use water spray t	g measures that are appropriate to local cir- the surrounding environment. y due to the risk of explosion. to cool unopened containers. ged containers from fire area if it is safe to do
		l protective equipment fighters	:	necessary.	ed breathing apparatus for firefighting if tective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec-	:	Evacuate personnel to safe areas.
tive equipment and emer-		Avoid skin contact with leaking liquid (danger of frostbite).
gency procedures		Ventilate the area.
2		Follow safe handling advice (see section 7) and personal pro-
		tective equipment recommendations (see section 8).



Version 9.7	Revision Date: 04/18/2022		DS Number: 49484-00049	Date of last issue: 08/16/2021 Date of first issue: 02/27/2017	
Env	ironmental precautions	:		the environment. akage or spillage if safe to do so. se of contaminated wash water.	
	Methods and materials for containment and cleaning up		: Ventilate the area. Local or national regulations may apply to releases and dispo- sal of this material, as well as those materials and items em- ployed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.		
SECTIO	N 7. HANDLING AND ST	OR	AGE		
Tec	hnical measures	:	Use equipment ra	ated for cylinder pressure. Use a backflow	

Technical measures	:	Use equipment rated for cylinder pressure. Use a backflow preventative device in piping. Close valve after each use and when empty.
Local/Total ventilation	:	Use only with adequate ventilation.
Advice on safe handling	:	Avoid breathing gas. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as- sessment Wear cold insulating gloves/ face shield/ eye protection. Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point. Use a check valve or trap in the discharge line to prevent ha- zardous back flow into the cylinder. Prevent backflow into the gas tank. Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems. Close valve after each use and when empty. Do NOT change or force fit connections. Prevent the intrusion of water into the gas tank. Never attempt to lift cylinder by its cap. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment.
Conditions for safe storage	:	Cylinders should be stored upright and firmly secured to pre- vent falling or being knocked over. Separate full containers from empty containers. Do not store near combustible materials. Avoid area where salt or other corrosive materials are present. Keep in properly labeled containers. Keep in a cool, well-ventilated place. Keep away from direct sunlight. Store in accordance with the particular national regulations.



Versi 9.7	ion	Revision Date: 04/18/2022		0S Number: 49484-00049	Date of last issue: 08/16/2021 Date of first issue: 02/27/2017
I	Materials to avoid		:	Self-reactive subs Organic peroxides Oxidizing agents Flammable liquids Flammable solids Pyrophoric liquids Pyrophoric solids Self-heating subs Substances and r flammable gases Explosives Very acutely toxic Acutely toxic subs	8
	Recomi perature	mended storage tem- e	:	< 126 °F / < 52 °C	
:	Storage	period	:	> 10 y	
	Further age sta	information on stor- bility	:	The product has a	an indefinite shelf life when stored properly.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
1,1,1,2-Tetrafluoroethane	811-97-2	TWA	1,000 ppm	US WEEL
2,3,3,3-Tetrafluoropropene	754-12-1	TWA	500 ppm	US WEEL
Pentafluoroethane	354-33-6	TWA	1,000 ppm	US WEEL
Difluoromethane	75-10-5	TWA	1,000 ppm	US WEEL

Ingredients with workplace control parameters

Engineering measures	:	Ensure adequate ventilation, especially in confined areas.
		Minimize workplace exposure concentrations.

Personal protective equipment

protection.	Respiratory protection	:	General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazar- dous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.
-------------	------------------------	---	--



Version 9.7	Revision Date: 04/18/2022		DS Number: 349484-00049	Date of last issue: 08/16/2021 Date of first issue: 02/27/2017
	d protection laterial	:	Low temperature	resistant gloves
R	emarks	:	on the concentrat applications, we r micals of the afor manufacturer. Wa	protect hands against chemicals depending tion specific to place of work. For special recommend clarifying the resistance to che- ementioned protective gloves with the glove ash hands before breaks and at the end of trough time is not determined for the pro- ves often!
Eye	protection	:		g personal protective equipment: nt goggles must be worn.
Skin	and body protection	:	Skin should be w	ashed after contact.
Prote	ective measures	:	Wear cold insulat	ing gloves/ face shield/ eye protection.
Hygi	ene measures	:	eye flushing syste king place. When using do ne	emical is likely during typical use, provide ems and safety showers close to the wor- ot eat, drink or smoke. ted clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Liquefied gas
Color	:	clear
Odor	:	slight, ether-like
Odor Threshold	:	No data available
рН	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	-51 °F / -46 °C
Flash point	:	Not applicable
Evaporation rate	:	> 1 (CCL4=1.0)
Flammability (solid, gas)	:	Will not burn

SAFETY DATA SHEET



Opteon™ XP40 (R-449A) Refrigerant

Ver 9.7	sion	Revision Date: 04/18/2022		S Number: 9484-00049	Date of last issue: 08/16/2021 Date of first issue: 02/27/2017
		explosion limit / Upper bility limit	:	Upper flammabili Method: ASTM E None.	
		explosion limit / Lower bility limit	:	Lower flammabili Method: ASTM E None.	
	Vapor p	oressure	:	12,748 hPa (77 °	F / 25 °C)
	Relativ	e vapor density	:	3.07 (Air = 1.0)	
	Relative	e density	:	1.10 (77 °F / 25 °	C)
	Solubili Wat	ty(ies) er solubility	:	No data available)
	Partitio octanol	n coefficient: n- /water	:	Not applicable	
	Autoigr	nition temperature	:	No data available	
	Decom	position temperature	:	No data available	
	Viscosi Visc	ty cosity, kinematic	:	Not applicable	
	Explosi	ve properties	:	Not explosive	
		ng properties	:		r mixture is not classified as oxidizing.
	Particle	e size	:	Not applicable	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.
Possibility of hazardous reac- tions	:	Can react with strong oxidizing agents.
Conditions to avoid	:	This substance is not flammable in air at temperatures up to 100 °C (212 °F) at atmospheric pressure. However, mixtures of this substance with high concentrations of air at elevated pressure and/or temperature can become combustible in the presence of an ignition source. This substance can also become combustible in an oxygen enriched environment (oxygen concentrations greater than that in air). Whether a mixture containing this substance and air, or this substance in an oxygen enriched atmosphere become combustible depends on



7	Revision Date: 04/18/2022		OS Number: 49484-00049	Date of last issue: 08/16/2021 Date of first issue: 02/27/2017
			and 3) the prop substance sho mospheric pres enriched enviro	onship of 1) the temperature 2) the pressure, portion of oxygen in the mixture. In general, the uld not be allowed to exist with air above at- ssure or at high temperatures; or in an oxyger poment. For example this substance should with air under pressure for leak testing or oth and sparks.
Incon	npatible materials	:	Incompatible w	
Haza produ	rdous decomposition	:	No hazardous	decomposition products are known.
•	ontact e toxicity			
Acute Not c		ilable	information.	
Acute Not cl	e toxicity lassified based on avai	ilable	information.	
Acute Not c <u>Com</u> 1,1,1,	e toxicity lassified based on avai ponents:	ilable :		ne substance or mixture has no acute oral tox
Acute Not cl Com 1,1,1 , Acute	e toxicity lassified based on avai ponents: 2-Tetrafluoroethane:	ilable :	Assessment: Th icity LC50 (Rat): > 5 Exposure time: Test atmospher	67000 ppm 4 h
Acute Not cl Com 1,1,1 , Acute	e toxicity lassified based on avai ponents: 2-Tetrafluoroethane: e oral toxicity	ilable : :	Assessment: Th icity LC50 (Rat): > 5 Exposure time: Test atmospher Method: OECD No observed ac Test atmospher	67000 ppm 4 h e: gas Test Guideline 403 Iverse effect concentration (Dog): 40000 ppm
Acute Not c <u>Com</u> 1,1,1, Acute	e toxicity lassified based on avai ponents: 2-Tetrafluoroethane: e oral toxicity	ilable : :	Assessment: Th icity LC50 (Rat): > 5 Exposure time: Test atmospher Method: OECD No observed ac Test atmospher Remarks: Cardi Lowest observe ppm Test atmospher	67000 ppm 4 h e: gas Test Guideline 403 Iverse effect concentration (Dog): 40000 ppm e: gas ac sensitization ed adverse effect concentration (Dog): 80000
Acute Not c <u>Com</u> 1,1,1, Acute	e toxicity lassified based on avai ponents: 2-Tetrafluoroethane: e oral toxicity	ilable : :	Assessment: Th icity LC50 (Rat): > 5 Exposure time: Test atmospher Method: OECD No observed ac Test atmospher Remarks: Cardi Lowest observe ppm Test atmospher Symptoms: May Cardiac sensitis Test atmospher	67000 ppm 4 h e: gas Test Guideline 403 Iverse effect concentration (Dog): 40000 ppm e: gas ac sensitization ed adverse effect concentration (Dog): 80000 re: gas y cause cardiac arrhythmia.



Version 9.7	Revision Date: 04/18/2022	SDS Number:Date of last issue: 08/16/20211349484-00049Date of first issue: 02/27/2017
		toxicity
	,3-Tetrafluoropropene e inhalation toxicity	: : LC50 (Rat): > 405800 ppm Exposure time: 4 h Test atmosphere: gas Method: OECD Test Guideline 403
		No observed adverse effect concentration (Dog): 120000 ppm Test atmosphere: gas Remarks: Cardiac sensitization
		Lowest observed adverse effect concentration (Dog): > 120000 ppm Test atmosphere: gas Remarks: Cardiac sensitization
		Cardiac sensitisation threshold limit (Dog): > 559,509 mg/m³ Test atmosphere: gas Remarks: Cardiac sensitization
Pent	afluoroethane:	
Acute	e inhalation toxicity	 LC50 (Rat): > 800000 ppm Exposure time: 4 h Test atmosphere: gas Method: OECD Test Guideline 403
		No observed adverse effect concentration (Dog): 75000 ppm Remarks: Cardiac sensitization
		Cardiac sensitisation threshold limit (Dog): 368.159 mg/m ³ Remarks: Cardiac sensitization
Diflu	oromethane:	
	e oral toxicity	: Assessment: The substance or mixture has no acute oral tox- icity
Acute	e inhalation toxicity	: LC50 (Rat): > 520000 ppm Exposure time: 4 h Test atmosphere: gas Method: OECD Test Guideline 403
		No observed adverse effect concentration (Dog): 350000 ppm Test atmosphere: gas Remarks: Cardiac sensitization
		Lowest observed adverse effect concentration (Dog): > 350000 ppm Test atmosphere: gas Remarks: Cardiac sensitization
		Cardiac sensitisation threshold limit (Dog): > 735,000 mg/m³ Test atmosphere: gas



ersion 7	Revision Date: 04/18/2022		DS Number: 49484-00049	Date of last issue: 08/16/2021 Date of first issue: 02/27/2017
			Remarks: Cardia	c sensitization
Acute	dermal toxicity	:	Assessment: The toxicity	substance or mixture has no acute derma
Not cl	corrosion/irritation assified based on availa conents:	able	information.	
1,1,1,1, Resul	2-Tetrafluoroethane: t	:	No skin irritation	
2,3,3, Resul	3-Tetrafluoropropene: t	:	No skin irritation	
Difluc Result	promethane: t	:	No skin irritation	
Not cl	us eye damage/eye irr assified based on availa ponents:			
1,1,1,1, Resul	2-Tetrafluoroethane: t	:	No eye irritation	
2,3,3, ; Resul	3-Tetrafluoropropene: t	:	No eye irritation	
Difluc Resul	promethane: t	:	No eye irritation	
Respi	ratory or skin sensitiz	atic	on	
	sensitization assified based on availa	able	information.	
Respi	iratory sensitization assified based on availa			
Comp	oonents:			
	2-Tetrafluoroethane: s of exposure t	:	Skin contact negative	
Route Specie Resul		:	Inhalation Rat negative	



ersion 7	Revision Date: 04/18/2022	SDS Number: 1349484-00049	Date of last issue: 08/16/2021 Date of first issue: 02/27/2017
Route Speci Resul		: Inhalation : Humans : negative	
2,3,3,	3-Tetrafluoropropene:		
Route Resul	es of exposure It	: Skin contact : negative	
Difluc	promethane:		
Route Resul	es of exposure It	: Skin contact : negative	
	cell mutagenicity assified based on availa	able information	
	oonents:		
1,1,1,	2-Tetrafluoroethane:		
Geno	toxicity in vitro		Bacterial reverse mutation assay (AMES) CD Test Guideline 471 ative
			Chromosome aberration test in vitro CD Test Guideline 473 ttive
Geno	toxicity in vivo	cytogenetic a Species: Mo Application F	use Route: inhalation (gas) CD Test Guideline 474
		mammalian Species: Rat Application F	Route: inhalation (gas) CD Test Guideline 486
	cell mutagenicity - ssment	: Weight of ev cell mutager	ridence does not support classification as a gern
	3-Tetrafluoropropene: toxicity in vitro	: Test Type: B	Bacterial reverse mutation assay (AMES) CD Test Guideline 471 ive
			Chromosome aberration test in vitro CD Test Guideline 473 utive

SAFETY DATA SHEET



/ersion 9.7	Revision Date: 04/18/2022	SDS Number: 1349484-00049	Date of last issue: 08/16/2021 Date of first issue: 02/27/2017
Genotoxicity in vivo		cytogenetic ass Species: Mouse Application Rou	e ite: inhalation (gas) Test Guideline 474
		Species: Rat Application Rou	vo mammalian alkaline comet assay ite: inhalation (gas) Test Guideline 489 ə
		cytogenetic ass Species: Rat Application Rou	ite: inhalation (gas) Test Guideline 474
	cell mutagenicity - ssment	: Weight of evide cell mutagen.	nce does not support classification as a germ
Penta	afluoroethane:		
Geno	toxicity in vitro		terial reverse mutation assay (AMES) Test Guideline 471 e
		Result: negative	tro mammalian cell gene mutation test e d on data from similar materials
			omosome aberration test in vitro Test Guideline 473 e
Geno	toxicity in vivo	cytogenetic ass Species: Mouse Application Rou	e ite: inhalation (gas) Test Guideline 474
Diflue	promethane:		
Geno	toxicity in vitro		terial reverse mutation assay (AMES) Test Guideline 471 e
			omosome aberration test in vitro Test Guideline 473 e
Geno	toxicity in vivo	: Test Type: Mar cytogenetic ass	nmalian erythrocyte micronucleus test (in vivo ay)



ersion 7	Revision Date: 04/18/2022	SDS Number: 1349484-00049	Date of last issue: 08/16/2021 Date of first issue: 02/27/2017
			Route: inhalation (gas) CD Test Guideline 474
	cell mutagenicity - ssment	: Weight of ev cell mutager	/idence does not support classification as a germ ח.
	nogenicity assified based on avai	lable information.	
<u>Comp</u>	oonents:		
	2-Tetrafluoroethane:		
	cation Route sure time od	: Rat : inhalation (g : 2 Years : OECD Test : negative	as) Guideline 453
Carcir ment	nogenicity - Assess-	: Weight of ev cinogen	vidence does not support classification as a car-
2.3.3.	3-Tetrafluoropropene		
Resul		: negative	
Carcir ment	nogenicity - Assess-	: Weight of ev cinogen	vidence does not support classification as a car-
IARC			resent at levels greater than or equal to 0.1% is or confirmed human carcinogen by IARC.
OSH/		ent of this product ist of regulated ca	present at levels greater than or equal to 0.1% is rcinogens.
NTP			resent at levels greater than or equal to 0.1% is bated carcinogen by NTP.
Not cl	oductive toxicity assified based on avai ponents:	able information.	
1,1,1,	2-Tetrafluoroethane:		
Effect	s on fertility	: Species: Mo Application Result: nega	Route: Inhalation
Effect	s on fetal developmen	reproduction Species: Ra Application	Route: inhalation (gas) CD Test Guideline 414
		40	/ 22



Version 9.7	Revision Date: 04/18/2022		0S Number: 49484-00049	Date of last issue: 08/16/2021 Date of first issue: 02/27/2017
	productive toxicity - As- sment	:	Weight of evidend ductive toxicity	e does not support classification for repro-
23	3,3-Tetrafluoropropene:			
	ects on fertility	:	Test Type: Two-g Species: Rat Application Route Method: OECD T Result: negative	
Effe	ects on fetal development	:	Species: Rat Application Route	tal development toxicity study (teratogenicity) : inhalation (gas) est Guideline 414
•	productive toxicity - As- sment	:	0	e does not support classification for repro- o effects on or via lactation
Per	tafluoroethane:			
	ects on fertility	:	Species: Rat Application Route Result: negative	eneration reproduction toxicity study : inhalation (vapor) on data from similar materials
Effe	ects on fetal development	:	Test Type: Embry Species: Rat Application Route Method: OECD T Result: negative	
Difl	uoromethane:			
	ects on fertility	:	Species: Mouse Application Route Result: negative Remarks: Based	: Inhalation on data from similar materials
Effe	ects on fetal development	:		
			reproduction/deve Species: Rabbit Application Route	ined repeated dose toxicity study with the elopmental toxicity screening test : inhalation (gas) est Guideline 414



ersion 7	Revision Date: 04/18/2022	SDS Nu 1349484		Date of last issue: 08/16/2021 Date of first issue: 02/27/2017
Repro sessr	oductive toxicity - As- nent		ght of evider ve toxicity	nce does not support classification for repro-
	F-single exposure lassified based on availa	ble inform	nation.	
Com	ponents:			
1,1,1,	2-Tetrafluoroethane:			
	es of exposure ssment	: No s		ealth effects observed in animals at concentra
2,3,3,	3-Tetrafluoropropene:			
	es of exposure ssment	: No s	ation (gas) ignificant he of 20000 p	ealth effects observed in animals at concentra pmV/4h or less
Diflu	oromethane:			
	es of exposure ssment	: Nos		ealth effects observed in animals at concentra
	F-repeated exposure lassified based on availa	ble inform	nation.	
Com	ponents:			
1,1,1,	2-Tetrafluoroethane:			
	es of exposure ssment	: No s		alth effects observed in animals at concentra
2,3,3,	3-Tetrafluoropropene:			
	es of exposure	: inhal	ation (gas)	
	ssment	: No s tions	ignificant he of 250 ppm	ealth effects observed in animals at concentra
Asses		: No s tions	ignificant he of 250 ppm	ealth effects observed in animals at concentra V/6h/d or less.
Asses Diflue Route	ssment	tions : inhal : No s	of 250 ppm ation (gas) ignificant he	ıV/6h/d or less.
Asses Diflue Route Asses	oromethane: es of exposure	tions : inhal : No s	of 250 ppm ation (gas) ignificant he	alth effects observed in animals at concentra
Asses Diflue Route Asses Repe	oromethane: es of exposure ssment	tions : inhal : No s	of 250 ppm ation (gas) ignificant he	vV/6h/d or less. ealth effects observed in animals at concentra
Asses Diflue Route Asses Repe <u>Com</u>	oromethane: es of exposure ssment ated dose toxicity	tions : inhal : No s	of 250 ppm ation (gas) ignificant he	vV/6h/d or less. ealth effects observed in animals at concentra



Opteon[™] XP40 (R-449A) Refrigerant

Ver 9.7	sion	Revision Date: 04/18/2022	-	DS Number: 49484-00049	Date of last issue: 08/16/2021 Date of first issue: 02/27/2017
		ation Route ure time d	:	inhalation (gas) 2 y OECD Test Guide	eline 453
	2,3,3,3	-Tetrafluoropropene:			
		L - ation Route ure time	: :	Rat, male and fer 50000 ppm >50000 ppm inhalation (gas) 13 Weeks OECD Test Guide	
	Pentaf	luoroethane:			
		L ation Route ure time		Rat >= 50000 ppm inhalation (gas) 13 Weeks OECD Test Guide	eline 413
	Difluo	romethane:			
		L - ation Route ure time		Rat, male and fer 49100 ppm > 49100 ppm inhalation (gas) 13 Weeks OECD Test Guide	
	Aspira	tion toxicity			
	•	ssified based on availa	able	information.	
	Comp	onents:			
	4 4 4 9	Totrofluoroothonou			

1,1,1,2-Tetrafluoroethane:

No aspiration toxicity classification

2,3,3,3-Tetrafluoropropene:

No aspiration toxicity classification

Difluoromethane:

No aspiration toxicity classification

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

1,1,1,2-Tetrafluoroethane:

Toxicity to fish

: LC50 (Oncorhynchus mykiss (rainbow trout)): 450 mg/l Exposure time: 96 h



Versic 9.7	on	Revision Date: 04/18/2022		9S Number: 49484-00049	Date of last issue: 08/16/2021 Date of first issue: 02/27/2017
				Method: Regulation	on (EC) No. 440/2008, Annex, C.1
	Toxicity to daphnia and other aquatic invertebrates		:	Exposure time: 48	agna (Water flea)): 980 mg/l 3 h on (EC) No. 440/2008, Annex, C.2
	Toxicity to algae/aquatic plants		:	ErC50 (green alga Exposure time: 96 Remarks: Based o	
2	2,3,3,3-	Tetrafluoropropene:			
		to fish	:	LC50 (Cyprinus ca Exposure time: 96 Method: OECD Te	
		to daphnia and other invertebrates	:	EC50 (Daphnia m Exposure time: 48 Method: OECD Te	
	oxicity	to algae/aquatic	:	EC50 (Selenastru Exposure time: 72 Method: OECD Te	
				NOEC (Selenastre Exposure time: 3 Method: OECD Te	
P	Pentafl	uoroethane:			
		to fish	:	Exposure time: 96	hus mykiss (rainbow trout)): > 100 mg/l 5 h on data from similar materials
		to daphnia and other invertebrates	:	Exposure time: 48	agna (Water flea)): > 100 mg/l 3 h on data from similar materials
	oxicity lants	to algae/aquatic	:	mg/l Exposure time: 72 Method: OECD Te	
				mg/l Exposure time: 72 Method: OECD Te	
C	Difluor	omethane:			
Т	oxicity	to fish	:	LC50 (Fish): 1,50 Exposure time: 96 Method: ECOSAF ships)	

SAFETY DATA SHEET



ersion .7	Revision Date: 04/18/2022		98 Number: 49484-00049	Date of last issue: 08/16/2021 Date of first issue: 02/27/2017
	ity to daphnia and other ic invertebrates	:	EC50 (Daphnia) Exposure time: 4 Method: ECOSA ships)	
	Toxicity to algae/aquatic plants		EC50 (green alg Exposure time: 9 Method: ECOSA ships)	
Persi	stence and degradabil	ity		
<u>Com</u>	oonents:			
	2-Tetrafluoroethane: gradability	:		ily biodegradable. Test Guideline 301D
	3-Tetrafluoropropene: gradability	:		ily biodegradable. Test Guideline 301F
Penta	afluoroethane:			
Biode	gradability	:	Biodegradation: Exposure time: 2	
Difluc	oromethane:			
Biode	gradability	:		ily biodegradable. Test Guideline 301D
Bioad	cumulative potential			
<u>Com</u>	oonents:			
1,1,1,	2-Tetrafluoroethane:			
Bioac	cumulation	:	Remarks: Bioaco	cumulation is unlikely.
	ion coefficient: n- ol/water	:	log Pow: 1.06	
2,3,3,	3-Tetrafluoropropene:			
	cumulation	:	Remarks: Bioaco	cumulation is unlikely.
	ion coefficient: n- ol/water	:	log Pow: 2 (77 °l	F / 25 °C)
Penta	afluoroethane:			
Partiti	ion coefficient: n-	:	Pow: 1.48	
			18 / 22	



Version 9.7	Revision Date: 04/18/2022	SDS Number: 1349484-00049	Date of last issue: 08/16/2021 Date of first issue: 02/27/2017	
octan	ol/water	Method: OECE	0 Test Guideline 107	
Partit	oromethane: ion coefficient: n- ol/water	: log Pow: 0.714		
	lity in soil ata available			
	r adverse effects ata available			
SECTION	13. DISPOSAL CON	SIDERATIONS		
Dispo	osal methods			

Waste from residues	:	Dispose of in accordance with local regulations.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty pressure vessels should be returned to the supplier. If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

: UN 1078 : REFRIGERANT GAS, N.O.S.
 (1,1,1,2-Tetrafluoroethane, 2,3,3,3-Tetrafluoropropene) 2.2 Not assigned by regulation 2.2
 : UN 1078 : Refrigerant gas, n.o.s. (1.1.1.2 Tetrofluoroethone, 2.2.2.2 Tetrofluoroethone)
 (1,1,1,2-Tetrafluoroethane, 2,3,3,3-Tetrafluoropropene) 2.2 Not assigned by regulation Non-flammable, non-toxic Gas 200
: 200
 UN 1078 REFRIGERANT GAS, N.O.S. (1,1,1,2-Tetrafluoroethane, 2,3,3,3-Tetrafluoropropene) 2.2 Not assigned by regulation 2.2



Version 9.7	Revision Date: 04/18/2022	SDS Number: 1349484-00049	Date of last issue: 08/16/2021 Date of first issue: 02/27/2017
Marin	Code ne pollutant	: F-C, S-V : no	
	sport in bulk accordir pplicable for product as	-	RPOL 73/78 and the IBC Code
Dom	estic regulation		
	D/NA number er shipping name	: UN 1078 : Refrigerant gas (1,1,1,2-Tetraf : 2.2	es, n.o.s. uoroethane, 2,3,3,3-Tetrafluoropropene)
Pack Labe ERG	ing group	Not assigned b NON-FLAMMA 126 no	
Spec	ial precautions for us	ser	
base Shee	d upon the properties o	f the unpackaged mat fications may vary by	for informational purposes only, and solely erial as it is described within this Safety Data mode of transportation, package sizes, and
This	CLA Reportable Quan material does not conta	ain any components w	
	A 304 Extremely Haza material does not conta		ith a section 304 EHS RQ.
	-		hreshold Planning Quantity ith a section 302 EHS TPQ.
	A 311/312 Hazards		ressure
SAR	A 313	known CAS nu	bes not contain any chemical components with mbers that exceed the threshold (De Minimis) established by SARA Title III, Section 313.
US S	tate Regulations		
Penn	sylvania Right To Kn	ow	
	1,1,1,2-Tetrafluor 2,3,3,3-Tetrafluor Pentafluoroethane Difluoromethane	opropene	811-97-2 754-12-1 354-33-6 75-10-5
Calif	ornia List of Hazardou	us Substances	

Difluoromethane

- **International Regulations**
- Montreal Protocol

: 1,1,1,2-Tetrafluoroethane Pentafluoroethane

75-10-5



Opteon[™] XP40 (R-449A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 08/16/2021
9.7	04/18/2022	1349484-00049	Date of first issue: 02/27/2017

Difluoromethane


Additional regulatory information

2,3,3,3-Tetrafluoropropene 754-12-1 The United States Environmental Protection Agency (USEPA) has established a Significant New Use Rule (SNUR) for one of the components in this product.

See 40 CFR § 721.10182

This material contains one or more substances which requires export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D:

SECTION 16. OTHER INFORMATION



Opteon[™] and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours [™] and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

Full text of other abbreviations

US WEEL	:	USA. Workplace Environmental Exposure Levels (WEEL)
US WEEL / TWA	:	8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% response; EMS - Extremely Hazardous Substance; ERG - Emergency Response Guide; GHS - Globally Harmonized Sys-

SAFETY DATA SHEET



Opteon[™] XP40 (R-449A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 08/16/2021
9.7	04/18/2022	1349484-00049	Date of first issue: 02/27/2017

tem; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to	:	Internal technical data, data from raw material SDSs, OECD
compile the Material Safety		eChem Portal search results and European Chemicals Agen-
Data Sheet		cy, http://echa.europa.eu/

Revision Date : 04/18/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8