



• Grill

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 10" x 10".

Blower Wheel

One piece polymeric wheel 51/8" diameter, 23/8" wide, with 48 fins.

Motor

Heavy duty, permanently split capacitor, plug-in, 4 pole motor, life time lubrication, thermally protected, suitable for continuous operation. Rated 120 volts, 60 hz.

• Fan Housing

PC/ABS polymeric, dimensions 8¹¹/₁₆" x 9¹/₈" x 4³/₄".

Duct Collar


Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

• Ventilating Area

For bathrooms up to 65 sq. ft. For other rooms up to 85 sq. ft.

• Single Pack Shipping Info

Box Dim: 11¹/₁₆" x 12" x 6⁵/₁₆" UPC: 0-8316290306-8 Shipping Weight: 5¹/₄ lbs.



SPECIFICATIONS

EXHAUST FANS

Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.



<u>Unit Mounting</u>

Designed to mount in ceilings with at least 6" of clearance. The unit is mounted directly to the joist using a separate lock-in bracket (included with unit). The housing will mount through drywall thickness up to $\frac{3}{4}$ ", with a rough-in opening of $\frac{81}{16}$ " x $\frac{9}{8}$ ".

Suitable for wall insert mounting when discharged vertically and mounted outside of shower enclosure

				EXF	ANDE	D PERI	FORM/	ANCE			
	Static Pressure (inches of w.g.)							Sones @ .1 SP	Fan Speed RPM	Maximum Fan Watts	Amps
	0	0.05	0.1	0.125	0.15	0.2	0.25				
Air Flow - CFM	79	74	70	68	66	62	55	1.5	1300	23.5	0.3
PROJECT						ARCHITE	CT				
LOCATION	ENGINEER										
CONTRACTOR						SUBMITTED BY		DATE			
FAN MODEL Number Number	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY		OPTIONAL EQUIPMENT & REMARKS		
	_ <i>energ</i>	Y STAR	1	1	1	V T	 .S.: 820 Vest Ches el: (610) 6 ax: (610)	Canada: 6 Brampton Tel: 905-4 Fax: (905)	156-2033		

Specifications subject to change without notice.