

DECK-LOCK™ COVERING SYSTEM

Installation Guide Continued

OTHER CONSIDERATIONS

1. Installation by pool professionals is recommended.
2. Covering Systems for wooden deck installations are supplied with anchors that are attached to the deck with wood screws. Otherwise, installation is the same.
3. Installation is not recommended on loose stone, interlocking brick, paving stone or lawns unless concrete footings of at least 4" diameter and 3" deep are located so that every anchor can be positioned in the center of such columns.
4. Concrete decks should be at least 4" thick.
5. Pool water level should not be allowed to fall more than 18" below the deck.
6. To maintain a taut fit, straps may require periodic adjustment.
7. It is recommended that the deck and coping areas around the pool which is under the cover be padded with foam, carpet remnants or a similar material to avoid damage to the cover from chafing. Such damage is not covered under the products warranty.
8. **WARNING:** The Covering System is one of the most secure fitting covers for swimming pools. However, **Extreme Caution** must be taken when around the pool, even when the Covering System is installed. **DO NOT** walk or allow walking on the cover. When walking on the deck around the pool, extra precautions should be taken to avoid tripping on straps, or loosening straps by stepping on them.
While the risk of a person or pet drowning is reduced when a Covering System is properly installed, it is not intended to replace careful supervision being exercised within the pool area and we therefore cannot accept responsibility for the occurrence of any form of accident or injury.
IMPORTANT: In order to prevent the brass screw and insert from seizing the plug must be kept clean at all times. When the cover is removed in the spring, wash the screw and plug, cleaning any dust or debris that has built up during the winter. It is also recommended prior to re-setting the screw to apply a lubricant.
9. The supportive strength of the Deck-Lock cover is dramatically reduced under certain situations which eliminates or voids any safety aspect of the cover. These situations are:
 - A - The conventional (standard) concrete hardware plug is the only acceptable anchor. If more than 10% of a non standard anchor such as lawn stakes, interlocking stakes, etc. the safety is void i.e. if 40 anchors required no more than 4 can be other than the concrete plug and screw.
 - B - Any distance of more than 5' that is not anchored at both ends of the straps the safety is void for the entire cover. This includes areas where the cover goes around spas, water falls, rock areas, etc.
 - C - Any non mesh covers the safety is void. This includes the solid vinyl covers and the vinyl with mesh panel covers.
10. The cover should be inspected periodically for premature wear or deterioration.



645 Needham Lane, Mississauga, Ontario, Canada L5A 1T9
430 West Oak Orchard Street, Medina, N.Y. USA 14103

DECK-LOCK™ COVERING SYSTEM

Installation Guide

Congratulations on purchasing one of the finest pool covers available. Proper installation and care of this cover will ensure many years of use. Please read these instructions completely **BEFORE** you begin.

BEFORE GETTING STARTED:

1. Check to make sure all parts have arrived with the cover.
 - The number of brass anchors, brass insert screws, strap adjustment buckles and springs should each be equal to the number of straps protruding from the edge of the cover.
 - The notched rod included is to connect the springs to the anchors and screws during installation. It is also used during removal.
2. Make sure that you have the necessary tools to complete the installation including:
 - A 3/4" concrete drill bit (diamond type recommended).
 - Heavy duty hammer drill.
 - Tape measure.
 - Chalk line and piece of chalk.
 - Hammer.
 - Wooden block (2x4 scrap will suffice).
 - 1/4" Allen Key.
3. Arranging for a helper or two will make installation faster and easier.

INSTALLATION: RECTANGULAR COVERS - The Covering System is approximately 2' longer and 2' wider than the pool area, however for a perfect fit:

1. Check the measurements of your Covering System and pool as precisely as possible. Divide the difference between the Covering System length and the pool length in half and mark the deck at the ends of the pool this distance from the pool's edge. Two well separated marks at each end will be required. (Figure 1a).
2. Snap chalk line at each end of the pool. The chalk line should extend at least 30" beyond the pool sides (Figure 1b).
3. Perform Steps 1. and 2. using the widths of the Covering System and the pool (Figure 2).
4. Locate one corner where two chalk lines cross. Starting at this crossing point measure 16" towards the end of both lines and mark these positions. Do the same at each corner of the chalked rectangle (Figure 3).
5. Drill holes in the deck at the 8 locations marked in Step 4.
IMPORTANT - the depth of the side of each hole should be 1 5/8" so that the brass anchors cannot be set too deep into the deck. A convenient way to measure the depth is to measure 1 5/8" up the side of the drill bit (do not include the portion which tapers to the point) and wrapping tape around the bit so 1 5/8" portion is below tape. When drilling, stop when the lower edge of tape gets to the deck. **CHECK** all holes carefully to ensure the depth is correct or the anchors will protrude above the deck.
6. Remove the screw of the brass anchor and insert the aluminum tamping tool into the hollow of the anchor. Place the anchor in the hole then tap the top of the aluminum tool until the brass anchor is flush with the concrete.

Figure 1 For example, if the covering system is 30' long and the pool is 28' long, the difference of 2' becomes 1' at each end.




Figure 1





Figure 2 If the Covering System is 14'2" wide and the pool is 12' wide, locate the chalk line half of the 2'2" difference of 1'1" from the sides of the pool.




Marks 1'1" from pool sides

After positions located, snap chalk lines along sides of pool making sure they extend at least 30" beyond ends of pool.

Note When installation is complete, the covering system will cover the area enclosed by the chalk lines.

Figure 3



DECK-LOCK™ COVERING SYSTEM

Installation Guide Continued

- Turn the screws out until the tops are about 3/8" above the deck surface.
- Strap adjustment buckles and springs are now attached to the Covering System. To prolong the life of the cover, rub strips are attached to the underside of the cover where the straps would otherwise make contact with the deck and coping. The buckles are to be used with the edges pointing downward. From beneath the buckle feed the strap up through the first slot then down through the center slot. Now feed the strap through the squared end of a spring then up through the center slot and down through the third slot. Repeat until all springs and buckles are attached (Figure 4).
- The Covering System is now positioned on the pool by hooking the 2 straps at each corner to the corresponding anchors installed in Step 6. The notched rod is used to tension the springs over the brass screws by inserting the rod through the round end of a spring, placing the tab over the end of the screw and pulling the rod to just beyond a vertical position. This compresses the spring and guides it over the top of the screw with minimal effort. Turning the rod until the tab faces the pool will allow removal of the rod without disturbing the spring.
- Adjust the 8 straps until the edges of the Covering System are aligned with the chalked lines placed earlier and the springs are compressed by about 50%.
- Snap new chalk lines 16" from the outer edge of the Covering System.

NOTE: the ends should be at anchors already in place (Figure 5).
- Extend the straps at the ends of the pool and determine where these would cross the new chalk lines. Mark these locations, drill, insert anchors and screws and hook springs over screws adjusting as needed to keep the Covering System within the chalk lines placed earlier (Figure 6).
- Repeat Step 12 along the sides. Adjust the straps so that the shorter ones are not pulling the longer ones off line. Your installation is now complete.

FOR RECTANGLES WITH STEP SECTION:

- If the step section is offset from a corner, complete the installation of the Covering System identical to the above Steps 1 through 13.
- The step section, which is a flap attached to the main body cover, can be fastened down by placing your 4 plugs for the two corners similar to that of installing the main cover.

FOR RECTANGLES WITH CORNER STEP SECTIONS:

- If the step section is exactly at a corner, the area must be treated as the widest part when determining the Covering System location as per Figure 1 and Figure 2.
- With this type of step section the pool and Covering System have 5 corners which must be marked as in Figure 3.
- All other installation steps are the same as listed when installing a straight rectangle.

Figure 4




Figure 5 Place chalk lines for locating the placement of the remaining anchors.





Figure 6 Using unattached straps, mark for brass anchor placement.



DECK-LOCK™ COVERING SYSTEM

Installation Guide Continued

INSTALLATION OF OTHER SHAPES

- Thoroughly review the procedures for installing a rectangular Covering System to become familiar with the parts and processes involved.
- Attach springs and buckles to straps.
- Position the Covering System over the pool ensuring that the extra material is even around the perimeter.

HINT: Use a piece of chalk to mark the deck at 3' - 4' intervals around the pool, 16" from the edge to use as a guide (Figure 7).
- Temporarily secure the cover by placing weights on a few of the straps (Figure 8.).
- Locate one of the longest straps near the center of the cover, measure, mark and drill at both ends 16" from the edge of the cover in line with the strap. Allow a little more than 16" to compensate for any sagging in evidence (Figure 7).
- Insert anchors, attach springs and perform any adjustment necessary.
- Repeat Steps 5 and 6 using a centrally located strap which crosses the first one installed, adjusting the shorter strap so that the first one is straight and not pulled to one side or the other (Figure 8a).
- Working from the center straps toward the edge straps, positions for the anchors are located and drilled, plugs inserted, springs connected and straps adjusted to ensure that previously attached straps are not pulled out of position. To assure best fit, it is recommended that after the first two straps are fastened you proceed by fastening a long strap on either side of the center one, then a short strap on either side of the center one, then two more long ones and so on until all straps are secure (Figure 8b). This will minimize buckling or puckering of the material and result in the neatest installation possible.

COVERING SYSTEM REMOVAL

- With the notched rod held vertically, place it over the top of a brass insert screw ensuring that the protruding tab at the end of the rod is on the side of the screw nearest the pool.
- Turn the rod 180° or a half turn, keeping the tab on the rod between the spring and the screw.
- Leaning the top of the rod toward the pool will disengage the spring and it will slide up the rod a small distance. Proceed around the pool until one end of each strap is disconnected. The opposite end of each strap can now be removed by hand.
- Remove the cover, clean, dry and pack. Store where not exposed to the sun and in a location where not accessible to rodents.
- Use Allen Key to turn brass screws down into the anchors.

NOTE: To prevent dust, dirt etc. from damaging the plug threads it is advisable to coat the screw with a household lubricant.

Figure 7 Marking for placement of shaped or irregular Pool Covering System.




Figure 8 Attaching the initial straps.




Figure 8 a) Locate brass anchor placement of straps on either side of center strap, drill and install anchors. Secure straps. **Note** Adjust to make sure cross strap remains straight.




Figure 8 b) Locate brass anchor placement of straps on either side of the first cross strap installed. Drill and install anchors. Secure straps and adjust.