

SAFETY JOGGER

INDUSTRIAL

HEAVY DUTY

MARS-EH SB

EH-rated, high-cut puncture and slip resistant safety shoe

Upper	Corrected Nappa Leather
Outsole	PU/TPU
Toecap	Composite
Midssole	Textile
Lining	Mesh
Footbed	SJ foam footbed
Safety category	EN ISO 20345 - SB / P, SRC, E, FO
Sample weight	0.741 gr.
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 / CM 23.5-31.0



858




ELECTRICAL HAZARD (EH)

Electrical hazard (EH) rated safety shoes have nonconductive outsoles. As a secondary source of protection they reduce the potential for electric shocks under dry conditions.



COMPOSITE TOECAP

Metalfree and lightweight, no thermal or electrical conductivity




SJ FLEX

Metalfree puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.



WATER RESISTANT UPPER (WRU)

Prevents penetration of water if not permanently exposed to high levels.



METAL FREE

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.

SAFETY JOGGER

INDUSTRIAL

HEAVY DUTY

MARS-EH SB

Industries:

Automotive, Chemical, Construction, Industry, Logistics, Mining, Oil & Gas

Environments:

Dry environment, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



	Description	Measure unit	Result	EN ISO 20345
Upper	Corrected Nappa Leather			
	Upper: permeability to water vapor	mg/cm ² /h	2.0	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	16.3	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	51.9	≥ 2
	Lining: water vapor coefficient	mg/cm ²	415.5	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	PU/TPU			
	Outsole abrasion resistance (volume loss)	mm ³	41.8	≤ 150
	Outsole slip resistance SRA: heel	friction	0.37	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.32	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.16	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	NA	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
	Heel energy absorption	J	35	≥ 20
Toecap	Composite			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	16.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	21.0	≥ 14

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:
42