TECH-DRY BUILDING PROTECTION SYSTEMS PTY. LTD.

ACN 005 307 684 ABN 62 922 836 289

177-179 Coventry Street,

South Melbourne, Victoria 3205, Australia Telephone: 61 3 9699 8202 (all hours)

Facsimile: 61 3 9696 3362 Website: www.techdry.com.au E-mail: info@techdry.com.au



MATERIAL SAFETY DATA SHEET

STABILISED EARTH WATER REPELLENT WB

Page 1 of 2

Issued: 01/01/2022

Not classified as hazardous according to criteria of WorkSafe Australia

Identification Product name: STABILISED EARTH WATER REPELLENT WB

Other names: Silane/siloxane water repellent

Manufacturer's code:
UN number:
D.G. class:
Subsidiary risk:
Hazchem code:
Poisons schedule no:
Not allocated

Use Silane/siloxane ready-to-use emulsion as a water repellent impregnant for stabilised or

rammed earth substrates.

Physical properties Appearance: Milky white emulsion

Boiling point: ≥100 °C

Vapour pressures (20 °C): Not allocated

Density (20 °C): 1.0 g/ml

Flash point: >62 °C

Flammability limits (%): Not allocated

Solubility in water: Miscible

Other properties Autoignition point: Not allocated

Vapour density (air=1): Not allocated

pH: 7-8 Viscosity (20 °C): n/a

Ingredients	Chemical entity	CAS number	Proportion
	Silane/siloxane mixture	n/a	<10%
	Water		To 100%

Hazard Health Information

Health Effects: To the best of our knowledge, the adverse health effects of this product as a whole

have not been determined. However, normal industrial hygiene measures should be

followed when handling chemicals.

Acute:

Swallowed: Harmful if swallowed. It may cause irritation to mouth, throat and stomach.

Eye: Silane/siloxanes may cause eye irritation.

Skin: Silane/siloxanes may be irritating to the skin.

Inhaled: It may cause irritation to the mucous membranes and respiratory tract. Over exposure

can result in drowsiness, nausea, vomiting and dizziness. An aerosol mist of the silane

and siloxane may cause lung damage if inhaled.

Chronic: Not known.

First Aid:

Swallowed: If swallowed, do not induce vomiting. Give a glass of water. Never give anything by

mouth to an unconscious person. Get prompt medical attention.

Eye: Flush eyes with copious amounts of water for at least 15 minutes. Obtain medical

attention.

Skin: Remove contaminated clothing and wash skin thoroughly. Wash clothing before reuse.

Seek medical advice if effects persist.

Inhaled: Remove affected victim from exposure area to fresh air. If not breathing, give artificial

respiration. If breathing is difficult, give oxygen. Seek prompt medical advice.

First Aid Facilities: Washing facilities are strongly recommended for handling chemicals.

Advice to Doctor: Treat symptomatically.

Precautions For Use

Exposure Standards: There is no data allocated with this product. A small amount of methanol and ethanol

may release from the hydrolysis of the silane, the standard exposure: methanol:

200mg/m³ (TWA) and 250mg/mm³ (STEL) skin and ethanol: 1000ppm (TWA).

Engineering Controls: Keep away from sources of ignition. Take precautionary measures against static

discharges. Provide sufficient ventilation. Use local exhaust ventilation if need.

Personal Protection: Wear chemical resistant safety glasses or goggles, gloves and protective clothing.

Wear approved respiratory protection (AS1716/1715) if there is a risk of exposure to

intensive vapour concentrations. Wash hands after handling.

Flammability: This product contains low concentration of organic liquid and is not flammable. Avoid

heat and ignition sources. Use only in well ventilated areas.

Safe Handling Information

Storage and Transport: Consult AS1940 and relevant state or territory regulations on safe storage and

handling. Store under 25°C in a cool and well-ventilated area away from any heat and

ignition sources.

Spills and disposal: Wear full protective clothing while attending to spills. Extinguish all ignition sources.

Prevent entry into drainage systems, sewers and waterways. Dam and collect with inert absorbent material such as sand or earth. Ensure waste disposal conforms to

local waste disposal regulations.

Fire/Explosion Hazard: Shut and remove ignition sources if safe to do so. Use dry powder, sand, and foam

and/or carbon dioxide extinguisher. Wear a breathing apparatus and full protective measures while attending to the hazard. Prevent the product from entering drains or waterways. Hazard decomposition products may include carbon oxides, silicone

dioxide and traces of formaldehyde.

Other Information

Toxicity data: There is no toxicity data allocated for this product. However, any chemicals should

be handled according to relevant government or state or territory regulations on safe storage and handling. Do not introduce large amounts of silane/siloxanes into

purification plants, waterways and soil.

<u>Contact Point</u> For further information please contact Tech-Dry tel: 61 3 9699 8202 (all hours).

Important Note

To the best of our knowledge, the information sources for the preparation of this document were correct and complete at the time of writing. The information is therefore subject to possible change from time to time and cannot be guaranteed. This document should be taken as a safety guide for the product and its recommended uses but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product or any material existing within the product. For further information, please contact Tech-Dry Building Protection Systems Pty. Ltd.