

BELT DRIVE

NOW IMPROVED WITH THESE QUALITY FEATURES!

Available in: 24 in., 30 in., 36 in.



RE-ENGINEERED BRACING SYSTEM: Creates a more stable motor mount and virtually eliminates vibration

DUAL BALL BEARING TECHNOLOGY: Allows for superior shaft alignment and greater stability

DIRECT DRIVE

POPULAR CHOICE!

Available in: 24 in, 30 in.



FEATURES OF BELT + DIRECT DRIVE FANS:

- 1 Two-speed thermally protected PSC motors
- 2 Precision-balanced aluminum fan blade assembly
- 3 Four fan blades (unlike 3 in competing brands) for greater air movement
- 4 Steel venturi for enhanced durability
- 5 White, powder coated finish automatic shutter (included) has 95% plus air closure

UPGRADE YOUR FAN UNIT WITH WIRELESS CONTROLS! MODELS: CX24BDM-2SPDHUB, CX30BD-2SPDHUB, CX36BD2SPDHUB, CX242DDWTHUB, CX302DDWTHUB

	MODEL	SQ. FT. OF AREA TO BE VENTILATED	CFM	NET FREE AREA EXHAUST REQUIRED
DIRECT DRIVE	CX242DDWT	UP TO 1800 SQ. FT.	2,090 LOW / 2,985 HIGH	8 - 10 SQ. FT. (1,152 - 1,440 SQ. IN.)
	CX302DDWT	2,000 - 3,000 SQ. FT.	UP TO 4,425	10 - 12 SQ. FT. (1,440 - 1,728 SQ. IN.)
BELT DRIVE	CX24BDM-2SPD	1,200 - 1,800 SQ. FT.	UP TO 3,092	8 - 10 SQ. FT. (1,152 - 1,440 SQ. IN.)
	CX30BD-2SPD	2,000 - 3,000 SQ. FT.	4,160 LOW / 5,950 HIGH	10 - 12 SQ. FT. (1,440 - 1,728 SQ. IN.)
	CX36BD2SPD	OVER 3,000 SQ. FT.	6,800 LOW / 9,700 HIGH	12 - 14 SQ. FT. (1,728 - 2,016 SQ. IN.)

PERFECT FOR:



HOME



2-SPEED & ON/OFF WALL SWITCH



WIFI-OPERATION AVAILABLE



REDUCES COOLING COSTS



JOIST-IN & JOIST-OUT COMPATIBLE