evochlor®

SALT WATER CHLORINATORS







- Proven Reliability
- **☑** Battery Backup Timeclock
- **▼** 100% Australian Made
- **▼** Salt and Mineral Compatible
- 3 Year FULL Warranty



WATER & LIGHTING SOLUTIONS

www.evolutionwls.com.au

The Evochlor Series salt water chlorinator has been stringently designed, engineered and built for the toughest Australian conditions. Now with advanced microprocessor control, brown energy protection and mineral salt compatibility, this work horse is better than ever.

EVOCHLOR CHLORINATOR



SALT WATER CHLORINATORS

The Evochlor Advantage

- Wholly developed and manufactured in Australia.
- Proven reliability, even in the harshest Australian conditions.
- Salt and mineral salt compatibility.
- Advanced microprocessor controlled PCB.
- Brown energy and overload protection.
- Low salt operation of 3500 to 4500ppm.
- Over salt warning light.
- Bright display LEDS.
- External reset button (no internal fuse).
- 10% incremental adjustable chlorine output.
- Simple to set analogue time clock with battery backup.
- Energy efficient design with low kW use.
- High grade long lasting electrolytic plates.
- UV and impact resistant cell housing.
- Easy to install into new or existing pools.
- Optional Wireless models available with remote / app enabled control.

Warranty

- 3 year full warranty on Power Pack.
- 3 year full warranty on Electrolytic Cell.
- 12 months for commercial installations.

Why Chlorination

- No need to buy, transport and store hazardous liquid chlorine.
- No more sore eyes or irritated skin.
- Complete sanitisation that kills bacteria and prevents algae.
- Safe sparkling water all year round.
- Suitable for all pool types.





Specifications

M	lodel	Output (g/h)	Power Use (kW)	Cell Plumbing	Wireless Remote	Pool Size (L) Temperate Climate	Pool Size (L) Tropical Climate
A	15TS	15	.20	40/50	-	45,000	30,000
A	20TS	20	.20	40/50	Optional	65,000	50,000
A:	25TS	25	.20	40/50	Optional	80,000	65,000
A:	30TS	30	.35	40/50	Optional	100,000	85,000
A :	35TS	35	.35	40/50	Optional	120,000	100,000
A	.50G	50	.35	40/50	-	150,000	130,000

The above values are based on standard residential installations. For commercial applications please contact your authorised dealer.

