



## CLASSIC RP SERIES

SALT WATER ELECTROLYSERS  
CHLORINE GENERATORS

- Reverse polarity (reduced maintenance)
- The reversing action de-scales the build-up of calcium and reduces electrode cleaning maintenance by 95%
- Powered by transformer power supply
- Salinity 5,000 ppm
- Warranty: Residential application - 3 years, Commercial application - 1 year

MODEL	CHLORINE	INPUT AC POWER CONSUMPTION	WATER FLOW	DIMENSION (PACKAGED)	WEIGHT GROSS
	Grams / Hour	kW	Litres / Minute	L x W x H (cm)	Kg
RPMINI	5	0.070	200-400	37 x 31 x 22	11
RP7	7	0.100	200-400	39 x 19 x 30	5.5
RP15	15	0.215	200-400	37 x 31 x 22	11
RP20	20	0.290	200-400	37 x 31 x 22	11
RP25	25	0.360	200-400	37 x 31 x 22	11
RP36	36	0.290	200-400	37 x 31 x 22	11
RP50	50	0.760	200-400	43 x 33 x 27	27
RP64	64	0.505	200-400	43 x 33 x 27	27

**OPTIONS (AVAILABLE TO AUSTRALIAN CUSTOMERS ONLY)**

PREFIX	DESCRIPTION	ADDITIONS AVAILABLE FOR
T	Timer Option	Mini/15/20/25/36/50/64
QT	Timer With Battery Back Up	Mini/15/20/25/36/50/64
L12	Underwater Light Option 12V	Mini/15/20/25
L24	Underwater Light Option 24V	Mini/15/20/25
L32	Underwater Light Option 32V	Mini/15/20/25



NB: When ordering desirable model with options, simply add prefix to the model code. Example: AC25 TL12. Spare parts readily available including replacement cells. Recommended TDS level for AutoChlor operation: 5,000ppm\*