

# FEDPRO™

TRUSTED BRANDS SINCE 1915



DISTRIBUTOR CATALOG 2023

# SINCE 1915

**FEDPRO**<sup>™</sup>  
TRUSTED BRANDS SINCE 1915



Formerly  
**FEDERAL PROCESS  
CORPORATION**

Located and manufactured in Cleveland, Ohio, FedPro<sup>™</sup>, formerly known as Federal Process Corporation, first introduced Gasoila<sup>®</sup> Hard-Set thread sealant in 1915. Since then, FedPro has grown to include a diversified portfolio of trusted, leading products including thread sealants, premium cleaners, lubricants, and more.





**FEDPRO**  
TRUSTED BRANDS SINCE 1915

#### THE FEDPRO DIFFERENCE

Just as we did over 100 years ago, we proudly manufacture small batches of our products to meet the high quality standards set by our founders and trusted by our customers. Our premium cleaners, thread sealants, PTFE tapes and lubricants have become the products of choice in the petroleum, plumbing, LP gas, automotive, hardware, household and consumer, and general industrial markets.

## SOFT-SET Thread Sealant with PTFE



## HARD-SET Thread Sealant



## PLS® 2 Thread & Gasket Sealer



Stock Code	Container Size	Units per Case
SS01	1/8 oz. Tube	100
SS02	2 oz. Tube/Counter Disp.	24
SS04	1/4 pt. Brush	24
SS08	1/2 pt. Brush	24
SS16	1 pt. Brush	12
SS32	1 qt. Flat Top	6
SB32	1 qt. Brush	6
SS28	1 Gallon	2



- Soft-setting, PTFE paste
- Provides a positive seal on pipe threads, joints, fittings, hoses, nozzles, LPG cylinders, pump assemblies, oil burners, hydraulics, compressors, engines, motors, housings, plugs, fuel lines, couplings and more
- Use on brass, copper, stainless steel, aluminum, black pipe, tin, galvanized, iron, most plastics and more. Check with plastic pipe manufacturer to determine compatibility with Gasoila® Soft-Set.
- Excellent resistance to gasoline (up to 20% ethanol and petroleum blends), petroleum solvents, kerosene, diesel oil, propane, butane, LPG, cutting oils, ammonia, aliphatic solvents, acids, steam, potable water, compressed air and more. NOT for use with oxygen.
- Remains pliable in cold temperatures
- Temperature Range: -100°F to 600°F (-75°C to 315°C)
- Pressure Range: To 10,000 PSI (689 bar) sealing liquids; to 3,000 PSI (206 bar) sealing gases
- One year shelf life when stored at 40°F to 80°F (5°C to 27°C)

Stock Code	Container Size	Units per Case
BT04	1/4 pt. Brush	24
BT08	1/2 pt. Brush	24
BT16	1 pt. Brush	12
FT32	1 qt. Flat Top	6
FT28	1 Gallon	2



- Hard-setting, fast-drying, red varnish sealant
- Use on brass, copper, stainless steel, aluminum, black pipe, galvanized pipe, rubber, porcelain, wood, marble, epoxy, cork, plexiglass, paper, felt and more
- NOT for use on plastic
- Excellent resistance to all aliphatic, aromatic, chlorinated solvents; naphtha, benzenes, all petroleum products, refrigerants, propane, butane, kerosene, jet fuel, water, steam and more
- NOT for use on alcohol content over 20%
- NOT for use with oxygen
- Temperature Range: -60°F to 350°F (-51°C to 177°C)
- Pressure Range: To 500 PSI (34 bar) sealing face or butt joints; to 15,000 PSI (1034 bar) for threaded connections
- Dries to touch within 30 minutes; do not pressurize until cured, usually 24-48 hours
- One year shelf life when stored at 40°F to 80°F (5°C to 27°C)
- Flammable

Stock Code	Container Size	Units per Case
PB04-N	1/4 pt. Brush	24
PB16-N	1 pt. Brush	6
PL28-N	1 Gallon	2



- Textured, non-hardening, opaque gray paste
- Adheres readily to iron, stainless steel, aluminum, Monel, most plastics and synthetic rubber compounds. Check with plastic pipe manufacturer to determine compatibility with PLS 2.
- For use with dilute acids, aliphatic solvents, ammonia, dilute caustic alkali, diesel fuel, gasoline, kerosene, jet fuel, LPG, natural gas, petroleum solvents, heating oils, butane, hydraulic oils, mineral oils, refrigerants and steam
- NOT for use with oxygen
- Brush on to seal pipe joints, plugs, screwed fittings and gasketed connections in steam systems, refineries, gas service, refrigeration systems and chemical plants
- Temperature Range: -100°F to 600°F (-73°C to 315°C)
- Pressure Range: To 10,000 PSI (689 bar) sealing liquids; to 3,000 PSI (206 bar) sealing gases
- One year shelf life when stored at 40°F to 80°F (5°C to 27°C)

## 100 Thread Sealant



Stock Code	Container Size	Units per Case
GH04	1/4 pt. Brush	12
GH08	1/2 pt. Brush	12
GH16	1 pt. Brush	6

- Firm-setting, viscous, textured, black sealant
- Excellent performance with systems handling alcohols & ideal for concentrated or dilute acids & caustic alkali, compressed air, aromatic solvents, glycol/water solutions, coal tar, naphtha, cutting oils, ethylene glycol, gasoline and ketones
- NOT for use with oxygen
- NOT for use on plastic pipe
- Temperature Range: -50°F to 450°F (-45°C to 232°C)
- Pressure Range: To 5,000 PSI (344 bar) for gases; to 10,000 PSI (689 bar) for liquids
- One year shelf life when stored at 40°F to 80°F (5°C to 27°C)

## E-SEAL Thread Sealant with PTFE



Stock Code	Container Size	Units per Case
GE04	1/4 pt. Brush	24
GE08	1/2 pt. Brush	24
GE16	1 pt. Brush	12



- Non-hardening, opaque, viscous, textured, green paste designed specifically for ethanol blended gasoline including E10 and E85
- Provides a positive seal on pipe threads, joints, fittings, hoses, nozzles, pump assemblies, oil burners, hydraulics, bolts, compressors, engines, motors, fuel lines and couplings
- For use on brass, copper, stainless steel, aluminum, black pipe, tin, iron and galvanized pipe
- Excellent resistance to gasoline, ethanol blended gasoline such as E10 and E85, petroleum solvents, kerosene, diesel oil, up to 20% biodiesel, propane, jet fuels, butane, LPG, cutting oils, ammonia, aliphatic solvents, acids, steam and potable water
- NOT for use with oxygen
- Temperature Range: -100°F to 600°F (-73°C to 315°C)
- Pressure Range: Up to 10,000 PSI (689 bar) when sealing liquids & up to 3,000 PSI (206 bar) with gases
- One year shelf life when stored at 40°F to 80°F (5°C to 27°C)

## DEF Diesel Exhaust Fluid Sealant



Stock Code	Container Size	Units per Case
DE04	1/4 pt. Brush	12

- DEF (Diesel Exhaust Fluid) Sealant is designed for systems carrying urea-based chemical reactant used in SCR systems
- Excellent performance with systems handling Diesel Exhaust Fluid
- For use on brass, copper, stainless steel, aluminum and iron pipe
- NOT for use on plastic pipe
- NOT for use with oxygen
- Temperature Range: -50°F to +450°F (-45°C to 232°C)
- Pressure Range: Up to 10,000 PSI (689 bar) when sealing liquids and up to 5,000 PSI (344 bar) with gases
- One year shelf life when stored at 40°F to 80°F (5°C to 27°C)

## JC-30® High-Fill Thread Sealant - PTFE



Stock Code	Container Size	Units per Case
JC04	1/4 pt. Brush	24
JC16	1 pt. Brush	12

- High viscosity, heavy-duty, PTFE thread sealant
- Ideal for use on worn, damaged or irregular threads
- Provides excellent chemical resistance in use with water, steam, corrosives, acids, petroleum products, hydraulic fluids, cryogenics, jet fuel, CNG, LP and natural gas
- NOT for use with oxygen
- Forms a protective coating for movable surfaces exposed to high humidity
- Temperature Range: -100°F to 600°F (-73°C to 315°C)
- Pressure Range: To 10,000 PSI (689 bar) for liquids; 2,000 PSI (138 bar) for gases
- One year shelf life when stored at 40°F to 80°F (5°C to 27°C)

## NT Non-PTFE Thread Sealant



Stock Code	Container Size	Units per Case
NT08	1/2 pt. Brush	24
NT16	1 pt. Brush	12



- Blue, textured, non-PTFE thread sealant
- Use on most metals and plastics. Check with plastic pipe manufacturer to determine compatibility with Gasoila® NT.
- Recommended for use with valves, fittings, hoses, nozzles, motors, housings, gaskets, compressors and castings
- Use with potable water
- NOT for use with oxygen
- Temperature Range: -50°F to 400°F (-45°C to 204°C)
- Pressure Range: To 6,000 PSI (408 bar) sealing liquids; 3,000 PSI (206 bar) sealing gases
- One year shelf life when stored at 40°F to 80°F (5°C to 27°C)

## FasSeal ATS® Anaerobic - PTFE



Stock Code	Container Size	Units per Case
AS05	50 ml Tube	10
AS25	250 ml Tube	10

- Forms a tough, insoluble, vibration-proof seal
- Allows for easy disassembly of parts when required
- High-speed curing time without shrinkage and resists galling and seizing
- For use on inactive metals as well as conventional materials
- Resistant to petroleum, butane, propane, natural gas, water, steam, refrigerants, chlorine, acids, oils, gasoline and more
- NOT for use with oxygen
- Recommended for air conditioning lines, hydraulic and pneumatic lines, air compressor hoses, plated flare fittings, sprinkler installations, housings, plugs, pipe threads, fuel lines, steam lines, natural gas lines
- Temperature Range:  
-65°F to 400°F (-54°C to 204°C)
- Pressure Range: Seals to 10,000 PSI (689 bar) after application and then to the bursting strength of the pipe after curing
- One year shelf life when stored at 40°F to 80°F (5°C to 27°C)

**WARNING:** This product can expose you to cumene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## Zip Joint® Rope Gasket Maker - PTFE



Stock Code	Container Size	Units per Case
ZJ11	3/32" Dia. x 25' Coil	6
ZJ13	5/32" Dia. x 25' Coil	6

- Ideal for packing valves and faucets
- Quickly makes any gasket
- Simple and clean installation
- Spreads under compression to conform to odd shapes
- PTFE sealing agent withstands vibration
- Unique package allows for easy dispensing and storage
- Temperature Range:  
-400°F to 500°F (-240°C to 260°C)
- Pressure Range:  
To 500 PSI (34 bar) under general use

# Gasoila® PTFE Tapes - Industrial Strength



## Thred Tape HD High Density

## Thred Tape MD Medium Density

## Thred Tape SD Standard Density

## Economy Tape Low Density

Stock Code	Container Size	Units per Case
TT23	3/4" x 288"	24
TT33	3/4" x 576"	24
TT38	3/8" x 520"	144
TT40	1/2" x 260"	144
TT41	1/2" x 520"	144
TT42	1/4" x 520"	144
TT43	1/4" x 260"	144
TT44	1/2" x 1296"	144

Stock Code	Container Size	Units per Case
TT53	3/4" x 260"	24
TT54	3/4" x 520"	24
TT60	1/2" x 260"	144
TT61	1/2" x 520"	144

Stock Code	Container Size	Units per Case
ZT12	3/4" x 260"	100
ZT13	3/4" x 500"	100
ZT15	3/4" x 520"	100
ZT20	1/2" x 260"	144
ZT21	1/2" x 520"	144
ZT44	1/2" x 1296"	144
ZT51	1" x 520"	100
ZT60	2" x 260"	144


Stock Code	Container Size	Units per Case
1901B	1/2" x 1296"	100
1901C	1/2" x 260"	100
1901D	1/2" x 520"	100
1901E	3/4" x 520"	100
1901F	1" x 520"	50
1901G	1" x 1296"	140
1901H	3/4" x 260"	140

- All natural PTFE
- Temperature range: -450°F to 550°F (-268° to 288°C)
- Use up to 10,000 PSI for liquids 2,000 PSI for gases
- UL® Listed thread sealant

- All natural PTFE
- Temperature range: -450°F to 550°F (-268° to 288°C)
- Use up to 10,000 PSI for liquids 2,000 PSI for gases
- UL® Listed thread sealant

- All natural PTFE
- Temperature range: -450°F to 550°F (-268° to 288°C)
- Use up to 10,000 PSI for liquids 2,000 PSI for gases
- UL® Listed thread sealant

- All natural PTFE
- Temperature range: -450°F to 550°F (-268° to 288°C)



Density Type	High	Medium	Standard
Thickness (mils)	3.9	3.5	3.5
Tensile (Min *psi)	800	800	800
UL Listed	Yes	No	No
MIL SPEC*	AA-58092	AA-58092	AA-58092
MIL SPEC*	27730A	27730A	27730A
Density (g/cm3)	0.9 - 1.2	0.8 - 1.05	0.5 - 0.9
Elongation (%)	50	50	N/A
Temp. Range (°F)	-450 to +550	-450 to +550	-450 to +550
Shelf Life	Indefinite	Indefinite	Indefinite

**PTFE TAPE SPECIFICATIONS**



- Made with 100% virgin PTFE
- Can be used with oxygen
- Meets Mil Spec MIL-T-27730-A or AA-58092

\*Meets Performance Requirements of Mil Specifications Listed.



# Gasoila® PTFE Tapes - Specialty Series



**For Oxygen  
Green**



**For Gas  
Yellow**



**For Water  
Pink**



**For Stainless Steel  
Nickel**

Stock Code	Container Size	Units per Case
GT90-24	1/2" x 260"	24
GT90	1/2" x 260"	144

- Designed for sealing oxygen based lines
- Use on all types of threaded connections
- UL® Listed thread sealant
- Meets Mil Spec MIL-AA-58092

Stock Code	Container Size	Units per Case
YT70-24	1/2" x 260"	24
YT70	1/2" x 260"	144
YT71	1/2" x 520"	100
YT75	1" x 520"	100

- Designed for chemical installations and sealing lines carrying natural gas, propane, butane and oil
- Use on all types of threaded connections
- CSA® approved
- UL® Listed thread sealant
- Meets MIL Spec MIL-AA-58092

Stock Code	Container Size	Units per Case
PT80-24	1/2" x 260"	24
PT80	1/2" x 260"	144

- Designed for sealing water and/or steam lines
- Use on all types of threaded connections
- UL® Listed thread sealant
- Meets Mil Spec MIL-AA-58092

Stock Code	Container Size	Units per Case
SA26	1/2" x 260"	40
SA26-34	3/4" x 260"	40
SA520-1	1" x 520"	40
SA260-1	1" x 260"	40
SA60	1/2" x 600"	50

- Designed for use on difficult service conditions associated with stainless steel, aluminum and brass threaded connections
- Helps prevent seizing and galling
- NOT for use with oxygen
- UL® Listed thread sealant
- Meets Mil Spec MIL-T-27730A



	Yellow	Pink/Green	Stainless
<b>Density Type</b>	High	High	High
<b>Thickness (mils)</b>	3.8	3.7	4.3
<b>Tensile (Min *psi)</b>	1600	1600	1600
<b>UL Listed</b>	Yes	Yes	Yes
<b>MIL SPEC*</b>	AA-58092	AA-58092	AA-58092
<b>MIL SPEC*</b>	27730A	27730A	27730A
<b>Density (g/cm3)</b>	1.3 - 1.45	1.25 - 1.55	1.25 - 1.55
<b>Elongation (%)</b>	75	75	75
<b>Temp. Range (°F)</b>	-450 to +550	-450 to +550	-450 to +550
<b>Shelf Life</b>	Indefinite	Indefinite	Indefinite

\*Meets Performance Requirements of Mil Specifications Listed.



## Thred Gard® Anti-Seize Lubricant



High Temperature  
1000 °F (537 °C)



High Temperature  
1800 °F (982 °C)



High Temperature  
2600 °F (1427 °C)



Nonfood Compounds  
Program Listed H2

### General Purpose

Stock Code	Container Size	Units per Case
TG04	1/4 lb. Brush	24
TG08	1/2 lb. Brush	12
TG16	1 lb. Brush	12

### Copper Based

Stock Code	Container Size	Units per Case
CG04	1/4 lb. Brush	24
CG08	1/2 lb. Brush	12
CG16	1 lb. Brush	12

### Nickel Based

Stock Code	Container Size	Units per Case
NG04	1/4 lb. Brush	24
NG08	1/2 lb. Brush	12
NG16	1 lb. Brush	12

- Provides protection against seizing, galling, rust and corrosion at three high-temperature levels

- Brush on nuts, bolts, screws, bushings, cam rollers, shafts, sleeves, couplings, conveyers, motors, pumps, turbines and valves

- Speeds assembly and facilitates disassembly

- Industry applications include steel mills, forges, foundries, die casters, refining and chemical installations, marine services, farm and construction equipment, power and utility plants, paper and pulp mills and general plant maintenance

- Non-hardening, non-dripping

- Exceeds MIL Spec MIL-A-907D

## Gasoil® Thread Cutting Oil



### Dark Cutting Oil

Stock Code	Container Size	Units per Case
WD32	1 Quart	12
WD28	1 Gallon	4

- Dark Cutting Oil - medium viscosity, mineral type oil with sulphur and lard; ideal for cutting threads in steel pipe, bolts and rods

- Premium-grade cutting oils extend die life by cleaning threads, dissipating heat and reducing friction

- Use Dark Cutting Oil on non-ferrous metals when staining isn't critical

- Products contain NO chlorine or other halogens, PCBs or heavy metals

### Light Cutting Oil

Stock Code	Container Size	Units per Case
WL32	1 Quart	12
WL28	1 Gallon	4

- Light Cutting Oil - non-staining, translucent, low-odor oil that provides protection under heavy loads and high speeds

- Premium-grade cutting oils extend die life by cleaning threads, dissipating heat and reducing friction

- Products contain NO chlorine or other halogens, PCBs or heavy metals

## Gasoil® Gas Gauging Paste



Stock Code	Container Size	Units per Case
GG25	2.5 oz. Jar	24

- Indicates level of gasoline, naphtha, kerosene, crude and refined oils, jet fuels and a range of other commonly stored liquids

- Paste will turn blue upon contact with gasoline

# Gasoila® All Purpose Water Finding Paste



- AP02 packed in color counter display



Stock Code	Container Size	Units per Case
AP02	2 oz. Tube	24



- Full color instruction sheet included in every box



- Driver-friendly flip cap

- Fast, reliable way to detect water in fuel storage tanks
- Accurately detects phase separation in ethanol blend applications
- For all petroleum fuels including blends up to 20% ethanol, diesel, kerosene, #2 Oil, JP-4, JP-5 and more
- Works in seconds
- Paste will turn yellow-green upon contact with water
- User-friendly flip cap
- Plastic tube, less mess than metal tubes

# Gasoila® Regular Water Finding Paste



- Driver-friendly flip cap



Stock Code	Container Size	Units per Case
WF25	2.5 oz. Jar	24
WT25	2.5 oz. Tube	24



- WT25 packed in color counter display



- Reformulated for better consistency and improved color change
- Quickly and accurately detects water in fuel storage tanks
- Mustard yellow paste will turn red upon contact with water
- Effective with gasoline, diesel or other hydrocarbon products, sulphuric, nitric and hydrochloric acids, ammonia, soap solutions and other chloride solutions
- User-friendly flip cap
- Plastic tube, less mess than metal tubes

# Free All® Deep Penetrating Oil

# Lube-It All® Deep Lubricating Oil



RE12

RE12-RS



✓  
**SILICONE  
FREE**

✓  
**SILICONE  
FREE**

Stock Code	Container Size	Units per Case
RE01	1.5 oz. Aerosol	12
RE06	6 oz. Aerosol	12
RE12	11oz. Aerosol	12
RE12-RS	11 oz.w/Precision Straw	12
FS16	14 oz. Liquid	12
FA28	1 Gallon	4
FA55	55 Gallon Drum	1
RE12DC	11 oz. Counter Display	12
RE12-STK	11 oz. Stack Display	60

- Free All® spreads deep into rusted or frozen parts, freeing them with ease
- Penetrates rust, scale and corrosion to free parts and assemblies
- Loosens tar, grease, carbon and graphite deposits
- Specially formulated rust eating agent is ideal for plumbing, automotive, marine and general industrial applications
- Will free up threaded pipe connections, rusted machine screws, bolts, nuts, clamps for mufflers and tail pipes, pillow blocks, universal joints and locks
- Contains NO silicones, making it safe for use in paint and body shop environments



RE12-STK



RE12DC

Stock Code	Container Size	Units per Case
LA01	1.5 oz. Aerosol	12
LA06	6 oz. Aerosol	12
LA12	11 oz. Aerosol	12

- Contains Molybdenum disulphide and graphite for superior lubricating performance
- Silicone free
- Forms a thin lubricant coating to reduce friction
- Displaces water on surfaces and repels moisture to prevent corrosion
- Penetrates through fine gaps to deliver a coating to assembled parts and obstructed surfaces
- Can be used on metal and plastic surfaces, rotating parts and gears
- Temperature Range: -30°F to 350°F (-34°C to 177°C)



**FREE ALL**  
DEEP PENETRATING OIL



**WARNING:** This product can expose you to methyl isobutyl ketone, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P66Warnings.ca.gov](http://www.P66Warnings.ca.gov).

**LUBE-IT ALL**  
DEEP LUBRICATING OIL



## Lube-It All® Multi Purpose Food Grade Lubricant



✓  
**SILICONE  
FREE**

## Lube-It All® Multi Purpose Food Grade Silicone



**15%  
SILICONE**

## Lube-It All® White Grease



✓  
**SILICONE  
FREE**

Stock Code	Container Size	Units per Case
LA450	12 oz. Aerosol	12

- NSF H1
- Silicone free
- Economical general-purpose lubricant
- Penetrates and loosens dirt
- Safe on styrenes and urethanes
- Works on paint, metal, plastic and wood
- Virtually odorless and tackless
- Temperature Range: -20°F to 500°F (-29°C to 260°C)

Stock Code	Container Size	Units per Case
LA525	11 oz. Aerosol	12

- NSF H1
- Colorless, low viscosity formula
- 15% silicone
- Stops sticking without transfer
- Temperature Range: -40°F to 450°F (-40°C to 232°C)

Stock Code	Container Size	Units per Case
WG16	11 oz. Aerosol	12

- High solid, non-staining white lithium grease
- 2x thicker vs. competitor product
- Clings to vertical surfaces
- Effective from: -20°F to 275°F (-28°C to 135°C)
- Use on chains, gears, drives, hinges and other overhead surfaces
- Forms a complete coating around moving parts
- Protects metal surfaces against rust and wear
- Safe on most plastics and painted surfaces

## Lube-It All® Heavy Duty Silicone Lubricant



Stock Code	Container Size	Units per Case
LA12SL	10 oz. Aerosol	12

- Forms a coating around moving parts
- 3x more silicone vs. competitor product
- Colorless, low viscosity formula
- Temperature Range: -40°F to 450°F (-40°C to 232°C)

# Tub O' Towels® Heavy Duty Cleaning Wipes



## 90-Count Tub

- 10" x 12" extra large heavy duty cleaning wipes are great for use on the job or at home

## 40-Count Tub

- A more portable 7" x 8" size wipe with a slim profile for the glove box, tool box or tackle box

## On-The-Go Packs

- Individually wrapped 10"x12" cleaning wipes (TW01) for on-the-go messes
- Store in tool chest, glove compartment, bags & more
- Can be pegged or sit in tray
- Available in 6-pack or 15-pack



### 100% SOLUTION SOAKED

Every wipe comes out of the container fully saturated and ready to work hard.



### DURABLE FIBER WEAVE

A special fiber weave wicks up moisture, enhances scrubbing and grabs dirt. The quilted design offers cushioning and surface texture.



### OVERSIZED, OVERACHIEVING

Bigger, stronger and tougher by design. Tub O' Towels cleaning wipes are generously sized (10" x 12" in the 90-count tub).



### TOUGH ON DIRT, GENTLE ON HANDS

Our wipes contain aloe, vitamin E and lanolin to protect hands and leave them clean and soft.



### VAPORLOCK™ CANISTER

A heavy-gauge plastic tub and locking lid minimize solution evaporation.



TW01-GR

Stock Code	Container Size	Units per Case
TW90	90 Wipe Canister	6
TW40	40 Wipe Canister	12
TW01	Single Wipe Packs	350
TW01-6	6 Pack Pouch	24
TW01-15	15 Pack Pouch	18
TW01-GR	TW01 Gravity Feed Box	1
TW90-STK	90 Wipe Floor Display	24
TW90-CD	90 Wipe Counter Display	6
TW90-P	90 Wipe Refill Pouch	8
BRKTTW90	Wall Mount Bracket	1


# TUB O' TOWELS®



# Tub O' Towels® Specialty Wipes



## For Stainless Steel



- Shines and polishes stainless steel, chrome and other metal surfaces
- Easily removes greasy fingerprints, watermarks, food, grease, oils and much more
- No streaks or residues during application
- Doesn't contain silicones, abrasives or acids



## For Granite & Marble



- Removes grime, grease and more while providing a polished surface
- Safe for stone surfaces, marble, granite, quartz, travertine, limestone, onyx, Corian®, Formica®, Silestone®, laminate, porcelain, tile, ceramic, fiberglass and any non-porous hard surface countertop
- Contains Fluoropolymer that repels water and prevents oils from sticking to the stone surface
- Will not discolor sealed grout



## For Carpet & Upholstery



- Removes the toughest stains through a blend of cleaners designed to clean carpet and upholstery
- Attacks soils embedded in close-knit fibers of carpet and upholstery
- Removes pet stains, food stains, grass stains, blood, grease, beverages, latex paint, cosmetics, ink, crayons, shoe polish and other water-based stains
- Available in packaging for automotive industry (#TW40-CPA)



## For Chrome & Wheels



- Returns the luster to polished metal surfaces
- Cleans, shines and protects wheels, trim, bumpers and exhaust tips
- Removes fingerprints, water marks, greasy stains and soil
- Leaves a brilliant, streak-free shine
- For chrome, aluminum, copper, diamond plate, brass and other metal surfaces

### Individually Wrapped Single Wipe Packs



Stock Code	Container Size	Units per Case
TW40-SS	40 Wipe Canister	12
TW01-SS	Single Wipe Packs	350
TW40-GR	40 Wipe Canister	12
TW01-G	Single Wipe Packs	350
TW40-CP	40 Wipe Canister	12
TW01-CP	Single Wipe Packs	350
TW40-CPA	40 Wipe Canister	12
TW40-CHR	40 Wipe Canister	12
TW01-CHR	Single Wipe Packs	350

# Gasoil® Extreme Temperature Leak Detector

# Tub O' Scrub® Heavy Duty Hand Cleaner



Stock Code	Container Size	Units per Case
LT08	8 oz. w/Dauber	12
LS16	1 pt. Spray Bottle	12
LT28	1 Gallon	4
LT55	55 Gallon Drum	1

Stock Code	Container Size	Units per Case
TS18	18 oz. Bottle	12
TS64	1/2 Gallon Pump	4
TS28	1 Gallon Pump	4
TS01	0.3 oz Single Pack	350
TS01-GR	Gravity Feed Box	100
TS18-FD	Floor Display	32
TS64-FD	Floor Display	24
BRCKTTS28	Wall Mount Bracket	1

• Gasoil® Extreme Temperature Leak Detector is specifically engineered for use on gas lines, gas cylinders, refrigeration condensers, air lines, air pumps or any other system carrying gas

- Non-corrosive
- Temperature Range: -10°F to 350°F (-23°C to 177°C)
- NOT for use on oxygen systems



**NO**  
Petroleum  
Distillates  
or Pumice

- Unique biodegradable formula
- Removes grease, oil and tough grime without water
- Walnut shell formula will NOT block drains or septic tank systems
- Other formulas contain low-cost pumice that can clog drains or septic systems
- Walnut shells completely sanitized and safe for use
- Contains NO petroleum distillates, which can be harmful to skin, water and septic systems
- Lotion-like formula
- Lanolin, aloe vera, and vitamin E among other emollients that leave hands soft and moisturized after use



## FasMark® Cap & Cover Paint



Stock Code	Color Use	Units per Case
● FM15O	Vapor Recovery Orange	12
● FM15Y	Diesel Yellow	12
● FM15BR	Kerosene Brown	12
● FM15R	Premium Red	12
● FM15G	Heating Oil Green	12
● FM15BL	Mid-Grade Blue	12
● FM15BRZ	Bronze	12
○ FM15W	Unleaded White	12
● FM15B	Black	12

- 15 oz. aerosol
- Permanent, upside down paint
- Spray-through cap saves time
- Direct to metal
- Apply to clean, dry surface
- High solid, highly pigmented formula
- Bright long lasting color
- Quick dry formula – 8 to 10 minutes
- VOC compliant

#### Use On:

- Manhole Covers
- Tank Valves
- Island Forms
- Structural Steel
- Storage Tanks
- Equipment




**WARNING: Cancer and Reproductive Harm**  
www.P65Warnings.ca.gov

## WorkSav'r® Stainless Steel Polish



✓  
**SILICONE FREE**

Stock Code	Container Size	Units per Case
SC16	15 oz. Aerosol	12



- Renews stainless steel and chrome surfaces in one application
- Removes tarnish, residues and oxidation and also leaves a repellent coating
- Oil emulsion that cleans, polishes and protects
- Silicone free
- Superior performance vs. water based competitors
- Industrial strength foaming action for vertical applications
- Removes fingerprints

## WorkSav'r® EFS Expanding Foam



Stock Code	Container Size	Units per Case
EF12	12 oz. Aerosol Can	12

- Insulates and seals around ducts, pipes, air conditioning units, heating equipment vents and much more
- Foam dries to the touch in 30 minutes and cures hard in 4 hours
- Cured product can be trimmed, sanded and painted
- Resists mildew
- Perfect for voids





Item Number	Length Inches	Width Inches	Tensile Strength	Color	Units Per Bag	Bags Per Case
CT04	4	.10	18	Natural	100	10
CB04	4	.10	18	Black	100	10
CT06	6	.10	18	Natural	100	10
CB06	6	.10	18	Black	100	10
CT08-18	8	.10	18	Natural	100	10
CB08-18	8	.10	18	Black	100	10
CB05	5	.14	40	Black	100	10
CT08	8	.14	40	Natural	100	10
CB08-40	8	.14	40	Black	100	10
CT07	7	.19	50	Natural	100	10
CB07	7	.19	50	Black	100	10
CT11	11	.19	50	Natural	100	10
CB11	11	.19	50	Black	100	10
CT14	14	.19	50	Natural	100	10
CB14	14	.19	50	Black	100	10
CT17	17	.19	50	Natural	100	10
CB17	17	.19	50	Black	100	10
CT08-120	8	.30	120	Natural	100	10
CB08-120	8	.30	120	Black	100	10
CT14-120	14	.30	120	Natural	100	10
CB14-120	14	.30	120	Black	100	10
CT18	18	.30	120	Natural	100	10
CB18	18	.30	120	Black	100	10
CT24	24	.35	175	Natural	50	5
CB24	24	.35	175	Black	50	5
CT36	36	.35	175	Natural	50	5
CB36	36	.35	175	Black	50	5
CT48	48	.35	175	Natural	50	5
CB48	48	.35	175	Black	50	5

# BUNDLE BUDDIES™

- Tough nylon cable ties
- Continuous locking threads
- UV (black) cable ties are ultra violet stabilized for prolonged life
- Temperature Range: -40°F to 185°F (-40°C to 85°C)
- Meets ASTM-D4066 Specifications











**HOLD IT IN PLACE!**



**SEALANT REFERENCE GUIDE:** The information is provided solely as a guide. Recommendations are based on a wide variety of customer experience. Always check with plastic pipe manufacturer to determine compatibility.




		TYPE	APPLICATIONS	USED BY	USED ON	APPROVALS
	<h2>Soft-Set</h2>	Blue Green Paste with PTFE	Water, Steam, Natural Gas, LPG, Propane, Gasoline, Butane *Not for Use with Oxygen systems	<ul style="list-style-type: none"> <li>Mechanical Contractors</li> <li>Plumbers</li> <li>Gas Utilities</li> <li>Service Station Installers</li> <li>Manufacturing Plants</li> </ul>	Most Metals & Most Plastics	CSA, UL NSF 61 NSF 14
	<h2>E-Seal</h2>	Green Paste with PTFE	Ethanol Blended Gasoline, including E10 and E85 (*NOT 100% Ethanol applications) *Not for Use with Oxygen systems	<ul style="list-style-type: none"> <li>Gas Station Installers</li> </ul>	Most Metals	UL
	<h2>Hard-Set</h2>	Red Varnish	Aliphatic, Aromatic & Chlorinated Solvents *Not for Use with Oxygen systems	<ul style="list-style-type: none"> <li>Auto Industry to Seal Drive Trains, Coat parts</li> <li>Contractors Installing Underground Piping, Steam Systems</li> <li>Marine Manufacturers</li> </ul>	Most Metals Rubber, Porcelain and Wood	UL
	<h2>PLS-2</h2>	Gray Paste with PTFE	Chlorine, Diesel, Jet Fuel, Steam, Dilute Acid, LPG *Not for Use with Oxygen systems	<ul style="list-style-type: none"> <li>Chemical Plants</li> <li>Gas Utilities</li> <li>Refineries</li> <li>Airlines, Hydraulics</li> <li>Tank Trucks</li> </ul>	Most Metals & Most Plastics	CSA UL
	<h2>100</h2>	Black Paste	High Concentrations of Alcohol, Solvents, Caustic Chemicals 100% Ethanol 100% Methanol *Not for Use with Oxygen systems	<ul style="list-style-type: none"> <li>Pharmaceutical</li> <li>Chemical Companies</li> </ul>	Most Metals *Not for Use on Plastic Pipe	
	<h2>JC-30</h2>	Off White Paste with PTFE	Water, Steam, Natural Gas, LPG, Propane, Gasoline, R-22 and Hydraulic Fluids *Not for Use with Oxygen systems	<ul style="list-style-type: none"> <li>Plumbers,</li> <li>Gas Utilities</li> <li>Manufacturing Plants</li> </ul>	Most Metals	
	<h2>NT</h2>	Bright Blue Paste without PTFE	Water, Steam, LPG, Propane, Gasoline *Not for Use with Oxygen systems	<ul style="list-style-type: none"> <li>Propane Companies</li> <li>Petroleum Companies</li> </ul>	Most Metals & Most Plastics	NSF 61 NSF 14
	<h2>FasSealATS</h2>	Smooth White Paste with PTFE	Air Conditioning Lines, Hydraulic-Pneumatic Lines, Air Compressor Hoses, Sprinkler Installations *Not for Use with Oxygen systems	<ul style="list-style-type: none"> <li>HVAC</li> <li>Refrigeration Companies</li> </ul>	Most Metals *Not for Use on Plastic Pipe	

# FEDPRO<sup>TM</sup>


TRUSTED BRANDS SINCE 1915



SEALANTS



WIPES



HAND CLEANERS



PENETRANTS



LUBRICANTS



SPECIALTY

**FEDPRO, INC.**

4520 Richmond Road  
Cleveland, Ohio 44128  
Phone: 216-464-6440  
Fax: 216-464-2080

Website: [www.fedpro.com](http://www.fedpro.com)



©2023 Fedpro, Inc. – All rights reserved.  
Printed in the USA.  
#FPRO-CAT | 01/23