



Televes reserves the right to modify the product

Kit: NanoKom mast amplifier and "F" Power Supply Unit

Ref. 561301 + Ref. 550104

The kit consists of:

Ref. 561301: NanoKom mast amplifier, 1 input: Low VHF/High VHF/UHF

Masthead amplifier for the amplification of terrestrial television signals coming from an antenna.

Equipped with a single input, with amplification on some bands. The amplifier is powered through the output coaxial cable at 12 Vdc.

Ref. 550104: "F" Power Supply Unit, 12V - 220mA, 2 outputs

12 V-power supply (220 mA) that powers equipment through the input coaxial cable while allowing the transmission of the TV signal.

Included in the installation to power either mast amplifiers or a BOSS system. Furthermore, it is equipped with two outputs. The power supply is UL certified (US plug).

Ref.561380

Art.Nr

EAN13

8424450197479

Highlights

- Very low noise figure
- Integrated Low VHF+High VHF and UHF gain manual regulators
- Ultra-small ergonomic design
- EasyF connection system
- Fully automated manufacturing, subject to the most stringent quality controls
- High-screening Zamak chassis

Main features

- ON/OFF switches to allow DC pass towards the UHF inputs for the powering of a BOSS system
- Easy mounting. Equipped with a plastic tie for mast mounting
- Resistant ABS-plastic orange case for outdoor installation

Technical specifications

Reference		561301		
Bands		UHF	High VHF	Low VHF
Frequency range	MHz	470-698	174-216	54-88
Gain	dB	30	21	20
Gain regulation margin	dB	Manual 0 ... 15	Manual 0 ... 12	
Output level	dBmV	DIN 45004B	47	43
		EN 50083 (-35dB)	55	51
Noise figure	dB	1,5	3,5	
Powering	Vdc/mA	12/45		
Max. inputs current	OFF	mA	0	
	ON		50	
Operating temperature	°F	23...113		
Protection index	IP	23		

Reference		550104	
Frequency range	Mhz	5 - 862	
Through losses	dB	1 Out	Main: 1.5 / Aux: ----
		2 Out	Main 4 / Aux: 4
Output voltage	V	12 ±1.5	
Max. output current	mA	220	
Min. output current	mA	30	
Power supply	V~ / Hz	108 - 132 / 50-60	
Max. consumption	mA~ / W	65 / 3.6	
Protection index	IP	20	
Operating temperature	°F	14 ... +113	