



OWNER'S MANUAL

Canyon250



Always wear a helmet; It could save your Life!

Do not remove this operator's manual from this vehicle.

Please obtain, review, and follow provincial / municipal government acts and regulations pertaining to owning and operating an off-road vehicle.



WARNING

This manual should be considered as a permanent part of the vehicle and should remain with the vehicle when resold or otherwise transferred to a new user or operator. The manual contains important safety information and instructions which should be read carefully before operating the vehicle.



WARNING

Failure to follow the age recommendations for this ATV.
Failure to supervise children under 16 on ATV models intended for their use.

Use by children of ATVs that are not recommended for their age can lead to severe injury or death of the child.

Even though a child may be within the age group for which an ATV is recommended, he or she may not have the skills, abilities, or judgement needed to operate the ATV safely and may be involved in a serious accident.

Category Y (Youth Model) ATV. An ATV of appropriate size intended for recreational use under adult supervision by an operator under age 16. Youth model ATVs can further be categorized as follows:

Category Y-6+ ATV. A Category Y-6+ ATV is a youth model ATV that is intended for use by children age 6 or older

Category Y-10+ ATV. A Category Y-10+ ATV is a youth model ATV that is intended for use by children age 10 or older.

Category Y-12+ ATV. A Category Y-12+ ATV is a youth model ATV that is intended for use by children age 12 or older.

Category T (Transitional Model) ATV. A Category T ATV is an ATV of appropriate size that is intended for recreational use by an operator age 14 or older under adult supervision, or by an operator age 16 or older.

Congratulations on your purchase of the Ricky Power Sports, LLC's Canyon 250 ATV. The period of warranty for the vehicle shall be 90 days from the date of purchase and the warranty covers the manufacturer's faulty workmanship and materials. During the warranty period Ricky Power Sports, LLC, will at its option, repair, provide replacement parts or replace your Ricky Power Sports, LLC's 250cc ATV in free. This warranty does not cover normal wear items or damage caused by neglect or misuse of the product.

Engine Warranty – 90 days

Frame Warranty – 90 days

Warranty is void if:

Frame is bent or broken due to abuse.

Wheels are bent or broken.

Fender bent or broken due to abuse.

Any sign of impact, accident, jumping, spin-outs or roll over.

RICKY POWER SPORTS, LLC is not liable for any damage claim or liability claim personal or otherwise resulting from the operation of this product in any way.

Should you experience a problem with your vehicle, please call Ricky Power Sports, LLC Customer service line toll free at 1-844-250-2199 You will be instructed how to proceed.

A COPY OF THE SALES RECEIPT IS REQUIRED.

Table of Contents

IMPORTANT.....	2
NOTICE TO THE USER.....	4
Ricky Power Sports Canyon250 ATV.....	8
FUEL AND OIL.....	9
LOCATION OF LABELS.....	10
INDICATOR LIGHTS AND MAIN KEY SWITCH ASSEM.(W/ Speedometer).....	12
LEFT HANDLEBAR.....	13
RIGHT HANDLEBAR.....	14
REAR FOOT BRAKE.....	14
FUEL VALVE.....	15
FUEL TANK CAP.....	15
SEAT LOCK.....	16
12V UTILITY SOCKET.....	17
RIDING YOUR ATV.....	18
BEFORE RIDING.....	18
INSPECTION BEFORE RIDING.....	19
BREAK-IN.....	20
SAFETY GEAR.....	22
STARTING THE ENGINE.....	25
SHIFTING.....	27
BRAKING.....	29
TURNING.....	30
OPERATION ON HILLS.....	31
RIDING OVER OBSTACLES.....	34
SKIDDING OR SLIDING.....	35
RIDING THROUGH WATER.....	36
RIDING IN COLD WEATHER.....	37
RIDING ON SNOW OR ICE.....	40
ACCESSORY USE AND VEHICLE LOADING.....	41

Table of Contents

VEHICLE WEIGHT LIMITS.....	42
INSPECTION AND MAINTENANCE.....	43
VALVE CLEARANCE.....	45
TOOLS.....	46
SPARK PLUG.....	46
BATTERY INSTALLATION.....	48
FUSE REPLACEMENT.....	52
HEADLIGHT/TAILLIGHT REPLACEMENT.....	52
THROTTLE LEVER ADJUSTMENT.....	53
IDLE SPEED ADJUSTMENT.....	54
FUEL HOSE.....	54
ENGINE OIL/OIL STRAINER/OIL FILTER.....	55
AIR FILTER.....	57
CLUTCH ADJUSTMENT.....	59
REAR GEAR CASE LUBRICATION.....	60
TIRES.....	61
BRAKES.....	64
HYDRAULIC FRONT BRAKES	65
REAR DRUM BRAKE	65
MUFFLER/ SPARK ARRESTER.....	67
GENERAL LUBRICATION.....	70
TROUBLESHOOTING.....	71
TRANSPORTING.....	73
CLEANING PROCEDURE.....	74
STORAGE PROCEDURE.....	76
SERIAL NUMBER LOCATION.....	77
SPECIFICATIONS.....	78
EMISSION CONTROL SYSTEM WARRANTY.....	80

How to Read This MANUAL

Please read this manual and follow all instructions carefully. To emphasize the special information, the symbol ▲ and the words WARNING or CAUTION have some special meanings. Pay great attention to the messages.

▲ WARNING-or-CAUTION

Indicates a potential hazard that could result in death or injury.

▲ CAUTION

Indicates a potential hazard that could result in vehicle damage.

NOTE: Indicating special information which is to make maintenance easier or instructions clearer.

WARNING and CAUTION are arranged like this:

▲ WARNING-or-CAUTION

The first part will identify a POTENTIAL HAZARD.

The second part will describe WHAT COULD HAPPEN if you ignore the WARNING or CAUTION.

The third part will describe HOW TO AVOID THE HAZARD.

This user's manual contains important safety and maintenance information. Read it carefully before riding. Failing to follow the warnings contained in this manual could result in INJURY or DEATH.

It is important that this manual remain with the vehicle when you transfer it to another user or owner.

All information, illustrations, photographs and specifications contained in this manual are based on the latest product information available at the time of publication. Due to improvements or other changes, there will be some discrepancies in this manual. We reserve the right to make product changes at any time, without notice and without incurring any obligation to make the same or similar changes to the vehicle previously built or sold.

NOTICE TO USERS

We believe in conservation and protection of the earth's natural resources. We encourage every vehicle owner and operator to do the same by obeying posted signs and riding only in areas designated and approved for off-road recreational use.

NOTICE TO PARENTS

This ATV is built for use by children age 16 and older, but the user's manual is written for adults who will be supervising the children, we strongly recommend , therefore, that you review this entire manual with your child and carefully explain the instructions, requirements, and warnings it contains so that your child can understand them.

Children differ in skills, physical abilities, and judgment. Some children may not be able to operate an ATV safely. Parents should supervise their child's use of the ATV at all times. Parents should permit continued use only if they determine that the child has the ability to operate the ATV safely.

It is very important that every child who rides the ATV should complete a training course.

THIS ATV IS NOT A TOY AND COULD BE HAZARDOUS TO OPERATE. An ATV handles differently from other vehicles including motorcycles and cars. A collision or rollover can occur quickly, even during routine maneuvers such as turning and driving on hills or over obstacles, if you fail to take proper precautions.

SEVERE INJURY OR DEATH can result if you do not follow these instructions:

- Read this manual and all labels carefully and follow the operating procedures described.
- Never operate an ATV without proper instruction. Take a training course.

Beginner should receive training from a certified instructor. Contact an authorized ATV dealer or call Ricky Power Sports, LLC at **1-844-250-2199** to find out about the training courses nearest you.

- Always follow these age recommendations:

Category Y (Youth Model) ATV. An ATV of appropriate size intended for recreational use under adult supervision by an operator under age 16. Youth model ATVs can further be categorized as follows:

Category Y-6+ ATV. A Category Y-6+ ATV is a youth model ATV that is intended for use by children age 6 or older

Category Y-10+ ATV. A Category Y-10+ ATV is a youth model ATV that is intended for use by children age 10 or older.

Category Y-12+ ATV. A Category Y-12+ ATV is a youth model ATV that is intended for use by children age 12 or older.

Category T (Transitional Model) ATV. A Category T ATV is an ATV of appropriate size that is intended for recreational use by an operator age 14 or older under adult supervision, or by an operator age 16 or older.

- Never allow a child under age 16 to operate an ATV without adult supervision, and never allow continued use of an ATV by a child if he or she does not have the abilities to operate it safely.

Never carry a passenger on an ATV.

- Never operate an ATV on any paved surfaces, including sidewalks, driveways, parking lots and streets.

- Never operate an ATV on any public street, road or highway, even a dirt or gravel one.

- Never operate an ATV without wearing an approved motorcycle helmet that fits properly. You should also wear eye protection (goggles or face shield), gloves, boots, long-sleeved shirt or jacket, and long pants.

- Never consume alcohol or drugs before or while operating this ATV.

- Never operate this ATV at excessive speeds. Always go at a speed that is proper for the terrain, visibility and operating conditions, and your experience.

- Never attempt wheelies, jumps, or other stunts.

- Always inspect your ATV each time you use it to make sure it is in safe operating condition. Always follow the inspection and maintenance procedures and schedules described in this manual.

- Always keep both hands on the handlebars and both feet on the footrests of the ATV during operation.

- Always go slowly and be extra careful when operating on unfamiliar terrain.

Always be alert to changing terrain conditions when operating the ATV.

- Never operate on excessively rough, slippery or loose terrain until you have learned and practiced the skills necessary to control the ATV on such terrain.

Always be especially cautious on these kinds of terrain.

- Always follow proper procedures for turning as described in this manual.


Practice turning at low speeds before attempting to turn at faster speeds. Do not turn at excessive speeds.

- Never operate that ATV on hills too steep for the ATV or for your abilities. Practice on smaller hills before attempting larger hills.

- Always follow proper procedures for climbing hills as described in this manual. Check the terrain carefully before you start up any hill. Never climb hills with excessively slippery or loose surfaces. Shift your weight forward. Never open the throttle suddenly or make sudden gear changes. Never go over the top of any hill at high speed.**
- Always follow proper procedures for going down hills and for braking on hills as described in this manual. Check the terrain carefully before you start down any hill. Shift your weight backward. Never go down a hill at high speed. Avoid going down a hill at an angle that would cause the vehicle to lean sharply to one side. Go straight down the hill where possible.**
- Always follow proper procedures for crossing the side of a hill as described in this manual. Avoid hills with excessively slippery or loose surfaces. Shift your weight to the uphill side of the ATV. Never attempt to turn the ATV around on any hill until you have mastered the turning technique described in this manual on level ground. Avoid crossing the side of a steep hill if possible.**
- Always use proper procedures if you stall or roll backwards when climbing a hill. To avoid stalling, use proper gear and maintain a steady speed when climbing a hill. If you stall or roll backwards, follow the special procedure for braking described in this manual. Dismount on the uphill side or to a side if pointed straight uphill. Turn the ATV around and remount, following the procedure described in this manual.**
- Always check for obstacles before operating in a new area. Never attempt to operate over large obstacles, such as large rocks or fallen trees. Always follow proper procedures when operating over obstacles as described in this manual.**
- Always be careful when skidding or sliding. Learn to safely control skidding or sliding by practicing at low speeds and on level, smooth terrain. On extremely slippery surfaces, such as ice, go slowly and be very cautious in order to reduce the chance of skidding or sliding out of control.**
- Never operate an ATV in fast flowing water or in water deeper than that specified in this manual. Remember that wet brakes may have reduced stopping ability. Test your brakes after leaving water. If necessary, apply them several times to let friction dry out the linings.**
- Always use the size and type tires specified in this manual. Always maintain proper tire pressure as described in this manual.**

- Never modify an ATV through improper installation or use of accessories.
- Never exceed the stated load capacity for an ATV. Cargo should be properly distributed and securely attached. Reduce speed and follow instructions in this manual for carrying cargo. Allow greater distance for braking.
- The combined weight of the rider and any accessories or cargo must never exceed the vehicle's load capacity of 220 lbs (100 kg).
- Do not tow a trailer. This vehicle is not designed for such use.

FOR MORE INFORMATION ABOUT ATV SAFETY, call Ricky Power Sports, LLC Safety Hotline at 1- 844-250-2199



Canyon250




FUEL AND OIL

FUEL

Proper fuel is very important for the engine. Ensure there is no dust, dirt, or water which has mixed in the fuel. Use regular unleaded gasoline.

ENGINE OIL

Your 250cc ATV has a four-stroke engine. Please use oil as described in the chart below. By using the prescribed oil, you will realize the best lubrication for the engine.




Use the chart to select a viscosity rating based on the temperature range in your area.

NOTE: In very cold weather (below 5°F (-15°C), use SAE10W-50 for good starting and smooth operation.

LOCATION OF WARNING LABELS

Read and follow all of the warnings labels on your ATV. Make sure you understand all the labels. Keep the labels on the ATV. Do not remove them for any reason. If a label comes off or becomes difficult to read, you should get a replacement by contacting Ricky Power Sports, LLC.



1- **WARNING**

Improper ATV use can result in **SEVERE INJURY or DEATH**

ALWAYS USE AN APPROPRIATELY SIZED AND PROTECTIVE GEAR

NEVER RIDE ON PUBLIC ROADS

NEVER CARRY PASSENGERS

NEVER USE WITH DRUGS OR ALCOHOL

NEVER OPERATE:

- Without proper training or instruction.
- At speeds too fast for your skills or the conditions.
- On public roads, a collision can occur with another vehicle.
- With passengers-passengers affect balance and steering and increase risk of losing control.

ALWAYS:

- Use proper riding techniques to avoid vehicle overturns on hills and rough terrain and in turns.
- Avoid paved surfaces-pavement may seriously affect handling and control.

LOCATE AND READ OWNER'S MANUAL CAREFULLY BEFORE OPERATING. FOLLOW ALL INSTRUCTIONS AND WARNINGS.

3- **WARNING**

UNDER 16

Operation of the ATV by children under the age of 16 increases the risk of severe injury or death.

NEVER permit children under age 16 to operate this ATV.

4- **GEAR SHIFT Pattern** **DRIVE SELECT LEVER**

Read owner's manual carefully before operating. **ATV MUST be stopped and be in first gear before shifting the drive select lever into or from reverse.**

2 **WARNING**

NEVER ride as a passenger. Passenger can cause a loss of control, resulting in **SEVERE INJURY or DEATH.**

5-

⚠ WARNING

IMPROPER TIRE PRESSURE OR OVERLOADING CAN CAUSE LOSS OF CONTROL.

LOSS OF CONTROL CAN RESULT IN SEVERE INJURY OR DEATH.

CORRECT TIRE PRESSURE:

Recommended: Minimum Front: 17kpa (2.5psi)
 Maximum Front: 23kpa (3.3psi)
 Minimum Rear: 22kpa (3.2psi)
 Maximum Rear: 28kpa (4psi)

Never set tire pressure below the recommended level. It could cause the tire to dislodge from the rim.

LOADING
 Maximum vehicle capacity is: 165kg (364 lbs.)

Maximum capacity includes the weight of the operator, cargo, and accessories plus the vertical weight on trailer hitch.

7-

LOAD LIMIT **⚠ WARNING**

30kg (66lbs) NEVER sit here

8-

LOAD LIMIT **⚠ WARNING**

45kg (99lbs) NEVER sit here

9-

⚠ WARNING

SHIFTING INTO OR FROM REVERSE CAN ONLY BE DONE IN FIRST GEAR. YOU MUST COME TO A COMPLETE STOP BEFORE SHIFTING INTO OR FROM REVERSE.

6-

CAUTION

- Accessories connected to utility socket should not exceed 100 watts.
- Make sure accessories are firmly plugged in utility socket before use.
- Using utility socket more than 10 minutes, without engine running, will drain battery.

10-

⚠ WARNING

THIS VEHICLE IS AN ALL-TERRAIN VEHICLE AND IS NOT INTENDED FOR USE ON PUBLIC HIGHWAYS

SPEEDOMETER, INDICATOR LIGHTS AND MAIN KEY SWITCH

1. Speedometer

Indicates speed of ATV

2. Odometer

Indicates total mileage driven.

3. Gear indicator

Illuminates when ATV changes gear.

4. High beam indicator

Illuminates when high beam is on.

5. Right turning light indicator

Illuminates when right turning light is on.

6. Ignition key switch

Turn right "ON", Turn left "OFF". ATV will only start when ignition key is turned to the "ON" Position. Make sure ignition key switch is in the "OFF" position when not in use.


7. Emergency light button

8. Emergency light indicator


Illuminates when emergency light is on.

9. left turning light indicator

Illuminates when left turning light is on.



LEFT HANDLEBAR SWITCHES: REAR BRAKE LEVER AND PARKING BRAKE LOCK



1 - Engine Stop Switch

With the Engine stop switch in the “OFF”  position the engine cannot be

started. With the Engine stop in the “RUN”  position the engine can be started.

2 - Rear brake lever

Rear brake is applied by squeezing the rear brake lever towards the grip.

3 - Electric start button

Depressing the electric start button will start the engine while the Ignition Key Switch is in the “ON” and Engine Stop Switch is in the “RUN” position.

4 - Light switch. There are 3 positions on the light switch: “OFF”, “Daytime running lights” and “Headlights”.

5 - High beam / low beam switch.


6 - Parking Brake Lock. While starting the engine or parking the machine, especially on a slope, apply the parking brake by squeezing the rear brake lever and pushing down the Parking Brake Lock.

7 - Manual Choke Lever. When engine is cold, place the choke lever to the ON position. When engine has warmed up, place lever back to the OFF position.

8 - Turning light switch.

9 - Horn button switch.

RIGHT HANDLEBAR: FRONT BRAKE LEVER AND THUMB THROTTLE



1 - Throttle lever

Controls engine and ATV speed. Operate this lever with your thumb. Push it forward to increase engine and ATV speed. Release it to decrease engine and ATV speed.

2- Front brake lever

Squeeze lever toward hand grip to apply front brakes.

3- Speed limiter screw

The speed limiter keeps the throttle from fully opening, even when the throttle is pushed to the maximum. Turning the speed limiter screw clockwise limits the maximum engine power available and decreases the maximum speed. Adjust this limiter screw according to the rider's skill and experience.

4 - Brake fluid reservoir


Use DOT3 or DOT4 brake fluid. Do not mix brake fluid types.

REAR FOOT BRAKE

Foot brake

Located on the right hand side of the ATV.

Foot brake stops the rear wheels.



FUEL VALVE

This vehicle has one manually operated fuel valve. There are 3 positions



“ON”



“OFF”



“RESERVE”

“ON” position

In this position, fuel is allowed to flow into the carburetor when the engine is running or being started.

“OFF” position


In this position the fuel is shut off from the carburetor. The fuel valve needs to be placed in this position when the ATV is not in use

“RESERVE” position

If the fuel level in the fuel tank becomes too low for the engine to stay running while the fuel valve is in the “ON” position, turn the fuel valve to “RESERVE”. This will allow the engine to begin using the reserve fuel supply. You will need to re-fuel as soon as possible. Once re-fueled, turn the valve back to the “ON” Position .

FUEL TANK CAP

To open the fuel tank cap, take the end of the vent tube out from the vehicle body; turn the fuel tank cap counterclockwise. To close the fuel tank cap, turn it clockwise and tighten it securely. Be sure that the vent tube is securely connected to the cap as shown.



▲ WARNING

Overfilling the fuel tank could be hazardous.

If you overfill the fuel tank, fuel may overflow when it expands. Expanding is due to heat from engine or sun. Overheated fuel could easily catch fire.

Stop adding fuel when the fuel level reaches the bottom of the filler neck.

▲ WARNING

Improper fueling of the ATV could be hazardous.

Failing to follow safety precautions when refueling could result in a fire or let you to breathe toxic fumes.

Refuel in a well ventilated area. Make sure the engine is off and avoid spilling fuel on a hot engine. Do not smoke, and make sure there are no open flames or sparks in the area. Avoid breathing gasoline vapors. Keep children and pets away when you are refueling the ATV.

SEAT LOCK

To remove the seat, move the seat lock lever backward. Raise the rear end of the seat and slide it back.

To lock the seat, slide the seat lever into its retainer and push the seat down firmly.



▲ WARNING

Improperly installing the seat could be hazardous.

Failing to install the seat properly could allow the seat to move and cause the rider to lose control.

Make sure seat is in proper position and attached securely when you install it.

12V Utility Socket

CAUTION

Using Accessories with wattage requirements over 100 watts could damage ATV

Using Accessories with wattage requirements over 100 watts could cause wiring and electrical components to overheat causing failure.

Check accessory wattage requirements before plugging in to 12V electrical socket.



12V Utility socket Use:

1. Remove 12V utility socket accessory cap.
2. Plug in accessory making sure plug is pushed all the way in socket.

Note: Do not use accessory more than 10 minutes without engine running, doing so will drain battery.

3. After use, make sure cap is placed back on socket.

RIDING YOUR ATV

WHAT YOU SHOULD KNOW BEFORE RIDING

Before riding, you should read all the following information carefully. If you are properly prepared, you will have a more enjoyable ride.

Before riding, you should find a good place to practice the skills. Find a flat, open area with enough space to practice the new skills.

▲ WARNING

Operating this ATV without proper instruction.

The risk of an accident is greatly increased if the operator does not know how to operate the ATV properly in different situations and on different types of terrain.

Beginning and inexperienced operators should complete the certified training course offered by SVIA (www.svia.org). They should then regularly practice the skills learned in the course and the operating techniques described in the owner's manual.

For more information about the training course, contact an authorized ATV dealer or call SVIA at 1-800-887-2887. For More information on ATV safety, please call: 1-844-250-2199.

Make sure that it is legal to ride in the area you selected. Review the local laws and make sure you are not trespassing. Call the police if you don't know where you can ride.

Protect your riding areas. When you are riding, remember to keep the terrain in good condition. Don't destroy plants, trees or other vegetation. Don't litter and don't bother wildlife. With your help, your riding area can remain open for use in the future.

After you have found a good place to practice, review the control system on your ATV before riding. Learn to find these controls without looking for them, because you will not have time to look for them when you are riding.

Canadian residents must obtain, review, and follow all provincial and municipal government acts and regulations pertaining to owning and operating an off-road vehicle.

INSPECTION BEFORE RIDING

ITEM TO CHECK	CONTENT
Steering	Smoothness; No restriction of movement; No play or looseness
Brakes	Proper brake lever free play; enough brake force; Parking brake effectiveness
Tires	Proper air pressure; Enough tread depth; No cracks, rips, or other damages
Fuel	Enough fuel for the intended trip; Fuel hose connected securely; No damage to fuel tank or cap; Fuel tank cap closed securely
Engine stop switch	Proper operation of switch
Engine oil	Proper level – Check oil by inspecting Engine Oil Dip Stick. The engine oil should be between the Minimum and Maximum lines.
Throttle	Proper free play of throttle lever; smooth response; quick return to idle position
General condition	Bolts and nuts are tight; no rattle from any parts of the engine when running, no visible evidence of Damage

⚠ WARNING

Failing to inspect the ATV before operating could be hazardous. Failing to perform proper maintenance could also be hazardous.

Failing to inspect and maintain your ATV could increase the chances of an accident or equipment damage

Always inspect your ATV each time before riding, and make sure it is in a safe operating condition. Refer to the INSPECTION AND MAINTENANCE section in this manual.

⚠ WARNING

Operating this ATV with improper tires, or improper tire air pressure could be hazardous.

If you use improper tires or improper air pressure, you may lose control of the ATV. This will cause an accident.

Always use the size and type of tires specified in this user's manual. Always maintain proper tire air pressure as described in the INSPECTION AND MAINTENANCE section.

▲ CAUTION

Failure to follow Break-In procedures can significantly shorten the life of your vehicle.

By not following Break-In procedure, you risk causing excessive wear, and damaging the engine.

Be careful to correctly follow Break-in Procedure.

BREAK-IN

The first month is the most important in the life of your vehicle. Proper operation during this break-in period will be helpful for assuring maximum life and performance of your new vehicle. The following guidelines explain proper break-in procedures.

Maximum Throttle Opening Recommendation

During the first 10 hours of operation, you should always use less than $\frac{1}{2}$ throttle opening.

Vary the Engine Rotating Speed

Vary the engine rotating speed during the break-in period. This allows the parts to “load” and then “unload” (allowing the parts to cool). Although it is essential to place some stress on the engine components during break-in, you must be careful not to load the engine too much.

Avoid Constant Low Rotating Speed

Operating the engine at constant low rotating speed (light load) can cause parts to glaze and not seal properly. Allow the engine to accelerate freely without exceeding the maximum throttle limit.

Allow the Engine Oil to Circulate Before Riding

Allow enough idling time after warm or cold engine starting. This allows the lubricating oil to reach all critical engine components.

Observe Your Initial and Most Critical Service

The initial service (break-in maintenance) is the most important service that your vehicle will receive. Observing a proper break-in operation, will help engine components seal properly. Maintenance required as part of the initial service includes proper adjustments, tightening of all bolts & nuts, and replacement of dirty oil. Timely performance of this service will help you get the best service life and performance of the engine.

▲ WARNING

Carrying a passenger on this ATV.

Greatly reduces your ability to balance and control this ATV. Could cause an accident, resulting in harm to you and/or your passenger.



Never carry a passenger. The long seat is to allow the operator to shift position as needed during operation. It is not for carrying passenger.

▲ WARNING

Operating this ATV on paved surfaces.

The ATV's tires are designed for off-road use only, not for use on pavement. Paved surfaces may seriously affect handling and control of the ATV, and may cause the vehicle to go out of control.



Never operate the ATV on any paved surfaces, including sidewalks, driveways, parking lots and streets.

▲ WARNING

Operating this ATV on public streets, roads or highways.

You may collide with another vehicle.

Never operate this ATV on any public street, road or highway, even a dirt or gravel one. In many states is it illegal to operate ATVs on public streets, roads and highways.



▲ WARNING

Never operate this ATV at night. Night is defined as the period of time 30 minutes before sunset to 30 minutes after sunrise.

You may collide with another vehicle, a stationary object, or hazard found in the terrain.

SAFETY GEAR

A DOT approved motorcycle helmet is the most important part of your safety gear. A DOT approved motorcycle helmet can help prevent a serious head injury. Choose a helmet that fits snugly. Motorcycle dealers can help in selecting a good quality helmet which fits properly.

▲ WARNING

Operating this ATV without wearing an approved motorcycle helmet, eye protection and protective clothing.

Operating without an approved motorcycle helmet increases your chances of a severe head injury or death in the event of an accident. Operating without eye protection can result in an accident and increases your chances of a severe injury in the event of an accident. Operating without protective clothing increases your chances of severe injury in the event of an accident.

Always wear an approved motorcycle helmet that fits properly.


You should also wear:

- eye protection (goggles or face shield)
- gloves
- boots
- long-sleeved shirt or jacket
- long pants

You should wear eye protection when you ride. If a rock or a branch hits your eyes, you could be severely injured. Wear goggles or a face shield.

Wear proper clothing when you ride. Proper clothes can protect you from injury.

Wear a good pair of gloves, strong boots that are over the ankle, long pants, and a long sleeve shirt



▲ WARNING

Operating this ATV after consuming alcohol or drugs.

- Could seriously affect your judgement.**
- Could cause you to react more slowly.**
- Could affect your balance and perception.**
- Could result in an accident.**

Never consume alcohol or drugs before or while driving this ATV.

▲ WARNING

Operating this ATV at excessive speeds.

Increases your chances of losing control of the ATV, which can result in an accident.

Always go at a speed that is proper for the terrain, visibility and operating conditions, and your experience.

▲ WARNING

Attempting wheelies, jumps, and other stunts.

Increases the chance of an accident, including an overturn.

Never attempt stunts, such as wheelies or jumps. Don't try to show off.



▲ WARNING

Failure to inspect the ATV before operating.
Failure to properly maintain the ATV.

Increases the possibility of an accident or equipment damage.

Always inspect your ATV each time you use it to make sure the ATV is in safe operating condition.

Always follow the inspection and maintenance procedures and schedules described in the owner's manual.

▲ WARNING

Removing hands from handlebars or feet from the footrests during operation.

Removing even one hand or foot can reduce your ability to control the ATV or could cause you to lose your balance and fall off of the ATV. If you remove a foot from the footrest, your foot or leg may come into contact with the rear wheels, which could injure you or cause an accident.

Always keep both hands on the handlebars and both feet on the foot rests of your ATV during operation.

▲ WARNING

Failing to use extra care when operating this ATV on unfamiliar terrain.

You can come upon hidden rocks, bumps, or holes, without enough time to react. Could result in the ATV overturning or going out of control.



Go slowly and be extra careful when operating on unfamiliar terrain.

Always be alert to changing terrain conditions when operating the ATV.

▲ WARNING

Running your ATV indoors where there is little or no ventilation.

Breathing in exhaust gases from the ATV could cause severe injury.

Always run your ATV outdoors where there is fresh air.

STARTING THE ENGINE

Before attempting to start the engine, make sure to follow these steps.

1. Turn the fuel valve to the “ON” position
2. Turn the key switch to the “ON” position.
3. Set the engine stop switch to the “ON” position.
4. Set the thumb lever choke to the “ON” position
5. Apply the rear brake lever and make sure that the rear wheels are in locking condition.
6. Press the starter button “START” to start the engine.
7. Allow engine to warm up then place the thumb lever for the choke to the “OFF” position.

▲ WARNING

Failure to use extra care when operating on excessively rough, slippery or loose terrain.

Could cause loss of traction or vehicle control, which could result in an accident, including an overturn.

Do not operate on excessively rough, slippery or loose terrain until you have learned and practiced the skills necessary to control the ATV on such terrain. Always be especially cautious on these kinds of terrain.



▲ WARNING

Opening the throttle suddenly could be hazardous.

The front wheels could leave the ground and cause loss of control of the ATV.

Always open the throttle gradually when you want to accelerate.

▲ WARNING

The ATV could start moving as soon as you start the engine.


Unexpected movement could cause you to lose control of the ATV.

Be sure to set the parking brake before you start the engine.

▲ WARNING

The ATV may start moving as soon as you release the parking brake.

Unexpected movement could cause you to lose control of the ATV.



When you are sure the engine is warm, release the parking brake. Release brake lever and open the throttle gradually to move forward.

▲ WARNING

Opening the throttle suddenly could be hazardous.

The front wheels could leave off the ground and cause loss of control of the ATV.

Always open the throttle gradually when you want to accelerate.

SHIFTING:


This ATV has a 5 speed transmission with a centrifugal automatic clutch.

To shift vehicle in neutral while driving, repeatedly depress the gear shift lever. The green indicator light will illuminate when in neutral.

To shift the vehicle through gears 1-5

1. Release the throttle lever.
2. Shift into first gear by lifting up once on the gear shift lever from neutral.
3. Open throttle gradually. Once vehicle has reached adequate speed, release throttle and shift into 2nd gear.
4. Open throttle gradually then repeat procedure for the remaining gears.

When slowing down or stopping, release the throttle and apply the brakes smoothly. As the ATV slows down, shift to a lower gear by depressing the gear shift lever.



Gear shift lever

DRIVE SELECT LEVER

The drive select lever shifts the ATV in either forward or reverse

1. Shift the gear select lever in neutral
2. Apply brakes until the vehicle comes to stop completely.
3. Shift transmission into first gear.

4. Push down the drive select lever (pic 1)

NOTE: When the gear is in reverse, the reverse indicator light should be illuminated, if light does not illuminate, check to see if vehicle is in first gear or the drive select lever is completely pushed down.

5. Check for people or obstacles behind you.

6. Open the throttle gradually continuing to watch to the rear while backing.

7. After the vehicle finishes moving backward, stop the vehicle completely, set the gear is in neutral before pull back the drive select lever. (pic 2)



(pic 1)



(pic 2)

▲ WARNING

Not looking behind vehicle before and while going in reverse could be hazardous.

Failure to look behind while backing could cause the ATV to run into an obstacle or person resulting in an injury and/or property damage.

Before going in reverse and while backing, look behind the vehicle for any obstacles or people to avoid.

CAUTION

Always release the throttle before shifting gears.

Failure to release the throttle before shifting gears could cause damage to the engine and drive train.


CAUTION

Do not coast for long periods of time with the engine not running, and do not tow the machine a long distance.

Even when the machine is in neutral, the gears are not properly lubricated unless the engine is running. Towing the machine with the engine not running could cause damage to the drive train.

Be sure to check for leaks in the gear case and keep oil up to the prescribed level.

BRAKING



Rear hand brake



Rear foot brake



Front hand brake

To stop the ATV, first release the throttle lever. And then apply the rear and front brakes smoothly.

▲ WARNING

Braking while turning the ATV could be hazardous.

Use of the brake when turning could cause the ATV to slide or roll over.

Use the brake to slow down before you begin to turn.

▲ WARNING

Braking hard on slippery surfaces could be hazardous.

The ATV could skid and go out of control if you brake too hard.

Apply the brakes lightly and carefully on slippery surfaces.

▲ WARNING

Operating the parking brake when the ATV is moving could be hazardous.

The front wheels could lock, and it will cause a skid and an accident.

Use the parking brake only after you stop the ATV.

TURNING

▲ WARNING

Turning improperly.

ATV could go out of control, causing a collision or overturn.

Always follow proper procedures for turning as described in the owner's manual.

Practice turning at low speeds before attempting to turn at faster speeds.

Do not turn at excessive speed.

To turn the ATV, the rider must use the proper technique. Because this vehicle has a solid rear axle, both rear wheels always turn at the same speed. This means that if the rear wheels are getting equal traction, the vehicle will tend to move straight ahead. This is because the rear wheels will travel the same distance. For the vehicle to turn, the outside rear wheel must travel a longer distance than the inside rear wheel. To make this happen, the rider must create less traction for the inside wheel, allowing it to skid. This allows it to travel a shorter distance than the outside wheel. This happens even though both wheels are still turning at the same speed.



To turn ATV, use the following technique:

- Move your body weight forward and to the inside of the turn.
- Turn the handlebar while looking in the direction of the turn.

FOR HIGHER SPEEDS OR SHARPER TURNS

Use the same technique that you use when you move your body weight farther toward the inside of the turn to maintain your balance. Natural turning forces (which can push the vehicle to the outside of the turn) increase as the speed or the turn sharpness increases. This means you must lean your body farther into the turn as you go faster or turn more sharply. This prevents the vehicle from tipping over to the outside of the turn. If your ATV starts to tip while turning, lean your body farther into the turn while gradually reducing the throttle and making the turn wider, if possible.

OPERATION ON HILLS

▲ WARNING

Operating on excessively steep hills.

The vehicle can overturn more easily on extremely steep hills than on level surfaces or small hills.

Never operate the ATV on hills too steep for the ATV or for your abilities.

Practice on smaller hills before attempting larger hills.

Climbing a Hill

▲ WARNING

Climbing hills improperly.

Could cause loss of control or cause ATV to overturn.

Always follow the proper procedures for climbing hills as described in this owner's manual.

Always check the terrain carefully before you start up any hill.



Never climb hills with excessively slippery or loose surfaces.

Shift your weight forward.

Never open the throttle suddenly or make sudden gear changes. The ATV could flip over backwards.

Never go over the top of any hill at a high speed. An obstacle, a sharp drop, or another vehicle or person could be on the other side of the hill.



To climb a hill with the ATV, follow the directions below.

1. Speed up and maintain a steady speed before reaching the top of the hill.

Remember that you must ride at a steady speed all the way to the top of the hill.

2. Shift your body forward by sliding forward on the seat. Lean slightly forward. For steep hills, stand on the footrests and lean forward.

3. Maintain a steady speed while climbing the hill.

4. Slow down gradually when you reach the top of the hill.

Descending a Hill

▲ WARNING

Going down a hill improperly.

Could cause loss of control or cause ATV to overturn.

Always follow proper procedures for going down hills as described in the owners manual. **NOTE: a special technique is required when braking as you go down a hill. Always check the terrain carefully before you start down any hill.**

Shift your weight backward.

Never go down a hill at high speed.

Avoid going down a hill at an angle that would cause the vehicle to lean sharply to one side. Go straight down the hill where possible.

To ride down a hill with the ATV, follow the instructions below.

1. Check the terrain carefully for any obstacles before you go down the hill.
2. Point the ATV straight down the hill.
3. Transfer your body to the rear by sliding back on the seat.
4. Ride down the hill slowly with the throttle released.
5. Apply the rear brake to control the speed.
6. Avoid going down a hill at an angle that would cause the vehicle to lean sharply to one side. Go straight down the hill if possible.



▲ WARNING

Improperly crossing hills or turning on hills.

Could cause loss of control or cause ATV to overturn.

Never attempt to turn the ATV around on any hill until you have mastered the turning technique as described in the owner's manual on level ground.

Be very careful when turning on any hill.

Avoid crossing the side of a steep hill if possible.

When crossing the side of a hill:

Always follow proper procedures as described in the owner's manual.

Avoid hills with excessively slippery or loose surfaces.

Shift your weight to the uphill side of the ATV.



▲ WARNING

Stalling, rolling backwards or improperly dismounting while climbing a hill.

Could result in ATV overturning.

Use proper gear and maintain steady speed when climbing a hill.

If you lose all forward speed:

Keep weight uphill.

Apply brakes.

Lock parking brake, after you are stopped.

If you begin rolling backwards:

Keep weight uphill.

Never apply the rear brake while rolling backwards.

Apply the front brake.

When fully stopped, apply rear brake as well, and then

lock the parking brake.

Dismount on uphill side or to a side if pointed straight uphill.

Turn the ATV around and remount, following the procedure described in the owner's manual.



RIDING OVER OBSTACLES

▲ WARNING

Improperly operating over obstacles.

Could cause loss of control or a collision. Could cause the ATV to overturn.

Before operating in a new area, check for obstacles.

Never attempt to ride over large obstacles, such as large rocks or fallen trees.

When you go over obstacles, always follow proper procedures as described in the owner's manual.

If you come to an obstacle that you cannot avoid, you may be able to cross over it by using the following procedure.

1. If the obstacle is in front of you, approach at walking speed.
2. Rise up slightly on the footrests.
3. Pull up on the handlebar and apply a little throttle as the front wheels reach the obstacle.
4. Lean forward and release the throttle after the front wheels are over the obstacle.

Remember that some obstacles are too high for your ATV or for your abilities. If you are not sure that you can safely cross over an obstacle, back up and ride around the obstacle.

▲ WARNING

Skidding or sliding improperly.

You may lose control of this ATV.
You may also regain traction unexpectedly, which may cause the ATV to overturn.

Learn to safely control skidding or sliding by practicing at low speeds and on level, smooth terrain.
On extremely slippery surfaces, such as ice, go slowly and be very cautious in order to reduce the chance of skidding or sliding out of control.

SKIDDING OR SLIDING

You may experience skidding or sliding when you are not braking. You may be able to overcome it by using the techniques listed below.

If your front wheel skids:

Gain front wheel traction by reducing the throttle opening and leaning your body slightly forward.

If your rear wheel skids:

If space permits, steer in the direction of the skid. Shift your body away from the skid slightly. Avoid using the throttle or brakes until you regain directional control of the vehicle.

RIDING THROUGH WATER

You can ride the ATV through shallow water. Make sure it is not more than 10cm (4 inches) deep and is not moving fast. Choose a good place to cross before you ride through the water. Look for a spot where the banks are gently sloped on both sides and the bottom of the stream is hard. If you are unfamiliar with the area, park the ATV and inspect the stream first to find a suitable spot for crossing. When crossing, operate the ATV at a slow, steady speed. Be careful not to damage banks when crossing.

▲ WARNING

Operating this ATV through deep or fast flowing water.

Tires may float, causing loss of traction and loss of control, which could lead to an accident.

Never operate this ATV in fast flowing water or in water deeper than described in this owner's manual.

Remember that wet brakes may have reduced stopping ability. Test your brakes after leaving water. If necessary, apply the brakes several times to let friction dry out the linings.

CAUTION

Operating the ATV in water, sand, or mud causes rapid brake wear.

Excessive brake wear could cause the brakes to be less effective.

After repeated operation of the ATV in these conditions, bring it to your authorized service center to have the brakes inspected and cleaned.

RIDING IN COLD WEATHER

Pre-ride Inspection

Check that the throttle and all control levers move freely. Make sure that the footrests are free of ice or snow.

Move the ATV forward and backward to check that the wheels roll freely. If you cannot move the ATV, the tires may be frozen to the ground, or the brakes may be frozen to the wheels. If the tires are frozen to the ground, pour warm water around them to melt the ice. If the brakes are frozen, bring the ATV to a warmer area to thaw out the brakes.

After the engine has warmed up, check the brakes. Do this inspection on level ground and do not exceed the walking speed. Be sure to check the operation of both front and rear brakes. If the brakes do not work adequately, stop riding the ATV.

CAUTION
Using engine power to free up frozen wheels could damage your ATV.
Severe damage to the drive train may occur if you use engine power to free frozen wheels.
Before riding, manually move the ATV forward and backward to make certain that all wheels roll freely.

Bring the ATV to a warmer area to allow the brakes to thaw out. After the brakes thaw, dry them by applying them several times before riding. If the brakes do not regain full stopping power, ask your authorized service center to check them before you continue riding your ATV.

Water that enters the brakes may freeze after you park your ATV. The frozen water can prevent wheels from turning or the brakes from working. After riding through water, mud, snow or slush, it is important to dry the brakes before parking the ATV. To dry the brakes, apply them several times while riding slowly. Before your next ride, be sure to do a Pre-ride inspection as described earlier in this section.

▲ WARNING

Operating the ATV without a properly functioning brake system could be hazardous.

Wet or frozen brakes will increase stopping distance. This will increase your chance of having an accident.

Be sure to inspect the brakes before riding the vehicle in cold weather as described above.

Dressing for Cold Weather Riding

▲ WARNING

Operating your ATV in cold weather without proper clothing could be hazardous.

Continued exposure in the cold weather could lead to hypothermia. Hypothermia is a condition where your body's inner temperature drops low enough to cause injury or death.

Always dress for the worst weather conditions you might encounter. Be prepared for bad weather and ATV breakdowns.

Riding in cold weather can be hazardous. At a temperature of 10°F (-12°C), the wind chill created by going just 10 mph (16km/h) makes you as cold as if you were standing still at a temperature of -9°F (-23°C). At this temperature, exposed flesh will freeze in just a few minutes.

Continued exposure in the cold weather could lead to hypothermia.

Hypothermia occurs when your body's inner temperature drops. Symptoms include numbness in the extremities (hands, feet, arms, and legs), and shivering. Damp clothing contributes to hypothermia because cold water on your skin will drain heat from your body's core.

We strongly recommend that if you do any cold-weather riding, that you familiarize yourself with the symptoms, treatment, and prevention of hypothermia. Information is available at libraries and through government agencies.

Plan your winter rides with safety and comfort in mind. Dress for the worst conditions you might encounter. Be prepared for bad weather and ATV breakdowns. Wear warm, water-resistant clothing such as thermal underwear, snowmobile suits, lined gloves and boots, and wool socks.

⚠ WARNING

Wearing loose clothing when riding your ATV could be hazardous.

Loose clothing, such as a long scarf or shawl, could get caught in an ATV's moving parts.

Never wear loose clothing when riding your ATV.

Riding Your ATV on Snow and Ice

▲ WARNING

Riding on snow-covered terrain, even with care, could be hazardous.

The snow may be covering rocks, holes, ice or other hazards that can cause loss of control. Severe injury or death could occur if you lose control of the ATV.

Go slowly and be careful when riding on snow-covered terrain. Always be alert to changing terrain conditions.

▲ WARNING

Riding on a frozen lake or river could be hazardous.

Serious injury or death could occur if the ice breaks and you could fall into the cold water.

Check with local authorities to verify the thickness of the ice and areas to avoid.

▲ WARNING

Failing to use extra care when operating on slippery surfaces such as hard-packed snow and ice could be hazardous.

Failing to use extra care could cause loss of traction or loss of vehicle control. This could result in an accident, including an overturn.

Do not operate on slippery surfaces until you have learned and practiced the skills necessary to control the ATV on such terrain. Always use extra care on slippery surfaces. Avoid riding on the snow or ice covered hills whenever possible.

Practice riding your ATV in an open snow- or ice-covered area, at slow speeds, before handling out on snow- or ice-covered trails. Learn how your ATV responds to steering and braking on the type of terrain you will encounter on your ride.

Your eyes may be sensitive to sunlight when you ride over snow or ice on a bright, sunny day. Snow and ice reflects more light into your eyes than dirt or grass. Tinted eye protection will reduce the amount of light reaching your eyes. On overcast days, you may find it helpful to use yellow-tinted eye protection.

ACCESSORY USE AND VEHICLE LOADING

There are many types of accessories for sale. However, we cannot have direct control over their quality or suitability. We cannot test each accessory that is available. If you add the wrong accessories or misuse the vehicle with some accessories installed, it can make the ATV less safe to ride.

Be cautious when choosing and installing accessories to your vehicle. Your retailer may be able to help you choose accessories and install them correctly. The guidelines below should help you to decide how to equip your ATV and how to use it correctly when you use accessories.

▲ WARNING

Operating this ATV with improper modifications could be hazardous.

Improper installation of accessories or modifications of the vehicle may cause changes in handling which could lead to an accident.

Never modify the ATV with improper installation or use of improper accessories. All parts and accessories added to the ATV should be genuine parts or their equivalent designed for use on this ATV. Install and use them according to their instructions. If you have any questions, contact your retailer or Ricky Power Sports, LLC.

Accessory Use and Vehicle Loading Guidelines

1. The combined weight of the rider, tools, and any accessories or cargo plus the vertical weight on trailer hitch must never exceed the vehicle's load capacity of 165 Kg (364 lbs.).
2. Check accessory mounting brackets and other attachments to make sure they provide a rigid non-movable mount.
3. Accessories added to the handlebar of the ATV should be as light as possible. The extra weight would cause the vehicle to be harder to steer.
4. Do not add accessories or cargo which interferes with controls or other equipment.
5. Do not carry heavy or bulky cargo.
6. Distribute cargo weight evenly between the front and rear of the vehicle as well as both sides of the vehicle. Locate cargo weight as close to the center of the vehicle if possible.
7. Secure your load well. Shifting weight can affect your ability to handle the vehicle safely.
8. Ride at slow speeds and avoid hills when carrying cargo. Carrying loads would affect the stability and handling of your ATV.

9. Allow enough stopping distance. Stopping distance increases if you carry loads. Use engine braking as much as possible.

CANYON 250 WEIGHT LIMITS



Never exceed the weight limits shown

1. Total weight limit is 165 Kg (364 lbs); this limit includes rider, accessories, vertical weight on trailer hitch and cargo.
2. Front rack - 30 Kg (66 lbs.)
3. Rear rack - 45 Kg (99 lbs.)
4. Tool kit compartment - 1.7 Kg (3.75 lbs.)
5. Vertical weight on trailer hitch - 15 Kg (33 lbs.)

INSPECTION AND MAINTENANCE

It is very important to inspect and maintain your ATV regularly. Follow the guidelines in the chart. The intervals between periodic services in months are shown. At the end of each interval be sure to perform the maintenance listed.

MAINTENANCE SCHEDULE

Item	Initial 1 months	Initial 3 Months	Every 3 Months	Every 6 Months
Valves	I			I
Spark Plug		C	C	R
Air Filter	I Every 20 - 40 hours (more often in dusty areas)			
Carburetor		I		I
Cylinder head and breather hose				I
Exhaust system				I
Spark arrester				I
Fuel hose		I		I
Engine Oil	R			R
Engine Oil filter	C			C
Engine Oil strainer	C			C
Gear Oil	R			R
Brake Fluid level	I	I	I	
Brake Fluid Hose and joints		I	I	
Speed sensor		I		I
Brakes	I	I	I	
Clutch	I	I	I	
Wheels	I			I
Wheel bearings	I			I
Brake caliper linings and Brake pads	I	I	I	
Front and rear suspension				I
Steering system	I	I	I	
Bottom fitting of steering shaft - lubricate with lithium (Li) based grease)				L
Fittings and Fasteners	T	T	T	

I=Inspect and clean, adjust, lubricate or replace, if necessary.

C=Clean R=Replace T=Tighten L=Lubricate

▲ WARNING

Improper maintenance or failing to perform recommended maintenance could be hazardous.

If you perform improper maintenance or do not maintain your ATV you may have an accident.

Keep your ATV in good condition. Ask your authorized service center or a qualified mechanic to do the maintenance items marked with an asterisk (*). You may perform the unmarked maintenance items by referring to the instructions in this section if you have mechanical experience. If you are not sure how to do the maintenance ask your authorized service or call Ricky Power Sports, LLC.

CAUTION

If you use your ATV under severe conditions, it will need maintenance more often than shown in the chart.

Operating your ATV under severe conditions causes more wear on your ATV. Severe conditions include operating under frequent full throttle, or in dusty, wet, sandy, or muddy areas. These conditions could cause the ATV to wear more quickly.

Perform maintenance more often than shown in the chart. If you have any questions regarding maintenance intervals, consult your authorized service center or call Ricky Power Sports, LLC.

CAUTION

Using poor quality replacement parts could damage your ATV.

Poorly-made replacement parts could cause your ATV to wear more quickly and shorten its useful life.

When replacing parts on your vehicle, use only genuine replacement parts or their equivalent.

VALVE INSPECTION

Refer to maintenance schedule in this owner's manual for valve adjustment inspection intervals.

Valve clearance should be: 0.05mm

The engine will make excess noise if the gap is too large in air valve. If gap is too small valve operation will be hindered which could result in valve malfunction and failure. Therefore, air valve gap must be checked periodically.

If you have the proper tools and are mechanically proficient, instructions on adjusting the valve clearance are given in the service manual. If assistance is needed please contact Ricky Power Sports, LLC to find your local service center.

TOOLS



A tool kit is provided with your ATV.

SPARK PLUG

Your ATV is equipped with a TORCH D8RTC spark plug. To determine if the standard spark plug is in good condition, check the color of the plug's center electrode insulator after vehicle operation. A brown color indicates that the plug is correct. A white or dark insulator indicates that the engine may need adjustment, or another plug type may be needed. Consult your authorized dealer or Ricky Power Sports, LLC, if your plug insulator is not a light brown color.

CAUTION
<p>Failing to use the proper spark plug could damage your ATV.</p>
<p>An improper spark plug may have an incorrect fit or heat range for your engine. This may cause severe engine damage which voids the warranty.</p>
<p>Use only the spark plug recommended for this engine. Call Ricky Power Sports, LLC if you are not sure which spark plug is correct for you vehicle.</p>

NOTE: This ATV uses resistor-type spark plug to avoid jamming electronic parts. Improper spark plug selection may cause electronic interference with your ATVs ignition system, resulting in the vehicle performance problems. Use recommended spark plugs.

To install a spark plug turn it in as far as possible with your fingers, then tighten it with a wrench.

CAUTION

Improper installation of the spark plug could damage your ATV.

An overly tight or cross threaded spark plug will damage the aluminum threads of the cylinder head.


Carefully install spark plug by hand. If the spark plug is new, tighten it with a wrench about ½ turn past finger tight. If you are reusing the old spark plug, tighten it with a wrench about 1/8 turn past finger tight.

CAUTION

Dirt could damage your ATV if it entered an open spark plug hole of cylinder head.

Dirt could damage engine parts that move.

Cover the spark plug hole while the spark plug is out of the hole.



Spark Plug Cross Reference:

TORCH D8RTC ONLY

To maintain a proper functioning spark plug, keep the plug free of carbon.

Remove carbon from the plug with a wire or pin, and adjust the gap to 0.6~0.7mm (0.024 - 0.028 in) for a good ignition. Use a

thickness gauge to check the gap.

Battery Installation

INITIAL SERVICE AND INSTALLATION OF BATTERY:



▲ WARNING

The following procedure is very dangerous and should be performed with utmost care and attention. Wear protective eye wear, rubber gloves, and have water available should electrolyte come in contact with skin or eyes. **KEEP ALL CHILDREN AWAY FROM THE AREA WHILE THIS PROCEDURE IS BEING PERFORMED.**

POISON – CAUSES SEVERE BURNS

Contains sulfuric acid.

Avoid contact with skin, eyes, or clothing

To prevent accidents, rinse empty container with water.

ANTIDOTE:

External – flush with water

Internal – Call physician immediately. Drink large quantities of water or milk.

Follow with milk of magnesia, beaten eggs or vegetable.

Eyes – Flush with water for 15 minutes and get prompt medical attention.

KEEP OUT OF REACH OF CHILDREN.

Note: The following page is for vehicles with battery's containing separate electrolyte pack. Most battery's will come with the electrolyte already sealed into the battery.

Preparing the battery:

- Place battery on level surface. Remove sealing tape from top. (see figure 20)
- Take the electrolyte container out of the plastic bag.
- Place electrolyte container upside down with the



Figure 20

sealed silver mouths of the electrolyte bottles in line with the six filler holes of the battery. (see figure 21)

- Push the container down strongly enough to break the silver seals.
- As electrolyte starts flowing into battery, air bubbles will come up from the mouths of the plastic electrolyte bottles.
- Leave bottles upside down in battery holes until electrolyte is completely drained.
- Never leave children unattended around battery.
- If air bubbles cease to float to the top of the electrolyte bottles, tap lightly on top.
- **DO NOT** remove container from battery while it is draining.
- Never cut or pierce electrolyte container.
- After all the electrolyte has drained from the bottles into the battery, pull plastic electrolyte bottles gently out of the battery.



Figure 21

- Discard empty electrolyte bottles in a waste area that is inaccessible to children and animals.
- After filling let battery stand for at least 30 minutes before charging. This allows the electrolyte to penetrate plates for optimum performance and ensures longer battery life.
- After 30 minutes the battery is ready for its initial charge. Place cap strip loosely over the filling holes as shown in the picture. (see figure 22)



Figure 22

How to Initially Charge the battery:

1. Connect the red positive (+) cable to the red positive (+) pole of the battery.

(see figure 23)

2. Connect the black negative (-) cable to the black negative (-) pole of the battery. (see figure 24)

Note: The red positive (+) cable has a larger diameter than the black negative (-) cable.

3. Charging rate: Charge battery @ 0.7 Amps for 5 ~ 10 hours.

- After charging is complete, press down firmly with both hands to seat the caps. (Do not pound or hammer see figure 25)

The battery is now sealed.

- Locate battery compartment on ATV.

The battery compartment is located under the seat. Battery terminals should be facing the front (see figure 26).

- Once battery is firmly seated in battery compartment, attach red positive (+) cable to positive (+) terminal on battery.

Then attach black negative (-) cable to negative (-) terminal on battery (see figure 26).

- Secure battery with battery bracket (see figure 26).



Figure 23



Figure 25

⚠ WARNING
NEVER REMOVE THE STRIP OF CAPS NOR ADD ANY WATER OR ELECTROLYTE.




Figure 26

Battery Replacement:

- Remove old battery from under seat. The battery bracket will need to be removed (see figure 28). Mark which cable is connected to the positive terminal (+) and which cable is connected to the negative (-) terminal.
- Clean cable connectors with wire brush or sandpaper to remove oxidation.
- After charging, install new battery. Put dielectric grease on the battery terminals to avoid corrosion. Connect cables to the proper terminals. Positive cable to positive terminal A and negative cable to negative terminally.
- Positive (+) cable is red and larger in diameter. Negative y cable is black and smaller of the two in diameter. **CONNECT NEGATIVE CABLE LAST.**
- Torque terminal bolts to 40 in. /lbs.
- Securely fasten battery to the vehicle using metal battery strap.


⚠ WARNING

- **DO NOT** open sealed caps to add water to battery.
- **Always** wear safety glasses and charge in a ventilated area.
- If battery gets hot to the touch, discontinue charging and allow battery to cool down.
- Do not use fast charging unless it is an emergency.
- At the beginning or end of charging, turn off the charger first, in order to prevent electric spark and explosion.
- Charge in a well ventilated area.
- **DO NOT** smoke around batteries and keep away from open flame.

⚠ WARNING

- To avoid possibility of explosion, always connect battery cable in the order specified: **RED** first; **BLACK** last. An exploding battery can cause serious injury or death.
- Batteries contain sulfuric acid.
- **Always** shield eyes with protective eyewear when working around battery acid.
- Battery acid is poisonous and can cause severe burns.
- **DO NOT** smoke around batteries and keep away from open flame.

FUSE REPLACEMENT




Fuse may be bad if there is no spark while trying to start the ATV.

The fuse box is located under the seat directly in front of the battery.

To check fuse follow the instructions

- Turn off main key switch
- Lift seat and locate fuse box
- Remove fuse box cap
- Remove fuse and check. If fuse is bad, replace with 15 Amp fuse.

HEADLIGHT AND TAILLIGHT REPLACEMENT



Headlight bulb replacement.

- Turn off main key switch
- Locate headlights under front fender and slide back rubber moisture protector from headlight housing
- Push in bulb holder and turn left until tabs line up with groves .
- Remove bulb.

FUSE REPLACEMENT

Fuse may be bad if there is no spark while trying to start the ATV.

The fuse box is located under the seat directly in front of the battery.

To check fuse follow the instructions


- Turn off main key switch
- Lift seat and locate fuse box
- Remove fuse box cap

- Remove fuse and check. If fuse is bad, replace with 15 Amp fuse.


Moisture protector Bulb holder Bulb

Taillight replacement

- Turn off main key switch
- Locate screw holes in rear lens
- Remove lens
- Remove bulb by pushing in and turning left (CCW).



THE ADJUSTMENT OF THROTTLE LEVER



To adjust the throttle lever play:

1. Remove the adjuster cover (slide back on cable).
2. Loosen the throttle lever lock nut.
3. Turn the large adjustment nut in or out to obtain the correct play.
4. Tighten the throttle lever lock nut.
5. Recheck the throttle lever free distance.

Re-adjust it if it is not within the correct limits.

⚠ WARNING

Operating the vehicle with an inadequate throttle lever free play distance could be hazardous.

Inadequate throttle lever free distance could cause engine speed to rise suddenly when you turn the handlebars. This can lead the rider to lose control.

Adjust the throttle lever free distance so that engine idle speed does not rise due to handlebar movement.

IDLE SPEED ADJUSTMENT

To adjust the idle speed properly, you need a tachometer. If you do not have this one, ask your authorized service center to perform this adjustment.



Engine idle adjustment screw

To adjust the idle speed:

1. Start the engine and warm it up.
2. Turn the engine idle screw in or out so that the engine idle speed is at 1500r/min.

▲ WARNING

Improper adjustment of the idle speed could be hazardous.

An idle speed that is too high could cause the ATV to launch forward when you start the engine. This may cause an accident. Excessive engine wear may also result if idle speed is adjusted improperly or when the engine is not fully warmed up. Adjust the idle to the correct speed. Make sure the engine is fully warm before adjusting the engine idle speed.

FUEL HOSE

Fuel hose



Inspect the fuel hose for damage and fuel leakage. If any defects are found, the fuel hose must be replaced.


ENGINE OIL



To check oil level:

1. Park vehicle on level ground.

Oil cap and dipstick



2. Remove dip stick and wipe off with a clean rag. Insert the dipstick in the filler hole.

3. Remove the dipstick and inspect the oil level.

4. Oil level should be in between the minimum and maximum marks on the dipstick.


5. Add oil if oil is below minimum mark on dipstick. Do Not fill above maximum mark.

Refer to page 8 for correct engine oil type.


Engine oil replacement and oil filter element cleaning:

The engine oil should be changed every 20 to 40 hours of operation. It should be changed more often in dirty and dusty areas.

1. Park vehicle on level ground.
2. Remove oil dipstick



4. Remove oil filter cap
5. Remove oil filter



6. Clean oil strainer and oil filter with solvent.
7. Inspect rubber O-ring on the oil filter cap and replace if damaged.
8. Reinstall oil filter, O-ring and oil filter cover.
9. Reinstall oil strainer, spring and cap.
10. Torque drain plug to 18 ft.lbs. (24Nm) and reinstall oil filter cap.
11. Fill crankcase with specified oil. Refer to Pg.8 for correct oil.

▲ WARNING

New and used oil could be hazardous.

Children and pets may be harmed by swallowing new or used oil. Continuous contact with used oil can cause skin cancer in laboratory animals. Brief contact with the used oil may irritate the skin.

Keep new and used oil away from children and pets. To minimize your exposure to used oil, wear a long-sleeve shirt and moisture-proof gloves (such as dish washing gloves) when changing oil. If oil contacts your skin, wash thoroughly with soap and water. Launder any clothing or rags if wet with oil. Recycle or properly dispose of used oil.

CAUTION

Failure to use the correct oil could harm your ATV.

Be sure to use the oil specified in the FUEL AND OIL section.

CAUTION

Running the engine without an adequate amount of engine oil could cause severe engine damage.

Running the engine without any engine oil could cause engine overheating.

Always check the amount of engine oil before starting the engine.

AIR FILTER

The air filter element must be kept clean to provide good engine power. If you use your vehicle under normal, low-tension conditions, you should service the air filter at the intervals specified. If you ride in dusty, wet, or muddy conditions, you will need to inspect the air filter element much more frequently. Use the following procedures to remove the element, inspect it and clean it.

▲ WARNING

Operating the engine without the air filter element in place could be hazardous.

If the air filter element did not filter dirt, severe engine damage would occur if the dirt entered the running engine.

Never run the engine without the air filter element in place.

CAUTION


Failing to inspect the air filter element frequently if the vehicle is used in dusty, wet, or muddy conditions could damage your ATV.

The air filter element could become clogged under these conditions, and engine damage may result.

Always check the air filter element after riding in severe conditions. Clean or replace the elements as necessary. If water gets in the air filter case, immediately clean the element and the inside of the case.

AIR FILTER CHECKING

There is a clear air filter check cap at the bottom of the air filter case. If there is dust or water in this cap, empty the cap and clean the air filter element and case.




Air filter check cap

AIR FILTER REMOVAL AND CLEANING



1. Locate Air Filter Box under seat and remove cover.
2. Remove air filter.
3. Remove foam cover from Air filter element.
4. Tap the Air filter element gently to remove most of the dust and dirt.



Blow out remaining dust with compressed air.

If the element is damaged, replace it.

5. Wash the foam cover per instructions below.
6. Reinstall foam cover to the air filter element.
7. Reinstall air filter and close cover. Make sure that the element is securely in position and the air filter is properly sealed.

Washing Foam Cover OF AIR FILTER ELEMENT



To wash the foam cover:

1. Remove foam cover from air filter element.
2. Wash foam cover gently in water or a mild non flammable solvent
3. Squeeze water out of foam cover and let dry.
4. Reinstall foam cover over air filter Element

CAUTION

A torn air filter could damage your ATV.

Dirt and dust may get inside of the engine if the element is torn.

Examine carefully the element for tears before and after cleaning it.
Replace the element with a new one if it is torn.

⚠ WARNING

Oil and solvent could be hazardous.

Children and pets could be harmed if they have access to oil or solvent.

Be sure to keep oil and solvent away from children and pets. Dispose of used oil and solvent properly.


CAUTION

Failing to position the air cleaner element properly could damage your ATV.

Air will bypass the air cleaner element if the element is not positioned properly. This will cause the engine parts to wear more rapidly.

Be sure to position the air cleaner element properly.

CLUTCH ADJUSTMENT




1. Loosen lock nut
2. Slowly rotate adjusting bolt left until resistance is felt., then rotate 1/8 turn 45 deg. right.
3. Tighten the lock nut to the specified value 15Nm (10.8 ft.lb).

REAR GEAR CASE LUBRICATION

To check rear gear case oil:

1. Place vehicle on level ground
2. Remove gear case fill cap.
3. Inspect oil level. Oil level should be up to the brim of the hole.
4. If oil is low, add specified oil (SAE 80 API G- 4 Hypoid gear oil).
5. Tighten fill cap to 23Nm (17ft.lb)



Gear cover



Drain plug

To change gear oil:

1. Place vehicle on level ground
2. Remove gear case cover.
3. Place container under gear case.
4. Remove fill cap.
5. Remove oil plug.
6. Let oil drain out completely
7. Install the drain plug and tighten 24Nm (18 ft lb).
8. Install gear cover and tighten bolts
9. Add gear oil (SAE 80 API G-4 Hypoid Gear oil) fill to brim of hole approx. 9 oz (266ml)
10. Install fill cap and tighten to 23Nm (17 ft lb.)

CAUTION

Failing to have the proper amount of gear oil in the rear transfer case will damage your ATV.

Low or no gear oil will cause wear on the gears causing gears to seize.

Be sure to check for leaks in the gear case and keep oil up to the prescribed level.

TIRES

▲ WARNING

Operating this ATV with improper tires, or with improper or uneven tire pressure.

Use of improper tires on this ATV, or operation of this ATV with improper or uneven tire pressure, may cause loss of control, increasing your risk of an accident.

Always use the size and type of tires specified. Always maintain proper tire air pressure as described in this section.

▲ WARNING

Using worn tires could be hazardous.

The traction of the vehicle will be decreased. This increases your risk of having an accident.

Replace the front and rear tires when the depth on the tread is 4.0 mm (0.16 inches) or less.

▲ WARNING

Operating this ATV with improper modifications.


Improper installation of accessories or modifications to this vehicle may cause changes in handling which in some situations could lead to an accident.

Never modify this ATV through improper installation or use of accessories. All parts and accessories added to this vehicle should be genuine Ricky Power Sports, LLC or equivalent components designed for use on this ATV and should be installed and used according to instructions. If you have questions, consult a Ricky Power Sports, LLC authorized ATV dealer.

The ATV is equipped with low pressure tubeless tires of the size and type listed below:

	Front	Rear
Size	AT23*7-10	AT22*10-10

Tire Tread Condition



▲ WARNING

Overfilling the tires with air could be hazardous.

If you put too much air into the tire, the tire may burst causing severe injury.

Check the air pressure from time to time while gradually inflating the tire, until the specified air pressure is obtained.

Tire Air Pressure

Check the air pressure in all tires before riding. Improper air pressure would effect handling, steering response, traction, tire life and rider comfort. Be sure that the tires are inflated to the pressures shown below. Tire pressure should only be measured or adjusted when the tires are cold.

	Recommended pressure	Minimum	Maximum
Front	20kpa (3psi)	17kpa (2.5psi)	23kpa (3.3psi)
Rear	24kpa (3.5psi)	23kpa (3.3psi)	28kpa (4.0psi)

▲ WARNING

Overloading this ATV or carrying or towing cargo improperly.

Could cause changes in vehicle handling which could lead to an accident.

Never exceed the stated load capacity for this ATV.

Cargo should be properly distributed and securely attached.

Reduce speed when carrying cargo. Allow greater distance for braking.

Always follow the instructions in your owner's manual for carrying cargo.

Tire Replacement

Your ATV has low-pressure tubeless tires. Air is sealed by the contact surfaces of the inner wheel rim and the tire bead. If the inner wheel rim or tire bead is damaged, air may leak. Be extremely careful not to damage these sections when replacing tires.

It is very important to use the proper tools when repairing or replacing tires in order to protect the tire bead or wheel rims. Have this work done by your authorized service center or a qualified tire repair station.

When breaking the tire bead loose from the wheel, be extremely careful not to damage the inner wheel rim surface or the tire bead.

⚠ WARNING

Using tires that have been installed incorrectly could be hazardous.

The ATV may have unusual handling if the tires are installed incorrectly.

The tires are intended to rotate in a specific direction, as indicated by the arrows on the sidewall of each tire. Install tires correctly so they rotate in the proper direction.

Tubeless Tire Repair

If a leak or flat tire occurs due to a puncture, the tire may be repaired using a plug type patch. If the damage is from a cut, or if the puncture cannot be repaired using a plug, the tire should be replaced. When operating your ATV in areas where transportation or service facilities are not readily available, it is strongly recommended that you bring a plug type repair kit and a tire air pump with you.

BRAKING

The ATV has two front disc brakes and one rear drum brake.

▲ WARNING

Failing to inspect and maintain your ATV's brake system properly could be hazardous.

Improper maintenance of the brake increases your chance of having an accident.

Be sure to inspect the brake before riding according to the **INSPECTION BEFORE RIDING** section. Always maintain your brakes according to the **MAINTENANCE SCHEDULE**.


▲ WARNING

Operating the ATV in harsh conditions could be hazardous if you do not inspect brake wear often.

Operating in mud, water, sand, or other extreme conditions can cause accelerated brake wear. This could lead to an accident.


If you operate your vehicle under these conditions, the brake must be inspected more often than recommended in the **MAINTENANCE SCHEDULE**.

FRONT HYDRAULIC DISK BRAKE INSPECTION



1. Inspect the front disk brake caliper and brake fluid reservoir for leakage. If brake fluid leaks, the safety of riding could be affected.
2. Inspect the brake hose for cracks, and the joint for leakage.
3. Check the brake fluid level in the brake fluid reservoir, if level is at or below the LOWER mark, inspect brake pads for wear and hydraulic system for leaks.
4. To add brake fluid, unscrew the 4 screws on top of the brake fluid container. Add DOT3 or DOT4 brake fluid. Do not mix brake fluid types.

REAR BRAKES



REAR HAND AND FOOT BRAKE ADJUSTMENT

1. Try to move the vehicle backward and forward when the rear hand brake is applied. If the rear wheels can turn, adjust the brake to lock the wheels securely.
2. Measure the amount of free play in the rear hand brake lever. The free play should be about 5~7mm (0.2~0.3in).
3. Try to move the vehicle backward and forward when the rear foot brake is applied. If the rear wheels can turn, adjust the brake to lock the wheels securely.
4. After any adjustment of the brake




Brake rod adjustment nut (foot brake)

Brake cable adjustment nut (hand brake)

adjustment nuts, check again to make sure the front rear wheels cannot turn when the brake is applied.

REAR BRAKE SHOE INSPECTION

1. Locate brake wear indicator on outside of brake drum.
2. Check the position of the needle to see if it has reached the maximum wear limit.
3. If maximum wear limit has been reached (needle is at the end of the brake wear indicator), replace brake shoes as a set.




⚠ WARNING

Failing to maintain the brake shoes, the brake pads and the calipers could be hazardous.


Riding with worn brake shoes or pads, will increase your chance of having an accident.

If you need to replace brake shoe or pads, have your authorized service center do the work. Inspecting and maintaining the brake shoes, the brake pads and the calipers is recommended. Replace the shoe and the pads in sets.


SPARK ARRESTER CLEANING



1. Take out the spark arrester by unscrewing (screwdriver).



2. Three screws and spark arrester.



3. Clean out the carbon deposit on the surface of spark arrester by wire brush.



4. Assemble the spark arrester after clean.

▲ WARNING

The hot exhaust muffler could burn you.

The muffler will be hot enough to burn you after stopping the engine.

Wait until the exhaust muffler cools to remove the dowel.

▲ WARNING

Running the engine indoors or in a garage could be hazardous.

Exhaust gas contains carbon monoxide that is colorless and odorless. It could cause serious injury or death.

Only run the engine outdoors where there is fresh air.

▲ WARNING

Riding an ATV with improperly tightened drain bolt could be hazardous.

Running the engine with a loose drain bolt or without a drain bolt will let hot carbon particles to escape. This can cause a fire.

Tighten the drain bolt securely.

GENERAL LUBRICATION

Proper lubrication is important for safe, smooth operation and long life of your vehicle. Be sure that all lubrication is performed during periodic maintenance on the vehicle. Increase number of intervals when you use your ATV in severe conditions. Your authorized service center should do general lubrication as shown in the MAINTENANCE CHART. The authorized service center will do general lubrication. This includes the lubrication of wheel bearings, swing arm bearings, steering shaft holder, cables, etc.

OOil

GGrease

- 1 Bottom fitting of steering shaft – lubricate with lithium (Li) based grease)
- 2 Brake cable
- 3 Throttle cable
- 4 Throttle lever

TROUBLESHOOTING

This troubleshooting guide is provided to help you to find the cause of some common complaints.

COMPLAINT: Engine is hard to start or does not start at all. Something is probably wrong with the fuel system or ignition system.

CAUTION

Failing to troubleshoot a problem correctly would damage your ATV.

Improper repairs or adjustments may damage the vehicle. Such damage may not be covered under warranty. If you are not sure about the proper action, consult your authorized service center or Ricky Power Sports, LLC about the problem.

Fuel Supplying Check

1. Make sure there is adequate fuel in the fuel tank.
2. Check that the engine stop switch is in the "RUN " position.
3. Check that the fuel valve is in the "ON" position.
4. Make sure there is enough fuel reaching the carburetor from the fuel tank.

▲ WARNING

Draining fuel from the carburetor could be hazardous.

Fuel could catch fire if you do not handle it properly.

When draining the carburetor, be sure to shut the engine off. Do not smoke, and never drain or refuel in an area where there are open flames or sparks. Do not spill the fuel or you may create a fire hazard. Dispose of drained fuel properly.

- a. Loosen the drain screw which is located under the carburetor. Drain the fuel from the carburetor into a container.
- b. Tighten the drain screw.
- c. Run the engine for a few seconds. Shut off engine.
- d. Loosen the drain screw and check that the carburetor is filled back up with fuel.
- e. If fuel is reaching the carburetor, the ignition system should be checked next.

Ignition System Check

1. Remove the spark plug and reattach it to the spark plug lead.



2. Apply the rear brake lever to make sure the rear wheels are locked. Turn ignition key to the “ON” position. Slide the engine stop switch to the “RUN” position. Push the electric button “START “(yellow button). If the ignition system is operating properly, a blue spark should jump across the spark plug gap. If there is no spark, take your machine to your service center.

▲ WARNING

Performing the spark test improperly could be hazardous.

You could get a high voltage electrical shock if you are not familiar with this procedure.

Do not perform this check if you are not familiar with the procedure. Do not hold the spark plug near the spark plug hole during this test. Do not do this test if you have a heart condition or wear a pacemaker. Do not perform this test is any near any open fuel containers for near fuel which has spilled on the ground, on the engine, or any part of the ATV.

COMPLAINT: Engine stalls

1. Make sure there is enough fuel in the fuel tank.
2. Check to see that the spark plug is not fouled. Remove the spark plug and clean it. Replace it, if necessary.
3. Make sure the fuel valve is not clogged, and the fuel tank is not clogged, either.
4. Check the idle speed. If necessary, adjust it using a tachometer. The correct idle speed is 1500 r/min.
5. Make sure the air filter is clean.

TRANSPORTING

It is best to transport the ATV in the normal position.



Before transporting the ATV drain the fuel from the carburetor as follows:

1. Drain fuel from carburetor into an empty container by loosening the carburetor drain screw.
2. When the fuel has been drained, retighten the drain screw.

▲ WARNING

Draining fuel from the carburetor could be hazardous.

Fuel could catch fire if you do not handle it properly.

When draining fuel from the carburetor, be sure to shut the engine off. Do not smoke, and never drain or refuel in an area where there are open flames or sparks. Do not spill the fuel or you may create a fire hazard. Dispose of the drained fuel properly.

CAUTION

Failing to secure the ATV properly could be hazardous.

Failing to secure the vehicle properly may result in an accident or damage to the vehicle.

When transporting the ATV, lock the parking brake lever and tie down the vehicle securely with straps, rope, or some other suitable means. Use extra tie downs when you transport the vehicle in the standing position.

CLEANING PROCEDURE

A thorough cleaning of your ATV is a necessary part of maintenance. It will help keep your ATV looking and performing best. Proper cleaning can also extend the life of your ATV.

It is important to clean and inspect your ATV after every ride, especially if it is used in mud, brush, grass, water, salt water, or very dusty conditions

The build-up of mud, brush, grass, etc. especially on the engine and exhaust system, can reduce engine cooling ability, conceal damage, or increase wear of certain parts.

It is important to remove all debris during cleaning.

PREPARATION FOR CLEANING

Wash the ATV before any mud dries on the ATV.

Block or seal the end of the exhaust pipe (muffler) using a piece of plastic wrap, cloth rag or another method to prevent water from entering engine.

CAUTION

High pressure washers could damage your ATV.

High pressure washers such as those found at coin-operated car washes have enough pressure to damage the parts of your ATV. It may cause rust, corrosion and increase wear.

Do not use high pressure washers to clean your ATV.

WASHING YOUR ATV

With some care, your ATV can be washed in a similar manner to washing an automobile.

NOTE: Avoid spraying or allowing water to flow over the following places:

- Ignition switch
- Spark plug
- Fuel tank cap
- Carburetor
- Air filter

Use a garden hose at low pressure to remove the majority of dirt or other debris. Hand wash your ATV with mild soap or detergent and water. Try to thoroughly remove all dirt and debris without excessive water pressure, even at remote areas such as between engine cooling fins, linkages or mounting brackets. Cloth rags, washing mitts or cleaning brushes can be used. Be careful with brushes as they may scratch plastic or painted surfaces. Rinse the ATV thoroughly with clean water. Dry all areas using a chamois or soft absorbent cloth.

INSPECTION AFTER CLEANING

Remove the rags or wrapping from the exhaust pipe. For extended life of your ATV, lubricate according to GENERAL LUBRICATION section.

Follow the procedures in the INSPECTION BEFORE RIDING section to check your ATV for any problems that may have occurred during your last ride.

▲ WARNING

Operating the ATV with wet brakes could be hazardous.

Wet brakes may not provide as much stopping power as dry brakes. This could lead to an accident.

Test your brakes after washing the ATV, riding at a slow speed. If necessary, apply brake several times to let the friction dry out the linings.

STORAGE PROCEDURE

If you do not use your ATV for a long time, it will need special service requiring appropriate materials, equipment and skill. For this reason, we recommend that you trust this maintenance work to your authorized service center. If you wish to service the machine for storage yourself, follow the general guidelines below:

VEHICLE

Place the vehicle on level ground and wash the entire vehicle.

FUEL

Drain the fuel from the fuel tank by a hand pump. Drain the fuel from the carburetor by releasing the carburetor drain screw.

▲ WARNING

Draining the fuel could be hazardous.

Fuel could catch fire if you do not handle it properly.

When draining the fuel from the fuel tank, be sure to shut the engine off. Do not smoke, and never drain fuel in an area where there are open flames or sparks. Keep pets and children away from the fuel, and dispose of the drained fuel properly.

TIRES

Inflate tires to the normal pressure.

EXTERNAL

1. Spray all vinyl and rubber parts with rubber protection.
2. Spray unpainted surfaces with rust preventative.
3. Coat painted surfaces with car wax.


PROCEDURE FOR RETURNING TO SERVICE

1. Clean the entire vehicle.
2. Make sure that the vehicle is properly lubricated.
3. Perform the INSPECTION BEFORE RIDING as listed in this manual.
4. Start the vehicle as outlined in this manual.

SERIAL NUMBER LOCATION

You need to know the frame and engine serial numbers to get title documents for your ATV. You also need these numbers to help your authorized service center or Ricky Power Sports, LLC order parts.

The frame/VIN number is stamped on the front of the ATV frame as shown in the photograph. The engine serial number is located on the right side of the engine housing.



Frame number

Engine serial number



Write down the serial numbers here for your future reference

Frame No.:

Engine No.:

SPECIFICATIONS

DIMENSIONS AND DRY MASS

Overall length.....	1930mm
Overall width.....	1020mm
Overall height.....	1170mm
Wheelbase.....	1170mm
Ground clearance.....	220mm
Minumum turning radius.....	2913mm
Seat height	810mm
Dry weight	232Kg

ENGINE

Type.....	Four stroke,
Cooling.....	Air cooled
Number of cylinders.....	1
Bore X Stroke.....	71mm x 58mm
Displacement.....	229 cm3
Compression ratio.....	8.7:1
Carburetor.....	Injection Type
Air cleaner.....	Foam

TRANSMISSION

Transmission Type.....	Automatic clutch
5 - speed forward, 1 - speed reverse	
Operation.....	Left foot

GEAR RATIO:

1st.....	34/12 (2.833)
2nd.....	34/19 (1.789)
3rd.....	29/22 (1.318)
4th.....	26/25 (1.040)
5th.....	23/28 (0.821)
Reverse.....	73/22 x 34/12x19/18 x 46/11 (41.5)

ELECTRICAL

Ignition type.....	CDI
Generator system.....	A.C. Magneto
Battery type, voltage, capacity.....	14AH
Headlight.....	12V

Taillight.....12V

Neutral indicator.....12V

Reverse indicator.....12V

High beam indicator.....12V

OIL

Periodic engine oil change.....53 oz (1.5L)

with oil filter replacement.....56 oz (1.6L)

Total amount of engine oil.....63 oz (1.8L)

Total amount of gear oil.....9 oz (0.266L)

FUEL

Main fuel tank capacity.....2.64 gallons (9L)

Reserve fuel tank capacity.....0.35 gallons (1.3L)

BRAKES

Front brake type.....Hydraulic disc brake

Operation.....Right hand operation

Rear brake type.....Drum brake

Operation.....Right foot operation

SUSPENSION

Front.....2 Spring oil dampener
shocks

Rear.....1 Spring oil dampener
shock

Front suspension travel.....12.5mm (0.49 in)

Rear suspension travel.....13.5mm (0.53 in)

TIRES

Size Front.....AT23x7-10

Size Rear.....AT22x10-10

FRAME

Frame type.....Steel Tube

Ricky Power Sports, LLC – EMISSION CONTROL SYSTEM WARRANTY

YOUR WARRANTY RIGHTS AND OBLIGATIONS

The emission control system warranty period for this vehicle begins on the date the vehicle is delivered to the first purchaser other than an authorized dealer, or the date it is first used as a demonstrator, lease, or company vehicle, whichever comes first and continues for 5 years after that date, or 10,000km, whichever comes first, provided there has been no abuse, neglect or improper maintenance of your vehicle. Where a warrantable condition exists, the Distributor will repair your vehicle at no cost to you, including diagnosis, parts and labor. If an emission-related part on your vehicle is defective, the part will be repaired or replaced by the Distributor. This is your emission control defects warranty.

OWNER'S WARRANTY RESPONSIBILITIES

As the vehicle owner, you are responsible for the performance of the required maintenance. You should maintain a record of all maintenance performed on your vehicle and retain all receipts covering maintenance on your vehicle. You may not be denied a warranty claim solely because of your failure to ensure the performance of all scheduled maintenance or lack of maintenance records or receipts. You are responsible for presenting your vehicle to an authorized dealer as soon as a problem exists. The warranty repairs should be completed in a reasonable amount of time, not to exceed 30 days.

As the vehicle owner, you should be aware that you may be denied your warranty coverage if your vehicle or a part has failed due to abuse, neglect, improper maintenance, or unapproved modifications.

WARRANTY COVERAGE

The Distributor warrants that each new 2022 and later vehicle:

- is designed, built, and equipped so as to conform at the time of initial retail purchase with all applicable regulations of the United States Environmental Protection Agency, ; and
- is free from defects in material and workmanship which cause such vehicle to fail to conform with applicable regulations of the United States Environmental Protection Agency for the periods specified above.

Your emission control system warranty covers components whose failure would increase an engine's emission, including electronic controls, fuel injection system, carburetor, the ignition system, catalytic converter, or any other system utilized in this vehicle to control emission if it is originally equipped. Also included may be hoses, connectors and other emission-related assemblies.

Replacing or repairing other components (including parts, labor, and other costs) not covered by this emission control system warranty or the standard warranty is the responsibility of the owner.

Coverage of repairs under this warranty applies only when repairs are completed at an authorized dealer or repair facility. The Distributor will not cover repairs performed outside of an authorized dealer or repair facility. The use of replacement parts not equivalent to the original parts may impair the effectiveness of your vehicle's emission control system. If such a replacement part is

used and an authorized dealer determines it is defective or causes a failure of a warranted part, your claim for repair to bring your vehicle into compliance with applicable standards may be denied.

This Emission Control System Warranty is in addition to the standard Limited Warranty.

EXCLUSIONS AND LIMITATIONS

This warranty does not cover the following:

- Failures or malfunctions of the emission control systems caused by abuse, alteration, accident, misuse, the use of leaded gasoline.
- Replacement of expendable maintenance items unless they are original equipment defective in material or workmanship under normal use, and the first required replacement interval for the item has not been reached. Expendable maintenance items include but not limited to spark plugs, filters, coolant, lubricants, gaskets, hoses, and belts.
- Replacements of parts and other services and adjustments for required maintenance.
- Any vehicle equipped with an odometer or hour meter where the reading is altered so that actual mileage cannot be readily determined.
- Repairs or replacements as a result of:
 - o Accident
 - o Misuse
 - o Use of replacement parts or accessories not conforming to the original specifications which adversely affect performance
- Physical damage, corrosion, or defects caused by fire, explosions or similar causes beyond the control of the Distributor.
- Failures not caused by a defect in material or workmanship.

Use of the vehicle in any type of competitive racing or related events immediately and completely voids this and all other warranties.

LIMITED LIABILITY

The liability of the Distributor under this Emission Control System Warranty is limited solely to the remedying of defects in material workmanship by an authorized dealer at its place of business during customary business hours. This warranty does not cover inconvenience or loss of use of the vehicle or transportation of the vehicle to/from the authorized dealer. The Distributor is not liable to any person for incidental, consequential or special damages of any description, whether arising out of express or implied warranty or any other contract, negligence or other tort or otherwise.

No express emission control system warranty is given by the Distributor except as specifically set forth herein. Any emission control system warranty implied by law, including any warranty of merchantability or fitness for a particular purpose is limited to the express emission control system warranty terms stated in this warranty. The foregoing statements of warranty are exclusive and in lieu of all other remedies. All express warranties not stated in this warranty are disclaimed.

Some states do not allow limitations on how long an implied warranty lasts, so the above limitations may not apply if it is inconsistent with the controlling state law.

No dealer is authorized to modify this Emission Control System Warranty. If you have any questions regarding your warranty rights and responsibilities, you should contact Ricky Power Sports, LLC 1- 844-250-2199