LOCAL AUTHORITY BUILDING CONTROL REGISTERED

U-VALUE SOLUTIONS AS LOW AS UO.10

IDEAL FOR NEW BUILD OR RETROFIT

ROOF **R3.47**

R3.91

R5.22

USAGE



Super**FOIL**.co.uk



KEY FEATURES

- SF40 SuperFOIL has LABC Registered System Approval.
- SF40 SuperFOIL has an R value of 3.47 in pitch roofs & 3.91 in walls.
- Dupont ultra efficient nano coating technology.
- SF40 SuperFOIL also acts as a radiant barrier to reflect excessive heat gain during the summer months as well as insulating throughout the year.
- 'DUET' Installation An over and under the rafter application consisting of two layers of SuperFOIL. SF40 + SF40 provides a U-value of 0.14.
- 'COMBI' Installation Use SuperFOIL with any other insulation including mineral wool or foam board to achieve any required insulation U-value.
- SF40 SuperFOIL is ideal for use in walls and roof structures in new build and in renovation, refurbishment / extension projects.
- SF40's technical specification means high performance from a small footprint.
- Easy installation results in minimal waste. Superfoil is manufactured with 40% recycled materials and is recyclable at the end of its useful life.



TECHNICAL

PRODUCT DIMENSIONS	
Thickness	65mm
Length	10m
Width	1.5m
Coverage	15sqm
Weight	17.5kg
Sizes / Figures are sparaximate & Subject to change without notice, tolerance +/-57 FIRE PERFORIMANCE	*
Reaction to Fire (Euroclass)	Class E (behind plasterboard)

THERMAL PERFORMANCE	
Core	2.57 R Value
Roof (inc. air spaces)	3.47 R Value
Wall (inc. air spaces)	3.91 R Value
Floor (inc. air spaces)	5.22 R Value
Emittance	0.05

ADDITIONAL INFO	
Water Vapour Resistance	1200MNs/g
Resistance to water penetration	W1
Flexibility at low temp.	-40c
Tensile Properties - Length (After Ageing)	635 N/50mm
Tensile Properties - Width (After Ageing)	580 N/50mm











