

01/2021

	contains	m ²	ft ²	weight
1 pack Ocean	9 planks	2,20 m ²	23.71 ft ²	15,7 kg
1 pallet Ocean	56 packs	123,34 m ²	1327.61 ft ²	891 kg



product specifications

Dimensions	1288 x 190 mm
Total thickness	8 mm
Bevels	0
Loc System	DuoLoc
Level of use according to European standard EN13329	23 heavy domestic use
	32 general commercial use
Residential warranty	lifetime
Commercial warranty	5 years

Warranty conditions on www.berryalloc.com

composition


Surface layer	Direct laminated paper, impregnated with melamine resin
Substrate	Moisture resistant High Density Fiberboard (HDF) treated with hydro+ water repelling technology
Backing	Direct laminated paper, impregnated with melamine resin

test results

Abrasion resistance	EN13329	AC4 (IP≥4000)
Impact resistance	EN13329	Small ball : ≥ 12 N - Big ball : ≥ 750 mm
Thickness swelling	EN13329	12% (requirement ≤ 18%)
Fire resistance	EN14041	Cfl-S1
Formaldehyde emission	EN14041	E1
Slip resistance	EN14041	DS
Density	EN323	900 kg/m ³
Resistance to staining	EN438	5 (groups 1+2) ; 4 (group 3)
Effect of a furniture leg	EN424	No damage (foot type 0)
Effect of a castor chair	EN425	No change in appearance or damage
Thermal resistance in combination with underlay Excellence Plus	ISO 8302	0,08 m ² K/W – Suitable for floor heating/cooling. Detailed instructions on www.berryalloc.com

certificates/labels

- DOP : 170-DPLA18-1
- Sustainability of forests : PEFC certified (07-31-229)
- Labelling according to French VOC emission regulation: A+



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).