



TRUMPET MM

Phonostage



Made in USA

Copyrights & Trademarks

© Copyright Hagerman Audio Labs 2023. All rights reserved. No part of this document may be photocopied, reproduced, or translated to another language without prior written consent.

Disclaimer

The information contained in this document is subject to change without notice. Hagerman Audio Labs shall not be liable for errors contained herein or for consequential damages in connection with the furnishing, performance, or use of this material.

Warranty

Hagerman Audio Labs warrants this product free of defects in materials and workmanship for a period of 5 years (tubes 90 days). If you discover a defect, Hagerman Audio Labs will, at its option, repair or replace the product at no charge to you provided you return it during the warranty period, transportation charges prepaid to Hagerman Audio Labs. This warranty does not apply if the product has been damaged by negligence, accident, abuse or misuse or misapplication, has been damaged because it has been improperly connected to other equipment or has been modified without the express written permission of Hagerman Audio Labs. This warranty is limited to the replacement or repair of this product and not to damage to equipment of other manufacturers. Any applicable implied warranties, including warranty of merchantability, are limited in duration to a period of the express warranty as provided herein beginning with the original date of purchase and no warranties, whether express or implied shall apply to the product thereafter. Under no circumstances shall Hagerman Audio Labs be liable for any loss, direct, indirect, incidental, special, or consequential damage arising out of or in connection with the use of this product.

Hagerman Audio Labs

1521 Alexander St Apt 1701

Honolulu, HI 96822

808-383-2704

www.haglabs.com

Description

The Trumpet MM is a world-class phonostage suitable for the most demanding of audiophiles. This 3rd generation model maintains the superb sonic performance of the original, while cleverly cutting costs via technological advancements. The circuit remains fully balanced from input to output, including power supply. Equalization is split-passive with no feedback employed anywhere, resulting in a neutral non-fatiguing sonic presentation. Heaters are DC and a highly specialized internal low-noise boost converter generates B+ and B- rails (after a 40-second delay). Premium components are used throughout, such as polypropylene capacitors and metal film resistors. The aluminum chassis has a rugged powdercoat and is designed to match the Tuba.

Specifications

Item	Specification
Resistive Loading	47k
Capacitive Loading	50pF
Gain	44dB
Distortion	0.04% @ 3Vrms
Output	22Vrms @ 1% distortion
Equalization	+/-0.5dB
Tube Compliment	12AX7 x 4, 12AU7 x 2
Weight	3 lbs
Size	6 x 10 x 3.5 inches
Power	15Vdc @ 2A (included)

Tubes

Install tubes into positions as shown (12AU7 towards rear).



