



TESTIMONIAL

"The purpose of a fit test is not just to see if a particular size/make/model of masks fits an employee's face well, but also to ensure the employee can put it on correctly in a way that consistently provides a good seal.

The growth of my small company has been built on a reputation for providing a high level of expertise and attention to detail to a diverse base of respirator users, from construction workers to first responders.

The use of OHD's controlled negative pressure technology has been an important part of our success, and their customer service team has been behind us every step of the way."

Carlo Emami,
(Safewest) Instructor/Trainer

QUANTIFIT

The Industry Leader in Mask Fit Testing.

For first responders, there's no substitute for safety. Created for durability and portability, it's modern design is more streamlined and lighter than previous models. The Quantifit package includes a carrying case, keyboard, onboard memory and PC connections, as well as other unmatched features that make it reliable and easy to use, dramatically improving your respirator program. No other quantitative fit test instrument comes close.

Within the first ten seconds of testing, the Quantifit can determine whether the respirator user has a basic fit or not. And the OSHA-accepted Controlled Negative Pressure CNP Redon protocol takes as little as three minutes. If other quantitative fit test instruments measured accuracies of less than 40%, why put your employees at risk?

HERE'S HOW THE QUANTIFIT WORKS?

During a fit test, the respirator inlets are capped with test adapters, and the inhalation valves are propped open or removed from the mask. With the test subject holding his or her breath for no more than ten seconds, the Quantifit then establishes and maintains a slight vacuum, or controlled negative pressure, inside the mask. Since the respirator inlets are sealed, all sources of leakage into the mask are through the face-to-facepiece seal or due to integrity issues. The volume of air drawn out of the mask by the Quantifit during this short period of time is equal to the leak rate into the mask through the face-to-facepiece seal.



WHERE **EQUIPMENT** MATCHES **COURAGE**

5205, J.-Armand Bombardier, Longueuil, Québec J3Z 1G4, 1-800-469-1963
www.areo-fire.com



TESTIMONIAL

"I wanted to thank you for all of your assistance in our migration to the Quantifit Fit Test Machine. As we start to migrate over to the newer machine we are finding that we are able to perform the fit tests in about half the time, or less, from what it was taking us before. Since we perform about 5,000 fit tests annually, we will see a reduction in overtime costs and a real-time savings for staff as well.

As you know both myself and my staff spent a lot of time researching the available products for fit testing and chose to use the OHD Quantifit. This decision was made based off several factors including immediate cost, long term operating costs, customer service, ease of use and ease of training, and the time involved in each actual test.

The Quantifit was the clear winner for our needs."

*Bill Merritt, directeur exécutif,
Conformité environnementale, sécurité
et opérations d'urgence, Department
of Corrections du Maryland.*

QUANTIFIT

The Industry Leader in Mask Fit Testing.

FEATURES & BENEFITS

PROVEN TECHNOLOGY

The OHD Quantifit is a highly specialized instrument which utilizes the scientifically-proven and patented CNP (Controlled Negative Pressure) technology to directly measure respirator leakage. The OHD Quantifit is accepted by OSHA and appears in the Federal Regulations governing fit testing [29 CFR 1910.134]. The Quantifit is also included in the Canadian Standards [CSA Z94.4-2011] and UK HSE Standards [EN132-149], as well as ANSI Z88.10-2010.



FASTEST FIT TESTING AVAILABLE

With the OSHA-approved CNP REDON respirator fit test protocol, a fit test can be performed in as little as 2-3 minutes with no waiting period for smokers as required with other fit test methods. The REDON protocol uses CNP technology's superior speed and accuracy to help achieve the best respirator fit possible.

MULTIPLE DONNINGS

The OHD Quantifit, with its CNP technology, is the only system in the world that uses multiple donnings within the fit test. Multiple donnings ensure that the worker knows how to don the respirator correctly with each use.

MOST HEALTH PROTECTIVE

Peer-reviewed scientific studies have shown that the OHD Quantifit produces much more accurate, more health protective, and more believable test results than other systems. In studies where a known calibrated respirator leak was present, the OHD Quantifit measured 98% of known calibrated leak. The aerosol-based system measured only 37% of known calibrated leak¹.

EASY TO USE

The Quantifit takes the user through the test protocol step-by-step so that there is no guess-work, and very little time is needed to instruct the employee being tested. There is no instrument warm-up period to worry about, and the one-minute daily calibration ensures that the Quantifit is working within a strict tolerance. Ease of use means less mistakes, and quicker testing.

QUANTIFIT

The Industry Leader in Mask Fit Testing.

MOST RIGOROUS TEST

Using a challenge

pressure of 53.8 – 93.1 L/min, the OHD Quantifit stresses the mask as an employee would while breathing heavily under extreme physical conditions. The use of air as a standard (non-varying) gaseous challenge agent provides a more rigorous test of mask fit than an aerosol agent. If air leaks into a respirator, there is a chance that the particles, vapors, or gas contaminants also may leak in.

While aerosol-based systems can only see particles that may enter the respirator, CNP detects potential health hazards from contaminants smaller than particles.

DIRECT MEASUREMENT OF LEAK

The Quantifit directly measures facepiece leakage. The unit precisely measures leak rate (in cc/min) by determining the amount of air that leaks into the respirator during the fit test. Other test methods infer leak, while the Quantifit is the only system that directly measures the leak.

NIST CALIBRATION

The ability to calibrate the Quantifit with generally available primary calibration systems assures a higher standard of test results (NIST traceable standard).

NO CONSUMABLES

The OHD Quantifit eliminates the need for consumables in order to perform a fit test. Unlike older technologies that require probes, wicks and alcohol solutions, the Quantifit simply needs air for testing. This reduces the ongoing cost of replacing fit testing consumables and improves the user's ability to test.

TEST IN ANY ENVIRONMENT

With the patented CNP technology, OHD clients can perform fit testing in any environment. Outside, inside, dirty environments or clean environments, as long as air is present, the Quantifit can perform fit testing. Remove the concerns of lighting candles, blowing salt fog or filtration systems in a building. Choose the unrivaled technology of Quantifit to test "Anytime – Anywhere!"



DISTRIBUTE BY **SINCE 55 YEARS**
AREO-FIRE
WHERE EQUIPMENT MATCHES COURAGE

WHERE **EQUIPMENT** MATCHES **COURAGE**

5205, J.-Armand Bombardier, Longueuil, Québec J3Z 1G4, 1-800-469-1963
www.areo-fire.com

QUANTIFIT

QUANTIFIT SPECIFICATIONS

DYNAMIC RANGE

Leak Test Measurement

2-5 000 cc/min

Resolution

0,1 cc/min

Fit Factor Computation

6-53 000

PRESSURE SENSOR

PARAMETERS

Pressure Range

0-20 inches H₂O

Resolution

0,01 inches H₂O

Accuracy

± 0,25 % FS

Over-Pressure Limit

60 inch H₂O

Temperature compensation

15 °C to 30 °C (60 °F to 85 °F)

INSTRUMENT ACCURACY

Challenge Pressure

± 5 %

Leak Rate Measurement

±3% or ±3 cc/min, whichever is greater

DISPLAY

LCD Graphical 128 X 64 Pixels

USB INTERFACE

Dual Type A Ports

Supports Keyboard,
HP Inkjet printer,
or memory stick

Single Type B Port

For connection to PC

SETUP MEMORY

EEPROM, All Parameters

RTC, DATALOG MEMORY

Rechargeable Battery

DATA RETENTION

2 Years Without Power

OPERATING

RANGE

15o to 30o C (60° to 85° F)

STORAGE

RANGE

-40 °C to 60 °C (-40 °F to 140 °F)

CONSTRUCTION

Enclosure – Polyethylene Plastic Chassis –
1/8" Aluminum, Face – Lexan,
Back Printed

SIZE

5,5 x 10 x 15,5 po/139,7 x 25,4 x 393,7 mm
(HxWxD)

WEIGHT

< 7,5 lbs. (3,4 kg)

CONNECTIONS

Pressure: Quick Connect
Vent: Female Luer
Trigger Button : Phono Jack

POWER SOURCE

100 –240 VAC, 50/60 Hz

POWER SUPPLY

ADAPTER

9 VDC, 5000 mA

POWER CONSUMPTION

Less than 1000 mA

CERTIFICATIONS

UL, CE, CSA

WARRANTY

Instrument Coverage

Two-Years Parts and Labor.

Accessory Coverage

One-Year Parts and Labor.

Technical Support

No-charge phone support to original
owner of instrument.

STANDARD ACCESSORIES

- Hardcase with roller wheels, custom insert,
and retractable handle
- USB Keyboard
- Power Cord
- Trigger Button
- Triple Tube Assembly
- PC USB Cable
- FitTrack Gold Software
- Training DVD
- Operator's Manual

FITTRACK SOFTWARE

PC Requirements

Pentium 4, 2.5 GHz or better

RAM

2 MB or greater

Operating System

Windows^{MD} 7, 8, 10

Digital Interface

USB 2.0 Port

Disc Space

400 MB minimum

Printer used with software

Any Windows-compatible printer

OPTIONAL ACCESSORIES

- Fit Test Respirator Adapter
- USB Printer
- Fit Test Card Laminator
- Kit Extended Warranty
- Prepaid Service Contract

OPTIONAL RESPIRATOR

FIT TEST ADAPTERS

- 3M
- Avon Protection
- Draeger GVS
- Honeywell/Sperian
- ISI
- Interspiro
- Kemira MSA
- Miller
- Moldex North Safety
- RSI
- Scott
- Sundstrom

Call for information on additional models.

DISTRIBUTE BY

SINCE 55 YEARS

AREO-FIRE

WHERE EQUIPMENT MATCHES COURAGE



WHERE EQUIPMENT MATCHES COURAGE

5205, J.-Armand Bombardier, Longueuil, Québec J3Z 1G4, 1-800-469-1963

www.areo-fire.com