



S4000 SERIES SEPARATORMod. S43xx – ROTATING DRUM SEPARATOR



Technical Specification

Description	Rotating drum separator with rollers	
Frame	6060 anodized extruded aluminium profile 35x35mm (3 sides) and	
i raine	1 ,	
	80x30 (1 side)	
	AISI430 lateral/frontal protection, in/out ring and vertical/incline	
	adjustable infeed chute	
	3mm PC removable upper protection	
Leg	Perforated zinc plated steel legs 35x35x1000mm, vertical/incline	
	adjustment (0°÷20°)	
End leg	Metal black painted base with 2 wheels Ø 60mm and 2 legs	
Rotating drum	Ø 340mm, 15 adjustable gaps 0÷40mm, single roller gap	
_	adjustment by screw	
Rollers	20 PVC rollers Ø40x627mm	
Drive	Direct	
Asynchronous Motor	3PH 4poli (1360rpm) – 400Vac/50Hz	
Power	0,04KW	
Gear box with	i=1/15	
permanent		
lubrication		
Control Panel	Thermal protection, E-Stop	
Power Supply	400Vac / 3Ph / 50Hz (other Voltages on request)	

	Ø310 x L650	Ø310 x L950
PVC rollers	Mod. S4300	Mod. \$4310