

## S4000 SERIES SEPARATOR

Mod. S4600 – ROLLERS SEPARATOR

Mod. S4610 – ROLLERS SEPARATOR



### Technical Specification

|  |  |
|--|--|
| <b>Description</b>                         | 2 rollers separator  |
| <b>Frame</b>                               | 6060 anodized extruded aluminium profile 40x40mm<br>AISI430 lateral/frontal protection, inlet/outlet chute<br>3mm PC removable cover |
| <b>Leg</b>                                 | Perforated zinc plated steel legs 35x35x1000mm, vertical/incline adjustment (0°÷20°)<br>Mod. S4600: 2 legs<br>Mod. S4610: 4 legs     |
| <b>End leg</b>                             | Metal black painted base, 2 castors Ø60mm and 2 legs   |
| <b>Rotating rollers</b>                    | PVC, Ø140x600mm (mod. S4600), Ø140x950mm (mod. S4610)<br>adjustable gaps 0÷20mm by worm screw  |
| <b>Drive</b>                               | Direct   |
| <b>Asynchronous Motor</b>                  | 3PH 4poli (1360rpm) – 400Vac/50Hz  |
| <b>Power</b>                               | 0,04kW   |
| <b>Gear box with permanent lubrication</b> | i=1/15   |
| <b>Control Panel</b>                       | Thermal protection, E-Stop   |
| <b>Power Supply</b>                        | 230Vac / 1Ph / 50Hz (115Vac / 1Ph / 60Hz on request)   |