

STROKE — WORKING PRESSURE-

PORT SIZE ---

HOIST DETAILS

- 3600 - 2500 PSI

- 1-1/16" UNO

26 No. 0266A0528 >> © SHT of | REV

TEST PRESSURE— - 3125 PSI COMPONENTS LIST — - 0266K0528

- 0001S2040 SEAL KIT ----

PAINT ----- RED OXIDE

SWEPT VOLUME - 29 L ESTIMATED MASS - 105 KG

DO NOT SCALE IF IN DOUBT ASK

COPYRIGHT - ALL RIGHTS RESERVED

THIS DRAWING IS THE PROPERTY OF DELTA HYDRAULICS PTY LTD AND FURNISHED FOR TEMPORARY USE AND TO BE RETURNED THEREAFTER IF REQUESTED. IT IS NOT TO BE COPIED OR DISCLOSED TO OTHERS WITHOUT EXPRESS WRITTEN CONSENT.

			MATERIAL		
				DRAWN:	DELTA HYDRAULICS PTY MANUFACTURING HYDRAULIC ENGINEERS
			UNLESS OTHERWISE STATED ALL DIMENSIONS IN MILLIMETRES	D. FRANKCOMBE	ACN 009 567 186 JCLIENT
' [BREAK ALL EDGES 0.5 x 45° MIN. MACHINED SURFACE FINISH 3.2 μ m MIN. FABRICATED SURFACE FINISH 6.3 μ m MIN.	CHECKED: S. MORRIS	NEW ZEALAND HYDRAULICS
			DIMENSIONAL TOLERANCES MACHINED: 0-1000mm ±0.25	APPROVED	S2-55CC-4-3.6
			OVER 1000mm ±1 FABRICATED: 0-1000mm ±1 OVER 1000mm ±2	SALES: APPROVED	SERIES 2000 DELHOIST
	REV DESCRIPTION DATE	REVISED APF	PROVED REFERENCE AUSTRALIAN STANDARD AS1100		DATE : 17FEB16