

FOOTMOUNTS REMOVED FOR CLARITY



HOIST DETAILS
STROKE ————— 3600
WORKING PRESSURE ————— 2500 PSI
TEST PRESSURE ————— 3125 PSI
COMPONENTS LIST ————— 0266K0493
SEAL KIT ————— 0001S2706
PORT SIZE ————— 1 1/16" UNO
PAINT ————— DELTA RED

ESTIMATED DRY WEIGHT: 110 KG
CALCULATED SWEEP VOLUME: 25 L

DO NOT SCALE
IF IN DOUBT ASK

COPYRIGHT - ALL RIGHTS RESERVED
THIS DRAWING IS THE PROPERTY OF
DELTA HYDRAULICS PTY LTD AND
FURNISHED FOR TEMPORARY USE AND
TO BE RETURNED THEREAFTER IF
REQUESTED. IT IS NOT TO BE COPIED
OR DISCLOSED TO OTHERS WITHOUT
EXPRESS WRITTEN CONSENT.

REV	DESCRIPTION	DATE	REVISED	APPROVED

MATERIAL				SHT 1 of 1 REV
UNLESS OTHERWISE STATED ALL DIMENSIONS IN MILLIMETRES BREAK ALL EDGES 0.5 x 45° MIN. MACHINED SURFACE FINISH 3.2 µm MIN. FABRICATED SURFACE FINISH 6.3 µm MIN.	DRAWN: S. MORRIS	CLIENT NEW ZEALAND HYDRAULICS	TITLE S2-55TT-4-3.6 OP2, 5 & 9 SERIES 2000 DELHOIST	
DIMENSIONAL TOLERANCES MACHINED: 0-1000mm ±0.25 OVER 1000mm ±1 FABRICATED: 0-1000mm ±1 OVER 1000mm ±2	CHECKED: R. MASON	APPROVED SALES:		
REFERENCE AUSTRALIAN STANDARD AS1100	APPROVED ENG:	DATE : 27JUL15		