

SWEPT VOLUME — 92 L
 DRY MASS — 268 KG

- HOIST DETAILS
- STROKE — 7400
 - WORKING PRESSURE — 2500 psi
 - TEST PRESSURE — 3125 psi
 - COMPONENTS LIST — 0266K0536
 - SEAL KIT — 0001S2705
 - PORT SIZE — 1 5/16" UNO
 - PAINT — DELTA RED

**DO NOT SCALE
 IF IN DOUBT ASK**


COPYRIGHT — ALL RIGHTS RESERVED


THIS DRAWING IS THE PROPERTY OF DELTA HYDRAULICS PTY LTD AND FURNISHED FOR TEMPORARY USE AND TO BE RETURNED THEREAFTER IF REQUESTED. IT IS NOT TO BE COPIED OR DISCLOSED TO OTHERS WITHOUT EXPRESS WRITTEN CONSENT.

REV	DESCRIPTION	DATE	REVISED	APPROVED

MATERIAL

UNLESS OTHERWISE STATED ALL DIMENSIONS IN MILLIMETRES
 BREAK ALL EDGES 0.5 x 45° MIN.
 MACHINED SURFACE FINISH 3.2 µm MIN.
 FABRICATED SURFACE FINISH 6.3 µm MIN.
 ALL DRILL DEPTHS ARE TO POINT OF DRILL
 ALL THREAD DEPTHS ARE FULL THREAD
 DIMENSIONAL TOLERANCES
 MACHINED: 0-1000mm ±0.25
 OVER 1000mm ±1
 FABRICATED: 0-1000mm ±1
 OVER 1000mm ±2
 REFERENCE AUSTRALIAN STANDARD AS1100


 DRAWN: R. MASON
 CHECKED: J.F.W.
 APPROVED SALES:
 APPROVED ENG:


DELTA HYDRAULICS PTY LTD
 MANUFACTURING HYDRAULIC ENGINEERS
 ACN 009 567 186

CLIENT
NEW ZEALAND HYDRAULICS

TITLE
**S2-77TT-5-7.4 OP 5
 SERIES 2000 DELHOIST**

DATE : 18OCT2016 SCALE 1:2.5 A3

DRG No
0266A0536
 SHT of 1
 REV