DIMMABLE (On Head) / No Motion Sensor

DEM2202



Design By

Naoto Fukasawa

Collection =

Design







Colors & Finishes =



Features & Accessories =

• Anti-glare reflector

Specifications =

Delivered lumens

Light output ratio

Life expectancy

Control type

Input Voltage

Driver

Led type

Power consumption

CCT (Correlated Color Temperature)

CRI (Color Rendering Index)

- Fully adjustable arms and head
- Tiltable and rotatable diffuser
- Bottom of the head's body works as a heatsink for maximum heat dissipation
- Interchangeable plug options accommodate most electrical outlets for global versatility

869lm

72lm/W

10W C.O.B.*

12W

3000K

50000Hrs

120-240V


Plug-In

>90

Materials =


- Head in die-cast aluminum
- Arm in extruded aluminum
- Lower head diffuser in thermoplastic
- Internal tension springs and external tension control cables in aluminum
- Floor base in weighted steel with painted aluminum cover

Dimensions =



Light distribution

Direct



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane

Packaging =

3 Boxes

1 x 42" x 14" x 2-5/8" / 5.62 lbs - 106.5 cm x 35.5 cm x 6.5 cm / 2.55 kg

1 x 11-15/16" x 11-15/16" x 3-13/16" / 9.17 lbs - 30.1 cm x 30.1 cm x 9.5 cm / 4.16 kg

1 x 41-13/16" x 1-11/16" x 1-11/16" / 1.54 lbs - 106 cm x 4 cm x 4 cm / .7 kg

Luminaire weight =

10.36 lbs / 4.7 kg

Warranty =

