

Demetra Professional LED table with base

SPECIFICATIONS

DEM2002



Design By

Naoto Fukasawa

Collection

Design



Specifications

Delivered lumens	869lm
Light output ratio	72lm/W
Power consumption	12W
Led type	10W C.O.B.*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	DIMMABLE (On Head) / No Motion Sensor
Input Voltage	120-240V
Driver	Plug-In

Colors & Finishes

Matte Black


Materials

- Head and base in die-cast aluminum
- Arm in extruded aluminum
- Lower head diffuser in thermoplastic
- Internal tension springs and external tension control cables in aluminum
- Weighted steel base with thermoplastic matching painted finish

Features & Accessories

- Anti-glare reflector
- Fully adjustable arms and head
- Tilttable and rotatable diffuser
- Bottom of the head's body works as a heatsink for maximum heat dissipation
- Interchangeable plug options accommodate most electrical outlets for global versatility

Dimensions



Packaging

2 Boxes

1 x 42" x 14" x 2-5/8" / 5.62 lbs - 106.5 cm x 35.5 cm x 6.5 cm / 2.55 kg


1 x 11-15/16" x 11-15/16" x 3-13/16" / 9.17 lbs - 30.1 cm x 30.1 cm x 9.5 cm / 4.16 kg

Light distribution

Direct

Luminaire weight

9.26 lbs / 4.2 kg



Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane

Warranty