DIMMABLE (On Head) / No Motion Sensor

DEM1056



Design By

Naoto Fukasawa

Collection =

Design







Colors & Finishes



Specifications =

Delivered lumens

Light output ratio

Life expectancy

Control type

Input Voltage

Driver

Led type

Power consumption

CCT (Correlated Color Temperature)

CRI (Color Rendering Index)

- Features & Accessories = • Fully adjustable arms and head
- Tiltable and rotatable diffuser
- Interchangeable plug options accommodate most electrical outlets for global versatility

392lm

9W

3000K

50000Hrs

120-240V

Plug-In

>80


43.56lm/W

8.5W Array*

Materials =

- Head and arms in painted aluminum
- Lower head diffuser in thermoplastic
- Internal tension springs and external tension control cables in aluminum • Table clamp made in die-cast aluminum with matching painted finish

Dimensions =



Light distribution

Direct

Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane



1 x 42" x 14" x 2-5/8" / 5.51 lbs - 106.5 cm x 35.5 cm x 6.5 cm / 2.5 kg

1 x 5-3/16" x 4-13/16" x 3-5/8" / .44 lbs - 13 cm x 12 cm x 9 cm / .2 kg

Packaging =

5 cm table thickness min. 1/4" - max. 2 ^{1/16}" min. 0.7 cm - max. 5.2 cm clamp length min. 3 ^{11/16}" - max. 5 ^{7/16}" 2 ^{3/8}" min. 9.4 cm - max. 13.9 cm Luminaire weight

Warranty =

1.54 lbs / .7 kg

