

# Eames<sup>®</sup> Aluminum Group and Soft Pad Group Chairs

---

<b>°Description</b>	<b>EA423</b> This ottoman has a lightweight aluminum frame, 2"-thick upholstered foam cushion, and 1/2" (GD) glides for hard floors or carpet.
---------------------	---

---

<b>Construction</b>	<b>Seat</b> The nominal 2"-thick cushion shall be flexible urethane foam encapsulated in polyester fiber batting. The cushion cover shall be sewn on all 4 sides with interlocking stitches and flat seams to the continuous, nonstretch nylon suspension member.  <b>Upholstery</b> The upholstery cover shall be available in fabric and leather; see the current <i>Seating Price Book</i> for a listing. Customer's Own Material (COM) and Customer's Own Leather (COL) shall also be available; see the current <i>Seating Price Book</i> for exact yardage requirements and additional information.  The seat shall be uniform in appearance with no evidence of stitches, seams, welts, puckers, pleats, fasteners, or raw edges.  <b>Base</b> The round, tubular column shall be 14-gauge steel, 1 3/8" diameter, with enamel finish.  The 4-star base and structural members shall be die-cast aluminum with a scuff-resistant, bright polished aluminum finish.  Ottomans shall have 1/2" (GD) glides. See the "Casters and Glides" section for additional information.
---------------------	--