

m o o o i

Perch Light Branch

UMUT YAMAC



What is more poetic and elegantly captivating than a bird perched on a branch, flirting, singing and celebrating life? We all recognize this image and steal a moment from our precious time to admire this triumph of nature and beauty.

Detailing



These sunlit birds are free to swing when softly touched. They gently glow and bring along the promise of spring.

Colours


Brass and white

Perch Light Branch / Large

Dimensions

112cm | 44.1"

41cm | 16.1"



51cm | 20.1"

Product

WIDTH 112cm | 44.1"

HEIGHT 53cm | 20.9"

DEPTH 41cm | 16.1"

WEIGHT NETTO 9kg | 19.84lbs

Packaging

WIDTH 34cm | 13.4"

HEIGHT 53cm | 20.9"

CUBAGE 0.21m³ | 7.32ft³

LENGTH 115cm | 45.3"

WEIGHT 9kg | 19.84lbs

Technical CE

MATERIAL

Steel and aluminium frame with polypropylene (PP) and synthetic paper birds.

ENERGY LABEL

Energy Label B

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

5

SHAPE

Linear

INPUT VOLTAGE

180-240

FREQUENCY

50/60

MAX POWER CONSUMPTION

15W

DIMMABLE

Yes

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

CANOPY

Matching steel cylinder

COLOUR TEMPERATURE

3000 K

CRI

80

LIGHT DIRECTION

All directions

LIGHT OUTPUT

560 lm

Technical cULus

MATERIAL

Steel and aluminium frame with polypropylene (PP) and synthetic paper birds.

ENERGY LABEL

Energy Label B

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

5

SHAPE

Linear

INPUT VOLTAGE

90-305

FREQUENCY

50/60

MAX POWER CONSUMPTION

20W

DIMMABLE

Yes

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black

CABLE LENGTH

400cm | 157.5"

CANOPY

Matching steel cylinder

COLOUR TEMPERATUE

3000 K

CRI

80

LIGHT DIRECTION

All directions



LIGHT OUTPUT

560 lm

Perch Light Branch / Small

Dimensions

73cm | 28.7"



Product

WIDTH 73cm | 28.7"

HEIGHT 53cm | 20.9"

DEPTH 36cm | 14.2"

WEIGHT NETTO 7kg | 15.43lbs

Packaging

WIDTH 36cm | 14.2"

HEIGHT 41cm | 16.1"

CUBAGE 0.14m³ | 4.85ft³

LENGTH 93cm | 36.6"

WEIGHT 7kg | 15.43lbs

Technical CE

MATERIAL

Steel and aluminium frame with polypropylene (PP) and synthetic paper birds.

ENERGY LABEL

LIGHTSOURCE INCLUDED	Yes	LIGHTSOURCE TYPE	LED
SHAPE	Linear	NUMBER OF LIGHTSOURCES	3
FREQUENCY	50/60	INPUT VOLTAGE	100-240
DIMMABLE	Yes	MAX POWER CONSUMPTION	15W
LIFETIME	50000 hours	LAMPHOLDER	LED (Solid state)
CABLE LENGTH	400cm 157.5"; 1000cm 393.7"	CABLE COLOUR	Black
COLOUR TEMPERATUE	3000 K	CANOPY	Matching steel cylinder
LIGHT DIRECTION	All directions	CRI	80
		LIGHT OUTPUT	336 lm

Technical cULus

MATERIAL
Steel and aluminium frame with polypropylene (PP) and synthetic paper birds.

ENERGY LABEL		LIGHTSOURCE TYPE	LED
LIGHTSOURCE INCLUDED	Yes	NUMBER OF LIGHTSOURCES	3
SHAPE	Linear	INPUT VOLTAGE	90-264
FREQUENCY	50/60	MAX POWER CONSUMPTION	20W
DIMMABLE	Yes	LAMPHOLDER	LED (Solid state)
LIFETIME	50000 hours	CABLE COLOUR	Black
CABLE LENGTH	1000cm 393.7"; 400cm 157.5"	CANOPY	Matching steel cylinder
COLOUR TEMPERATUE	3000 K	CRI	80

LIGHT DIRECTION

All directions

LIGHT OUTPUT

336 lm

Dimmer

For fluent dimming behaviour we advise a dimmer that is compatible with the following specs.

DIMMER TYPE

1-10V

Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.
