

Technical Specifications

Sayl ® Chairs

Published February 2019

Work Chair	
Performance Information	2
Methodology and Dimension Description	3
Seating Measurements	4
Work Chair	16
Side Chair	
Performance Information	19
Methodology and Dimension Description	20
Seating Measurements	21
Side Chair	22
Stool	
Performance Information	22
Methodology and Dimension Description	23
Seating Measurements	24
Stool	28

Specifications are based on the latest information available at the time of publication. The right is reserved to make changes at any time without notice in finishes, materials, specifications, and models and to discontinue models and finishes.

For specific information about features and options available on each model, prices, and ordering information, please refer to the current Herman Miller Sayl® Chairs $Price\ Book$.

- © 2015 Herman Miller, Inc., Zeeland, Michigan
- $\ensuremath{\mathbb{R}}$ L, Herman Miller, and SAYL are among the registered trademarks of Herman Miller, Inc.

Work Chair Performance Information

Herman Miller, Inc., products are designed, developed, and tested to meet and exceed industry standards.

SAYL work chairs and stools meet or exceed all American National Standards Institute/Business and Institutional Furniture Manufacturer's Association (ANSI/BIFMA) performance requirements per ANSI X5.1- 2017 General Purpose Office Chairs, which includes the following tests:

- Back strength test (static), type I, Section 5
- Back strength test (static), types II and III, Section 6
- Base test (static), Section 7
- Drop test (dynamic), Section 8
- · Swivel test, Section 9
- · Tilt mechanism test, Section 10
- · Seating durability tests (cyclic), Section 11
- · Stability test, Section 12
- · Arm strength test (vertical), Section 13
- Arm strength test (horizontal), Section 14
- · Arm durability test (cyclic), Section 21
- Back durability test (cyclic), type I, Section 15
- Back durability test (cyclic), type II and type III, Section 16
- · Caster chair base durability test, Section 17
- · Out stop test for chairs with manually adjustable seat depth, Section 21

In addition, products have been designed and tested to Herman Miller requirements, which are derived from these ANSI minimum requirements but are much more comprehensive and generally exceeded the ANSI requirements. Herman Miller's Quality Assurance Group randomly and periodically tests standard products (seating) to ensure ongoing compliance to ANSI/BIFMA and Herman Miller corporate standards.

COMPLIANCE & CERTIFICATION

Compliancy FR

- California Technical Bulletin 117-2013 the foam and all HMI textiles used on SAYL comply with Cal TB 117-2013. Standard chairs contain no flame retardant chemicals.
- Cal TB 117-2013 is intended to determine the flame retardancy of resilient filling materials and textiles in upholstered furniture.

Ergonomics

- ANSI-HFES 100-2007 (all mandatory requirements)
- BIFMA G1-2002

Sustainability Certifications/Compliance

- level[™] 3 certified- BIFMA e3 Sustainability Standard (work & side chairs)
- Cradle-to-Cradle™ Silver certified
- GREENGUARD®GOLD Certified
- Complies with ANSI/BIFMA M7.1-2001 and ANSI/BIFMA X7.1.
- Please contact the SAYL Environmental Product Declaration for more information.

Methodology and Dimension Description

The following measurements are displayed in the subsequent measurement charts. The measurements reflect dimensional information necessary for space planning and standards/codes compliance data. The measurements relevant to standards/codes (indicated with a *) were taken with a Chair Measuring Device (CMD) in accordance with the BIFMA/CMD-1-2002 Universal Measurement Procedure for the Use of BIFMA Chair Measuring Device guideline.

Seat Height*

Distance between the floor and the compressed seat cushion where the user's thigh meets the seat.

Seat Depth*

Distance from the lumbar prominence to the front edge of the seat.

Seat Width*

Width of the chair seat within the indicated measuring zone.

Backrest Height*

Distance from the seat cushion at centerline to the highest point of the chair back.

Backrest Width*

Width of the backrest at the narrowest point of the lumbar support zone.

Lumbar Support

Height of the lumbar support region as measured from the base of the chair back to the top and bottom of the lumbar support areas.

Overall Height (Maximum)

Distance from the floor to the highest point of a chair back (unloaded), with seat height at highest position.

Overall Depth

The distance from the forward caster position/extended seat to the back. Center measured with the chair at an upright position.

Product Weight

Does not include packaging

Back Tilt Range*

Angle of the back from upright to fully reclined positions in relation to the floor.

Seat Pan Angle* Seat angle in

relation to the floor.

Backrest-to-Seat Angle Range*

Angle between the backrest and the seat from upright to fully reclined positions.

Armrest Height*

Distance from the compressed seat cushion to the top of an armrest.

Armrests, Inside Measurement Width

between the armrests.

Armrests, Outside Measurement

Overall distance from the outer edge of one armrest to the outer edge of the other armrest.

Base Diameter, Outside

Overall diameter of the base.

Seating Measurements - Work Chairs (Suspension & Mid-back Upholstered)

Work Chairs: Low-Height Range, Tilt Limiter & Seat Angle, Fixed & Adjustable Seat												
Chair Description Fully Adjustable Arms		Overall Height	Overall Width	Overall Depth	Weight (pounds)	Seat Height	Seat Depth	Seat Width	Backrest Height	Backrest Width		
	AS2VA13AF AS2SA13AF	37 ¾"	26.75"	26"	Polymer:	15″-19″	Fixed 16"	18.25"	20.9"	16.9"		
Suspension	AS2VA13AA AS2SA13AA						Polished: 40		Adjust 16-18"			
Mid-back	AS2VC13AF AS2SC13AF				Polymer: 39		Fixed 16"			17.1"		

Upholstered	AS2VC13AA AS2SC13AA				Polished: 42		Adjust 16-18"						
Height Adj	ustable Arms												
	AS2VA13HF AS2SA13HF	37 ¾"	24.75″	26"	Polymer: 36	15"-19"	Fixed 16"	18.25"	20.9"	16.9"			
Suspension	AS2VA13HA AS2SA13HA				Polished: 39		Adjust 16-18"						
Mid-back	AS2VC13HF AS2SC13HF				Polymer: 38		Fixed 16"			17.1"			
Upholstered	AS2VC13HA AS2SC13HA				Polished: 41					Adjust 16-18"			
Fixed Arms	3												
Suspension	AS2VA13PF AS2SA13PF	37 ¾"	24.75″	26"	Polymer: 36	15″-19″	Fixed 16"	18.25"	20.9"	16.9"			
	AS2VA13PA AS2SA13PA				Polished: 39		Adjust 16-18"	-					
Mid-back	AS2VC13PF AS2SC13PF			Polymer: 38		Fixed 16"			17.1"				
Upholstered	AS2VC13PA AS2SC13PA			Polished: 41		Adjust 16-18"							
No Arms													
	AS2VA13NF AS2SA13NF	37 ¾"	23.5"	26"	Polymer:	15"-19"	Fixed 16"	18.25"	20.9"	16.9"			
Suspension	AS2VA13NA AS2SA13NA				Polished: 37		Adjust 16-18"	-					
Mid-back	AS2VC13NF AS2SC13NF			Polymer: 36 Polished: 39	36		Fixed 16"			17.1"			
Upholstered	AS2VC13NA AS2SC13NA					Adjust 16-18"							
			·			•	•						
Seat Pan – Seat Pan		Tilt Range		Lumbar	Armres	t l	Base	Armres	st	Armrest Lengt			

Seat Pan – Backrest Angle	Seat Pan Angle	Tilt Range	Lumbar Support	Armrest Clearance /Inside Distance	Base Diameter Outside	Armrest Height	Armrest Length
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	16.5-19.7"	26.0"	6.7"-10.8"	6.4"-7.7"
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	19.3"	26.0"	6.7"-10.8"	6.9″-7.5″
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	19.1"	26.0"	9.4"	7.8"
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	N/A	26.0"	N/A	N/A

Weight

(pounds)

Seat

Height

Seat

Depth

Seat

Width

Backrest

Height

Chair Description

Work Chairs: Low-Height Range, Tilt Limiter, Fixed & Adjustable Seat

Overall

Width

Overall

Depth

Overall

Height

Backrest Width

Fully Adjus	table Arms												
	AS2VA12AF AS2SA12AF	37 ¾"	26.75"	26"	Polymer:	15″-19″	Fixed 16"	18.25"	20.9"	16.9"			
Suspension	AS2VA12AA AS2SA12AA				Polished: 40		Adjust 16-18"						
Mid-back	AS2VC12AF AS2SC12AF				Polymer: 39	-	Fixed 16"			17.1"			
Upholstered	AS2VC12AA AS2SC12AA				Polished: 42		Adjust 16-18"						
Height Adj	ustable Arms												
	AS2VA12HF AS2SA12HF	37 ¾"	24.75"	26"	Polymer: 36	15″-19″	Fixed 16"	18.25"	20.9"	16.9"			
Suspension	AS2VA12HA AS2SA12HA				Polished: 39		Adjust 16-18"						
Mid-back	AS2VC12HF AS2SC12HF				Polymer: 38		Fixed 16"			17.1"			
Upholstered	AS2VC12HA AS2SC12HA			Polished 41	Polished: 41		Adjust 16-18"						
Fixed Arms	; ;												
	AS2VA12PF AS2SA12PF	37 ¾"	37 ¾" 24.7	24.75"	26"	Polymer:	15″-19″	Fixed 16"	18.25"	20.9"	16.9″		
Suspension	AS2VA12PA AS2SA12PA				Polished: 39		Adjust 16-18"						
Mid-back	AS2VC12PF AS2SC12PF				Polymer: 38		Fixed 16"			17.1"			
Upholstered	AS2VC12PA AS2SC12PA				Polished: 41		Adjust 16-18"						
No Arms	ı												
	AS2VA12NF AS2SA12NF	37 ¾"	23.5"	26"	34 Polished: 37 Polymer: 36				15″-19″	Fixed 16"	18.25"	20.9"	16.9"
Suspension	AS2VA12NA AS2SA12NA						Adjust 16-18"						
Mid-back	AS2VC12NF AS2SC12NF						Fixed 16"			17.1"			
Upholstered	AS2VC12NA AS2SC12NA		Polished 39	Polished: 39		Adjust 16-18"	-						

Seat Pan – Backrest Angle	Seat Pan Angle	Tilt Range	Lumbar Support	Armrest Clearance /Inside Distance	Base Diameter Outside	Armrest Height	Armrest Length
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	16.5-19.7"	26.0"	6.7″-10.8″	6.4"-7.7"
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	19.3″	26.0"	6.7″-10.8″	6.9″-7.5″
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	19.1″	26.0"	9.4"	7.8"

96/111°	3/13°	101°/124		Fixed: 9.0" Adj: 4" rang	e N/A		26.0″	N/A		N/A	
Work Chai	rs: Standard	Height Ra	nge, Til	t Limiter & S	Seat Angle	, Fixed &	Adjustable	e Seat			
Chair Descri	ption	Overall Height	Overal Width	II Overall Depth	Weight (pounds)	Seat Height	Seat Depth	Seat Width	Backr Heigh		Backrest Width
Fully Adjus	stable Arms										
	AS2VA23AF AS2SA23AF	39 ¼"	26.75″	26"	Polymer: 37	16"- 20.5"	Fixed 16"	18.25"	20.9"		16.9"
Suspension	AS2VA23AA AS2SA23AA				Polished: 40		Adjust 16-18"				
Mid-back	AS2VC23AF AS2SC23AF				Polymer: 39		Fixed 16"				17.1"
Upholstered	AS2VC23AA AS2SC23AA				Polished: 42		Adjust 16-18"				
Height Adj	ustable Arms	5									
	AS2VA23HF AS2SA23HF	39 ¼"	24.75″	26"	Polymer: 36	16"- 20.5"	Fixed 16"	18.25"	20.9″		16.9"
Suspension	AS2VA23HA AS2SA23HA				Polished: 39		Adjust 16-18"				
Mid-back	AS2VC23HF AS2SC23HF				Polymer: 38		Fixed 16"				17.1"
Upholstered	AS2VC23HA AS2SC23HA				Polished: 41		Adjust 16-18"				
Fixed Arms	5										
	AS2VA23PF AS2SA23PF	39 ¼"	24.75	3	Polymer: 36	16"- 20.5"	Fixed 16"	18.25"	20.9"		16.9"
Suspension	AS2VA23PA AS2SA23PA				Polished: 39 Polymer: 38		Adjust 16-18"				
Mid-back	AS2VC23PF AS2SC23PF					38		Fixed 16"			
Upholstered	AS2VC23PA AS2SC23PA				Polished: 41		Adjust 16-18″				
No Arms											
	AS2VA23NF AS2SA23NF	39 ¼"	23.5"	26"	Polymer: 34	16"- 20.5"	Fixed 16"	18.25"	20.9"		16.9″
Suspension	AS2VA23NA AS2SA23NA				Polished: 37		Adjust 16-18"				
Mid-back	AS2VC23NF AS2SC23NF				Polymer: 36		Fixed 16"				17.1″
Upholstered	AS2VC23NA AS2SC23NA				Polished: 39		Adjust 16-18"				
Seat Pan – Backrest Angle	Seat Pan Angle	Tilt Range		Lumbar Support	Armres Clearan /Inside		Base Diameter Outside	Armres Height		Armr	est Length
					,						
94/96/111°	-3/3/13°	91°/ 101°/		Fixed: 9.0" Adj: 4" range	16.5-19	9.7"	26.0"	6.7″-1	0.8"	6.4″-	7.7″

94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	19.3″	26.0"	6.7"-10.8"	6.9″-7.5″
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	19.1"	26.0"	9.4"	7.8"
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	N/A	26.0"	N/A	N/A

Chair Descri	ption	Overall Height	Overall Width	Overall Depth	Weight (pounds)	Seat Height	Seat Depth	Seat Width	Backrest Height	Backrest Width
Fully Adjus	table Arms	-								
	AS2VA22AF AS2SA22AF	39 ¼"	26.75"	26"	Polymer:	16″- 20.5″	Fixed 16"	18.25"	20.9"	16.9"
Suspension	AS2VA22AA AS2SA22AA				Polished: 40		Adjust 16-18"			
Mid-back	AS2VC22AF AS2SC22AF				Polymer:		Fixed 16"			17.1"
Upholstered	AS2VC22AA AS2SC22AA				Polished: 42		Adjust 16-18"			
Height Adj	ustable Arms									
	AS2VA22HF AS2SA22HF	39 ¼"	24.75"	26"	Polymer: 36	16"- 20.5"	Fixed 16"	18.25"	20.9"	16.9"
Suspension	AS2VA22HA AS2SA22HA				Polished: 39		Adjust 16-18"	_		
Mid-back	AS2VC22HF AS2SC22HF				Polymer: 38		Fixed 16"			17.1"
Upholstered	AS2VC22HA AS2SC22HA		Polished: 41			Adjust 16-18"				
Fixed Arms	•									
	AS2VA22PF AS2SA22PF	39 ¼"	24.75"	26"	Polymer: 36	16"- 20.5"	Fixed 16"	18.25"	20.9"	16.9"
Suspension	AS2VA22PA AS2SA22PA				Polished: 39		Adjust 16-18"			
Mid-back	AS2VC22PF AS2SC22PF				Polymer: 38		Fixed 16"			17.1"
Upholstered	AS2VC22PA AS2SC22PA				Polished: 41		Adjust 16-18"			
No Arms										
	AS2VA22NF AS2SA22NF	39 ¼"	23.5"	26"	Polymer: 34	16"- 20.5"	Fixed 16"	18.25"	20.9"	16.9"
Suspension	AS2VA22NA AS2SA22NA				Polished: 37		Adjust 16-18"			
Mid-back	AS2VC22NF AS2SC22NF				Polymer: 36		Fixed 16"			17.1"
Upholstered	AS2VC22NA AS2SC22NA				Polished: 39		Adjust 16-18"			

Seat Pan – Backrest Angle	Seat Pan Angle	Tilt Range	Lumbar Support	Armrest Clearance /Inside Distance	Base Diameter Outside	Armrest Height	Armrest Length
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	16.5-19.7"	26.0"	6.7″-10.8″	6.4"-7.7"
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	19.3"	26.0"	6.7″-10.8″	6.9″-7.5″
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	19.1"	26.0"	9.4"	7.8"
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	N/A	26.0"	N/A	N/A

Chair Descri	iption	Overall Height	Overall Width	Overall Depth	Weight (pounds)	Seat Height	Seat Depth	Seat Width	Backrest Height	Backrest Width
Fully Adjus	stable Arms									
Suspension	AS2VA33AF AS2SA33AF AS2VA33AA	40 ¾"	26.75"	26"	Polymer: 37 Polished:	16.522"	Fixed 16" Adjust	18.25"	20.9″	16.9"
	AS2SA33AA				40		16-18"			
Mid-back	AS2VC33AF AS2SC33AF				Polymer: 39		Fixed 16"			17.1"
Upholstered	AS2VC33AA AS2SC33AA				Polished: 42		Adjust 16-18"			
Height Adj	ustable Arms									
	AS2VA33HF AS2SA33HF	40 ¾"	24.75″	26"	36 22" Polished:		Fixed 16"	18.25"	20.9"	16.9"
Suspension	AS2VA33HA AS2SA33HA				Polished:		Adjust 16-18"			
Mid-back	AS2VC33HF AS2SC33HF				Polymer: 38 Polished:		Fixed 16"	_		17.1"
Upholstered	AS2VC33HA AS2SC33HA				41		Adjust 16-18"			
Fixed Arms	5									
	AS2VA33PF AS2SA33PF	40 ¾"	24.75″	26"	Polymer: 36 Polished:	16.522"	Fixed 16"	18.25"	20.9"	16.9"
Suspension	AS2VA33PA AS2SA33PA				39		Adjust 16-18"			
Mid-back	AS2VC33PF AS2SC33PF				Polymer: 38 Polished: 41		Fixed 16"			17.1"
Upholstered	AS2VC33PA AS2SC33PA						Adjust 16-18"			
No Arms										
	AS2VA33NF AS2SA33NF	40 ¾"	23.5″	26"	Polymer: 34	16.5- 22"	Fixed 16"	18.25"	20.9"	16.9"

	Suspension	AS2VA33NA AS2SA33NA			Polished: 37	Adjust 16-18"			
	Mid-back Upholstered	AS2VC33NF AS2SC33NF			Polymer: 36	Fixed 16"		17.1"	
		AS2VC33NA AS2SC33NA		Polished: 39	Adjust 16-18"				

Seat Pan – Backrest Angle	Seat Pan Angle	Tilt Range	Lumbar Support	Armrest Clearance /Inside Distance	Base Diameter Outside	Armrest Height	Armrest Length
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	16.5-19.7"	26.0"	6.7″-10.8″	6.4"-7.7"
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	19.3"	26.0"	6.7″-10.8″	6.9″-7.5″
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	19.1"	26.0"	9.4"	7.8"
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	N/A	26.0"	N/A	N/A

Chair Descri	iption	Overall Height	Overall Width	Overall Depth	Weight (pounds)	Seat Height	Seat Depth	Seat Width	Backrest Height	Backrest Width
Fully Adjus	stable Arms									
	AS2VA32AF AS2SA32AF	40 ¾"	26.75"	26"	Polymer: 37	16.522"	Fixed 16"	18.25"	20.9"	16.9"
Suspension	AS2VA32AA AS2SA32AA				Polished: 40		Adjust 16-18"			17.1"
Mid-back	AS2VC32AF AS2SC32AF				Polymer: 39		Fixed 16"			
Upholstered	AS2VC32AA AS2SC32AA				Polished: 42		Adjust 16-18"			
Height Adj	ustable Arms									
	AS2VA32HF AS2SA32HF	40 ¾"	24.75"	26"	Polymer: 36	16.5- 22"	Fixed 16"	18.25"	20.9"	16.9"
Suspension	AS2VA32HA AS2SA32HA				Polished: 39		Adjust 16-18"			
Mid-back	AS2VC32HF AS2SC32HF				Polymer: 38		Fixed 16"			17.1"
Upholstered	AS2VC32HA AS2SC32HA				Polished: 41		Adjust 16-18"			
Fixed Arms	5									
	AS2VA32PF AS2SA32PF	40 ¾"	24.75″	26"	Polymer: 36	16.522"	Fixed 16"	18.25"	20.9"	16.9"
Suspension	AS2VA32PA AS2SA32PA			Adjust 16-18"						

Mid-back	VC3//C33DV				Polymer: 38		Fixed 16"			17.1"
Upholstered	AS2VC32PA AS2SC32PA				Polished: 41		Adjust 16-18"			
No Arms										
	AS2VA32NF AS2SA32NF	40 ¾"	23.5"	26"	Polymer:	16.5- 22"	Fixed 16"	18.25"	20.9"	16.9"
Suspension	AS2VA32NA AS2SA32NA				Polished: 37		Adjust 16-18"			
Mid-back	AS2VC32NF AS2SC32NF				Polymer: 36		Fixed 16"			17.1"
Upholstered A	AS2VC32NA AS2SC32NA				Polished: 39		Adjust 16-18"			

Seat Pan – Backrest Angle	Seat Pan Angle	Tilt Range	Lumbar Support	Armrest Clearance /Inside Distance	Base Diameter Outside	Armrest Height	Armrest Length
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	16.5-19.7"	26.0"	6.7″-10.8″	6.4"-7.7"
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	19.3"	26.0"	6.7″-10.8″	6.9″-7.5″
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	19.1"	26.0"	9.4"	7.8"
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	N/A	26.0"	N/A	N/A

Seating Measurements - Work Chairs (High-back Upholstered)

Chair Descri	ption	Overall Height	Overall Width	Overall Depth	Weight (pounds)	Seat Height	Seat Depth	Seat Width	Backrest Height	Backrest Width
Fully Adjus	table Arms									
High-back	AS2VD13AF AS2SD13AF	40 ¼" 26.75"		26"	Polymer: 39.5	15″-19″	Fixed 16"	18.25"	23.8"	17.1"
Upholstered	AS2VD13AA AS2SD13AA				Polished: 42.5		Adjust 16-18"			
Height Adj	ustable Arms									
High-back	AS2VD13HF AS2SD13HF	40 1/4"	24.75"	26"	Polymer: 38.5	15″-19″	Fixed 16"	18.25"	23.8"	17.1"
Upholstered	AS2VD13HA AS2SD13HA				Polished: 41.5		Adjust 16-18"			
Fixed Arms	5									
High-back	AS2VD13PF AS2SD13PF	40 ¼"	24.75"	26"	Polymer: 38.5	15″-19″	Fixed 16"	18.25"	23.8"	17.1"
Upholstered	AS2VD13PA AS2SD13PA				Polished: 41.5		Adjust 16-18"			
No Arms										
High-back	AS2VD13NF AS2SD13NF	40 1/4"	23.5"	26"	Polymer: 36.5	15″-19″	Fixed 16"	18.25"	23.8"	17.1"
Upholstered A	AS2VD13NA AS2SD13NA	NA		Polished: 39.5	d:	Adjust 16-18"				

Seat Pan – Backrest Angle	Seat Pan Angle	Tilt Range	Lumbar Support	Armrest Clearance /Inside Distance	Base Diameter Outside	Armrest Height	Armrest Length
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	16.5-19.7"	26.0"	6.7″-10.8″	6.4"-7.7"
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	19.3″	26.0"	6.7″-10.8″	6.9″-7.5″
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	19.1"	26.0"	9.4"	7.8"
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	N/A	26.0"	N/A	N/A

Work Chairs: Low-Height Range, Tilt Limiter, Fixed & Adjustable Seat												
Chair Descri										Backrest Width		
Fully Adjus	Fully Adjustable Arms											
	AS2VD12AF AS2SD12AF	40 ¼"	26.75"	26"		15″-19″	Fixed 16"	18.25"	23.8″	17.1"		

High-back Upholstered	AS2VD12AA AS2SD12AA				Polymer: 39.5 Polished: 42.5		Adjust 16-18"			
Height Adj	ustable Arms									
High-back	AS2VD12HF AS2SD12HF	40 1/4"	24.75"	26"	Polymer: 38.5	15″-19″	Fixed 16"	18.25"	23.8"	17.1"
Upholstered	AS2VD12HA AS2SD12HA				Polished: 41.5		Adjust 16-18"			
Fixed Arms	S									
High-back	AS2VD12PF AS2SD12PF	40 1/4"	24.75″	26"	Polymer: 38.5	15″-19″	Fixed 16"	18.25"	23.8″	17.1"
Upholstered	AS2VD12PA AS2SD12PA				Polished: 41.5		Adjust 16-18"			
No Arms										
High-back	AS2VD12NF AS2SD12NF	40 1/4"	23.5"	26"	Polymer: 36.5	15″-19″	Fixed 16"	18.25"	23.8"	17.1"
Upholstered	AS2VD12NA AS2SD12NA				Polished: 39.5		Adjust 16-18"			

Seat Pan – Backrest Angle	Seat Pan Angle	Tilt Range	Lumbar Support	Armrest Clearance /Inside Distance	Base Diameter Outside	Armrest Height	Armrest Length
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	16.5-19.7"	26.0"	6.7"-10.8"	6.4"-7.7"
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	19.3″	26.0"	6.7"-10.8"	6.9″-7.5″
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	19.1"	26.0"	9.4"	7.8"
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	N/A	26.0"	N/A	N/A

Work Chai	rs: Standard-I	Height Ra	nge, Tilt I	Limiter &	Seat Angle	, Fixed &	Adjustabl	e Seat		
Chair Descr	iption	Overall Height	Overall Width	Overall Depth	Weight (pounds)	Seat Height	Seat Depth	Seat Width	Backrest Height	Backrest Width
Fully Adjus	stable Arms									
High-back	AS2VD23AF AS2SD23AF	41 ¾"	26.75"	26"	Polymer: 39.5	16"- Fixed 20.5" Fixed		18.25"	23.8"	17.1"
Upholstered AS2VD23AA AS2SD23AA					Polished: 42.5		Adjust 16-18"			
Height Adj	ustable Arms									
High-back	AS2VD23HF AS2SD23HF	41 ¾"	24.75"	26"	Polymer: 38.5	16"- 20.5"	Fixed 16"	18.25"	23.8"	17.1"
Upholstered	AS2VD23HA AS2SD23HA				Polished: 41.5		Adjust 16-18"			
Fixed Arms										
	AS2VD23PF AS2SD23PF	41 ¾"	24.75"	26"		16"- 20.5"	Fixed 16"	18.25"	23.8"	17.1"

High-back Upholstered	AS2VD23PA AS2SD23PA				Polymer: 38.5 Polished: 41.5		Adjust 16-18"			
No Arms										
High-back	AS2VD23NF AS2SD23NF	41 ¾"	23.5″	26"	Polymer: 36.5	16"- 20.5"	Fixed 16"	18.25"	23.8"	17.1"
Upholstered	AS2VD23NA AS2SD23NA				Polished: 39.5		Adjust 16-18"			

Seat Pan – Backrest Angle	Seat Pan Angle	Tilt Range	Lumbar Support	Armrest Clearance /Inside Distance	Base Diameter Outside	Armrest Height	Armrest Length
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	16.5-19.7"	26.0"	6.7″-10.8″	6.4"-7.7"
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	19.3″	26.0"	6.7″-10.8″	6.9″-7.5″
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	19.1"	26.0"	9.4"	7.8"
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	N/A	26.0"	N/A	N/A

Cl : D :		0 "	0 "	0 "	147 1 1 1	<u> </u>		~ .	n	ь .							
Chair Descri	ption	Overall	Overall	Overall	Weight	Seat	Seat	Seat	Backrest	Backres							
		Height	Width	Depth	(pounds)	Height	Depth	Width	Height	Width							
Fully Adjus	table Arms																
	AS2VD22AF	41 ¾"	26.75"	26"	Polymer:	16"-	Fixed	18.25"	23.8"	17.1"							
High-back	AS2SD22AF				39.5	20.5"	16"										
Upholstered	AS2VD22AA				Polished:		Adjust	-									
	AS2SD22AA				42.5		16-18"										
Height Adj	ustable Arms																
	AS2VD22HF	41 ¾"	24.75"	26"	Polymer:	16"-	Fixed	18.25"	23.8"	17.1"							
High-back	AS2SD22HF				38.5 Polished:	20.5"	16"										
Upholstered	AS2VD22HA						Adjust	-									
	AS2SD22HA				41.5		16-18"										
Fixed Arms																	
	AS2VD22PF	41 ¾"	24.75"	26"	Polymer:	16″-	Fixed	18.25"	23.8"	17.1"							
High-back	AS2SD22PF				38.5	20.5"	16"										
Upholstered	7132352211				Polished:		Adjust										
					41.5		16-18"										
AS2VD22PA	AS2SD22PA																
No Arms																	
	AS2VD22NF	41 ¾"	23.5"	26"	Polymer:	16″-	Fixed	18.25"	23.8"	17.1"							
High-back	AS2SD22NF				36.5	, ,		,	,	,			20.5"	16"			
Upholstered	AS2VD22NA	VD22NA Polished:		Adjust	-												
ophoistered	AS2SD22NA				39.5	39.5		16-18"									

Seat Pan – Backrest Angle	Seat Pan Angle	Tilt Range	Lumbar Support	Armrest Clearance /Inside Distance	Base Diameter Outside	Armrest Height	Armrest Length

96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	16.5-19.7"	26.0"	6.7″-10.8″	6.4"-7.7"
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	19.3″	26.0"	6.7″-10.8″	6.9″-7.5″
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	19.1"	26.0"	9.4"	7.8"
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	N/A	26.0"	N/A	N/A

Work Chair	rs: Extended-I	leight Ra	nge, Tilt	Limiter &	Seat Angle	, Fixed &	Adjustab	le Seat								
Chair Descri	ption	Overall Height	Overall Width	Overall Depth	Weight (pounds)	Seat Height	Seat Depth	Seat Width	Backrest Height	Backrest Width						
Fully Adjus	stable Arms															
High-back	AS2VD33AF AS2SD33AF	43 ¼"	26.75"	26"	Polymer: 39.5	16"-22"	Fixed 16"	18.25"	23.8"	17.1"						
Upholstered	AS2VD33AA AS2SD33AA				Polished: 42.5	ea:	Adjust 16-18"									
Height Adj	ustable Arms															
High-back	AS2VD33HF	43 ¼"	24.75"	26"	Polymer: 38.5	16"-22"	Fixed 16"	18.25"	23.8"	17.1"						
riigii back					Polished: 41.5		Adjust 16-18"	-								
	AS2SD33HF															
Upholstere	d AS2VD33HA AS2SD33HA															
Fixed Arms	5															
High-back	AS2VD33PF AS2SD33PF	43 1/4"	24.75"	26"	Polymer: 38.5	16"-22"	Fixed 16"	18.25"	23.8"	17.1"						
Upholstered	AS2VD33PA AS2SD33PA				Polished: 41.5		Adjust 16-18"	_								
No Arms																
High-back	AS2VD33NF AS2SD33NF	43 ¼″	23.5"	26"	Polymer: 36.5	16"-22"	Fixed 16"	18.25"	23.8″	17.1"						
Upholstered	AS2VD33NA AS2SD33NA				Polished: 39.5								Adjust 16-18"			

Seat Pan – Backrest Angle	Seat Pan Angle	Tilt Range	Lumbar Support	Armrest Clearance /Inside Distance	Base Diameter Outside	Armrest Height	Armrest Length
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	16.5-19.7"	26.0"	6.7″-10.8″	6.4"-7.7"
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	19.3″	26.0"	6.7″-10.8″	6.9″-7.5″
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	19.1"	26.0"	9.4"	7.8"
94/96/111°	-3/3/13°	91°/ 101°/124°	Fixed: 9.0" Adj: 4" range	N/A	26.0"	N/A	N/A

Chair Descri	ption	Overall Height	Overall Width	Overall Depth	Weight (pounds)	Seat Height	Seat Depth	Seat Width	Backrest Height	Backrest Width
Fully Adius	stable Arms	rieigiit	Wideii	Берит	(pourius)	Tieigiic	Берит	Width	Tieigiic	Width
High-back	AS2VD32AF AS2SD32AF	39.5 1		Fixed 16"			17.1"			
Upholstered	AS2VD32AA AS2SD32AA				Polished: 42.5		Adjust 16-18"			
Height Adj	ustable Arms									
High-back	AS2VD32HF AS2SD32HF	43 1/4"	24.75"	26"	Polymer: 38.5	16"-22"	Fixed 16"	18.25"	23.8"	17.1"
Upholstered	AS2VD32HA AS2SD32HA				Polished: 41.5		Adjust 16-18"			
Fixed Arms	•									
High-back	AS2VD32PF AS2SD32PF	43 ¼"	24.75″	26"	Polymer: 38.5	16"-22"	Fixed 16"	18.25"	23.8"	17.1"
Upholstered	AS2VD32PA AS2SD32PA				Polished: 41.5		Adjust 16-18"			
No Arms										
High-back	AS2VD32NF AS2SD32NF	43 ¼"	23.5″	26"	Polymer: 36.5	16"-22"	Fixed 16"	18.25"	23.8"	17.1"
Upholstered	AS2VD32NA AS2SD32NA	20.5		Adjust 16-18"						

Seat Pan – Backrest Angle	Seat Pan Angle	Tilt Range	Lumbar Support	Armrest Clearance /Inside Distance	Base Diameter Outside	Armrest Height	Armrest Length
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	16.5-19.7"	26.0"	6.7″-10.8″	6.4"-7.7"
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	19.3″	26.0"	6.7″-10.8″	6.9″-7.5″
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	19.1"	26.0"	9.4"	7.8"
96/111°	3/13°	101°/124°	Fixed: 9.0" Adj: 4" range	N/A	26.0"	N/A	N/A

Work Chair

DESCRIPTION

This chair has a frameless 3D Intelligent™ Suspension back that allows freedom of movement, while providing targeted back support and moving heat away from the body. The suspension is supported by a Y Tower™ and anchored at the bottom by the ArcSpan™. The chair has an upholstered seat with foam padding and passive Posturefit® back support. The Harmonic™ tilt provides continuous balance and lets the body recline naturally, pivoting at the ankles, knees, and hips. The chair has a 5-star base and 3 heightadjustment options. The chair is all black, including the Y-Tower, arms, arm pads, tilt cover, base, and black Crossover upholstery. Shipped knocked down and is ready to assemble with no tools required.

Tilt options include a tilt limiter and tilt limiter with seat angle. The tilt limiter allows the user to set the tilt range to limit the amount of recline. The tilt limiter with seat angle allows the user to set the tilt range and select a 5° forward seat angle.

Seat options include a fixed 16"seat depth, or an adjustable seat depth that allows the user to adjust the depth from 16" to 18".

Back-support options include a standard option with no additional support, and an adjustable lumbar support option. The standard option has passive Posturefit back support molded directly into the strands of the suspension material, providing targeted support at the base of the back, below the beltline, that helps achieve healthier posture and improved lower back comfort. The adjustable lumbar support option adds a user-adjustable lumbar that adjusts 4" in height.

Arm choices include a no arm option; a fixed, non-adjustable option; a height adjustable option that allows the arms to move 4" vertically; and a fully adjustable option that allows the arms to move 4" vertically, 1 3/8" horizontally, 2" front-to-back, with arm pads that pivot 11° inward and 11° outward.

CONSTRUCTION

Seat

The contoured seat shall be constructed of molded polypropylene insert with molded polyurethane foam. The foam shall have a nominal $\frac{1}{2}$ '- 1 $\frac{1}{2}$ " thickness and have waterfall edges. Fabric is applied non-bonded. When chairs are refurbished, the complete seat assembly can be replaced.

Back

Suspension

The suspension back shall be constructed of thermoplastic urethane (TPU), stretched and fastened onto a structural frame (ArcSpan) on the bottom and fastened at the top by a Y-Tower made of an injection-molded glass-filled nylon.

Upholstered

The upholstered back shall have a polypropylene insert with urethane foam ($\frac{1}{2}$ '- 1'' thick) with a stapled textile cover.

Lumbar Pad (optional)

Suspension Back Models

The suspension back lumbar pad is constructed of unfilled nylon. It attaches to and slides up and down on an acetal lumbar bow. This bow is attached to the suspension back by two translucent polycarbonate clips.

Upholstered Models

The lumbar adjustment shall be a polypropylene pad supported by a polypropylene insert and a glass-filled nylon lever.

See "Adjustments" for lumbar-support adjustments.

Arms (Optional)

Chairs shall be available with no arms, fixed arms, height-adjustable arms, and fully adjustable arms.

Each arm shall have an arm support stem of glass-filled nylon with self-skinning polyurethane arm pads. Fixed and height adjustable arm pads shall be 8 6/8" by 2 3/4". Fully adjustable arm pads shall be 9 1/2" by 3 3/4"

Arms are detachable without tools; they are field-replaceable.

Tilt

The tilt mechanism shall be 2 fiberglass leaf springs, a lead-screw-driven tension adjustment, and a stamped steel housing. The tilt mechanism shall be in a 4-piece, snap-together polypropylene cover.

The tilt tension adjustment control shall be a glass-filled polypropylene knob located to the side. The tilt tension adjustment shall have 18 full revolution turns.

A tilt limiter adjustment, constructed of an injection-molded glass-reinforced nylon tilt limiter lever shall come standard and extend from the side of the tilt. On chairs with an optional seat-angle adjustment, an injection-molded glass-reinforced lever shall extend out on the left side.

Base

The 5-star base shall be glass-filled nylon with a textured finish. An optional die-cast aluminum base shall be available for a polished aluminum finish. The chair shall swivel 360°.

The chair base shall house a unitized pneumatic cylinder seat height adjustment mechanism contained in 2 steel tubes. The inner tube shall slide and rotate in a bushing within an outer tube. The outer tube shall be coated black.

The seat height activator shall protrude from the back of the tilt tension knob. The activator shall be glassfilled polypropylene.

Pneumatic cylinders shall be available to support three seat height ranges. Pneumatic cylinders can be interchanged or replaced on site. See "Adjustments" for seat height ranges.

Casters

Chairs shall be furnished with interchangeable casters. The chair shall be available with 2 ½" diameter casters. Casters for use on carpet only shall have a steel stem and black nylon wheels and yoke. Casters for use on hard floors or carpet shall have a steel stem, black nylon wheels and yoke, and soft polyurethane tread. See the "casters and Glides" section for more information.

ADJUSTMENTS

Seat Height

The seat height shall be adjusted by raising the seat-height lever, which is mounted to the right side of the seat. Raising the lever shall increase the seat height when the chair is unoccupied, and lower the seat height when the seat is occupied.

The approximate seat height range (with CMD) shall be 16" to 20.5" for standard-height-range pneumatic chairs, 15" to 19" for low-height chairs and 16.5-22" for the extended-height chairs.

Tilt

The tilt mechanism shall be a HarmonicTM tilt. The tilt tension shall be adjusted by turning the tilt tension knob, which is located on the right side of the seat.

Back Recline

Chairs with a standard tilt and tilt limiter shall have a nominal 25° of body-weight controlled recline (from horizontal). Chairs with a tilt limiter shall allow users to limit the amount of back recline in 3 incremental adjustments. Chairs with a tilt limiter and seat angle adjustment shall have a back recline range and a tilt limiter that allows users to limit the amount of back recline in 3 incremental positions. (4 positions with forward tilt)

Seat Angle

Chairs with a tilt limiter and seat angle adjustment shall let the user select a $+3^{\circ}$ horizontal or -3° forward seat angle (6° from neutral angle).

Adjustable Arms (Optional)

The adjustable arms shall feature a height, width, pivot and fore/aft adjustment. They shall have a height range adjustment of 4". The arms width adjustment range shall be approximately 1 3/8"(each arm). The arm caps will pivot 11° in and 11° out. The arm caps will move front-to-back by 2".

Height Adjustable Arms (Optional)

The height adjustable arms shall have a height range adjustment of 4".

Lumbar Adjustment (Optional)

The lumbar support shall be height adjustable with a 4" range.

PERFORMANCE DATA

The work chair shall be rated to support a maximum of 350 pounds. The chair shall accommodate the 5th percentile female to the 98th percentile male (through the combination of low, standard and high-range seat heights).

The chairs shall contain no flame retardant chemicals.

See the "Seating Measurements" chart for chair dimensions.

The chair shall meet ANSI/HFES 100-2007 Human Factors Engineering of Computer Workstations standard.

CASTERS

Casters	Size Diameter	Туре	Materials	Use
ВВ	2 1/2"	hard double wheels	black nylon wheels and yoke	carpet
C7	2 1/2"	double wheels	black nylon wheels and yoke, soft polyurethane tread	hard floors or carpet
C9	2 1/2"	double wheels	black nylon wheels and yoke soft polyurethane tread internal brake	Hard floors or carpet
Glides	Size Diameter	Туре	Materials	Use
GF	2 ½"		Black nylon	hard floors or carpet

Side Chairs Performance Information

SAYL Side chairs are designed to meet or exceed all American National Standards Institute/Business and Institutional Furniture Manufacturer's Association (ANSI/BIFMA) performance requirements per ANSI x5.1 2017 General Purpose Office Chairs, which includes the following tests:

- · Back strength test (for non-tilting chairs), Section 7
- Drop test, Section 9
- · Seating impact test, Section 12
- Stability test, Section 13
- · Arm strength test vertical, Section 14
- Arm strength test horizontal, Section 15
- Back durability test (for non-tilting seats), Section 17
- Leg strength test front application, Section 19
- · Leg strength test, side application, Section 20

In addition, products have been designed and tested to Herman Miller requirements, which are derived from these ANSI minimum requirements but are much more comprehensive and generally exceed the BIFMA requirements. Herman Miller's Quality Assurance Group randomly and periodically tests standard products (seating) to ensure ongoing compliance to ANSI/BIFMA and Herman Miller corporate standards.

Methodology and Dimension Description

The dimensions indicated with a (*) are measured with the Universal Measurement Procedure For the Use of BIFMA Chair Measuring Device® (CMD) detailed in the BIFMA/CMD-1-2002 guideline.

Seat Height

Distance between the floor and the compressed seat cushion where the user's thigh meets the seat.

Seat Depth

Distance from the lumbar prominence to the front edge of the seat.

Seat Width

Width of the chair seat at the spindle center.

Backrest Height*

Distance from the seat cushion at centerline to the highest point of the chair back.

Backrest Width*

Width of the backrest at the narrowest point of the lumbar support zone.

Seat Pan Angle* Seat angle in

relation to the floor.

Backrest-to-Seat Angle Range*

Angle between the backrest and the seat from upright to fully reclined positions.

Armrest Height*

Distance from the compressed seat cushion to the top of an armrest.

Armrests, Inside Measurement*

Width between the armrests.

Armrests, Outside Measurement*

Overall distance from the outer edge of one armrest to the outer edge of the other armrest.

Seating Measurements - Side Chairs

Chair Description	Seat Height	Seat Depth	Seat Width	Seat Pan Angle	Back-to-Seat Angle	Back Height	Back Width	Arm Height
4-Leg Base								
Without arms								
AS4SSN AS4SUN	18.5″	16.9"	18.5"	10°	94°	19.8″	16.7″	N/A
With arms								
AS4SSP AS4SUP	18.5″	16.9"	18.5"	10°	94°	19.8″	16.7"	8.3"

Chair Description	Arm-pad Inside Clearance*	Overall Height	Overall Depth	Overall Width	Weight (Pounds)
4-Leg Base					
Without arms					
AS4SSN AS4SUN	N/A	34 ¼″	22 5/8"	20 7/8"	16 17 19
With arms					
AS4SSP	21.2"	34 1/4"	22 5/8"	24"	17
AS4SUP					19 21

Chair Description	Seat Height	Seat Depth	Seat Width	Seat Pan Angle	Back-to-Seat Angle	Back Height	Back Width	Arm Height
Sled Base								
Without arms								
AS5SSN AS5SUN	18"	16.9"	18.5"	6°	97°	19.3"	16.7"	N/A
With arms								

AS5SSP	18"	16.9"	18.5"	6°	97°	19.3"	16.7"	8.1"
AS5SUP								

Chair Description	Arm-pad Inside Clearance*	Overall Height	Overall Depth	Overall Width	Weight (Pounds)
Sled Base					
Without arms					
AS5SSN	N/A	34 ¼"	24 ¾"	20 7/8"	20
AS5SUN					21
					23
With arms					
AS5SSP	21.2"	34 ¼"	24 ¾"	24"	21
AS5SUP					22
					25

Side Chair

DESCRIPTION

This side chair has a 4-leg or Sled base with glides or casters. It has an upholstered seat with foam padding and is available with an upholstered or suspension back. It is available with or without arms. All styles of the 4-leg base chair can be stacked up to 4-chairs high on the floor. Sled base chairs are not stackable.

CONSTRUCTION

Seat

The side chair shall have a textured, integral color, injection glass-filled nylon seat pan with an upholstered pad. The pad includes a polypropylene shell covered in high-resiliency, medium-density molded polyurethane foam and wrapped in fabric. The upholstery shall not be glued to the foam; it shall be stapled to the polypropylene shell. See the current price book for a list of fabrics approved on SAYL chairs. **Back**

Suspension

Side chairs with suspension backs shall be constructed of a textured, integral color, injection molded, glass filled nylon frame with nylon retainers screwed in place. A perforated thermoplastic urethane suspension material shall be snapped into the frame.

Upholstered

Side chairs with upholstered backs shall be constructed of a textured, integral color, injection molded, glass filled nylon frame, an upholstered front and rear insert made of polypropylene. The front insert shall be covered with a sheet of molded urethane foam; the foam shall be glued to the front insert. Both inserts are wrapped in fabric and stapled in place. The front and rear inserts have integral snaps that sandwich the frame between them. The upholstery shall not be glued to the foam. See the current price book for a list of fabrics approved on SAYL chairs.

Arms (Optional)

The side chairs (4-leg and sled-base) shall be available without arms or with fixed arms. Arm supports shall be rigid glass-filled nylon over a steel shaft.

4- leg chair – Legs

The chair's leg shall be 7/8" diameter tubular steel and shall be finished with powder-coat epoxy paint. The legs shall be also available with a trivalent chrome finish.

Sled base chair

The sled chair's base shall be a 7/8'' diameter welded steel tubular base with a secondary steel insert for strength; and shall be finished with powder-coat epoxy paint.

Casters & Glides (Optional)

The sled-base chair shall be available with optional nylon glides (XS) for use on hard floors or carpet. The four-leg base chair shall be available with optional casters or acetal glides.

PERFORMANCE DATA

The chair shall be rated for 300 pounds.

Textiles and foam on the SAYL chair shall meet the California Technical Bulletin 117-2013 fire safety standard.

CASTERS

Casters	Size Diameter	Туре	Materials	Use
4-Leg				
32	1 7/8"	Hard, double-wheel	Black nylon wheels and yoke	Carpet only
49	1 7/8"	Soft, double-wheel	Black nylon wheels and yoke, with urethane tread	Carpet or hard floors
Glides				
4-Leg				
16	2 1/8"		Black or fog acetal	Carpet only
69	2 1/8"		Black glass-filled nylon stem; steel-plated swivel foot with FloorSaver Glide insert	Hard floors
Sled				
XS	1/8"		Poly carbonate in black, fog, clear, and studio white finishes	Carpet or hard floors

Stool Performance Information

Herman Miller, Inc., products are designed, developed, and tested to meet and exceed industry standards.

SAYL stools meet or exceed all American National Standards Institute/Business and Institutional Furniture Manufacturer's Association (ANSI/BIFMA) performance requirements per ANSI X5.1-2017 General Purpose Office Chairs, which includes the following tests:

- Back strength test (static), type I, Section 5
- Back strength test (static), types II and III, Section 6
- Base test (static), Section 7
- · Drop test (dynamic), Section 8
- Swivel test, Section 9
- Tilt mechanism test, Section 10
- Seating durability tests (cyclic), Section 11
- Stability test, Section 12
- Arm strength test (vertical), Section 13
- Arm strength test (horizontal), Section 14
- Arm durability test (cyclic), Section 21
- Back durability test (cyclic), type I, Section 15
 Back durability test (cyclic), type II and type III, Section 16
- Caster chair base durability test, Section 17
- · Out stop test for chairs with manually adjustable seat depth, Section 21

In addition, products have been designed and tested to Herman Miller requirements, which are derived from these ANSI minimum requirements but are much more comprehensive and generally exceeded the ANSI requirements. Herman Miller's Quality Assurance Group randomly and periodically tests standard products (seating) to ensure ongoing compliance to ANSI/BIFMA and Herman Miller corporate standards.

COMPLIANCE & CERTIFICATION

Compliancy FR

- California Technical Bulletin (TB117-2013) the foam and all HMI textiles used on SAYL comply with Cal TB 117.
- Cal TB 117-2013 is intended to determine the flame retardancy of resilient filling materials and textiles in upholstered furniture.

Sustainability Certifications/Compliance

- GREENGUARD® GOLD Certified
- Complies with ANSI/BIFMA M7.1-2001 and ANSI/BIFMA X7.1.
- Please contact the SAYL Environmental Product Sheet for more information.

Methodology and Dimension Description

The following measurements are displayed in the subsequent measurement charts. The measurements reflect dimensional information necessary for space planning and standards/codes compliance data. The measurements relevant to standards/codes (indicated with a *) were taken with a Chair Measuring Device (CMD) in accordance with the BIFMA/CMD-1-2002 Universal Measurement Procedure for the Use of BIFMA Chair Measuring Device quideline.

Seat Height*

Distance between the floor and the compressed seat cushion where the user's thigh meets the seat.

Seat Depth*

Distance from the lumbar prominence to the front edge of the seat.

Seat Width*

Width of the chair seat within the indicated measuring zone.

Backrest Height*

Distance from the seat cushion at centerline to the highest point of the chair back.

Backrest Width*

Width of the backrest at the narrowest point of the lumbar support zone.

Lumbar Support

Height of the lumbar support region as measured from the base of the chair back to the top and bottom of the lumbar support areas.

Overall Height (Maximum)

Distance from the floor to the highest point of a chair back (unloaded), with seat height at highest position.

Overall Depth

The distance from the forward caster position/extended seat to the back. Center measured with the chair at an upright position.

Weight

Does not include packaging

Back Tilt Range*

Angle of the back from upright to fully reclined positions in relation to the floor.

Seat Pan Angle* Seat angle in

relation to the floor.

Backrest-to-Seat Angle Range*

Angle between the backrest and the seat from upright to fully reclined positions.

Armrest Height*

Distance from the compressed seat cushion to the top of an armrest.

Armrests, Inside Measurement Width

between the armrests.

Armrests, Outside Measurement

Overall distance from the outer edge of one armrest to the outer edge of the other armrest.

Base Diameter, Outside

Overall diameter of the base.

Seating Measurements - Stools (Suspension & Mid-back Upholstered)

Chair Descri	ption	Overall Height	Overall Width	Overall Depth	Weight (pounds)	Seat Height	Seat Depth	Seat Width	Backrest Height	Backrest Width
Fully Adjus	table Arms									
	AS7VA53AF AS7SA53AF	51 ¾"	26.75"	26"	Polymer: 39.3	23.5″- 33.5″	Fixed 16"	18.25"	20.9"	16.9"
Suspension	AS7VA53AA AS7SA53AA				Polished: 42.6		Adjust 16-18"			
Mid-back	AS7VC53AF AS7SC53AF				Polymer: 40.8		Fixed 16"			17.1"
Upholstered	AS7VC53AA AS7SC53AA				Polished: 43.6		Adjust 16-18"			
Height Adj	ustable Arms									
	AS7VA53HF AS7SA53HF	51 ¾"	24.75"	26"	Polymer: 38.9	23.5″- 33.5″	Fixed 16"	18.25"	20.9"	16.9"
Suspension	AS7VA53HA AS7SA53HA				Polished: 41.7		Adjust 16-18"	-		
Mid-back	AS7VC53HF AS7SC53HF				Polymer: 39.9	-	Fixed 16" Adjust 16-18"	-		17.1"
Upholstered	AS7VC53HA AS7SC53HA				Polished: 42.7			-		
Fixed Arms	•									
	AS7VA53PF AS7SA53PF	51 ¾"	24.75"	26"	Polymer: 38.9	23.5″- 33.5″	Fixed 16"	18.25"	20.9"	16.9"
Suspension	AS7VA53PA AS7SA53PA				Polished: 41.7		Adjust 16-18"	-		
Mid-back	AS7VC53PF AS7SC53PF				Polymer: 39.9		Fixed 16"			17.1"
Upholstered	AS7VC53PA AS7SC53PA				Polished: 42.7		Adjust 16-18"			
No Arms										
	AS7VA53NF AS7SA53NF	51 ¾"	23.5″	26"	Polymer: 37.2	23.5″- 33.5″	Fixed 16"	18.25"	20.9"	16.9"
Suspension	AS7VA53NA AS7SA53NA				Polished: 40	shed: Adjust 16-18" rmer: Fixed 16"				
Mid-back	AS7VC53NF AS7SC53NF				Polymer: 38.2				17.1"	
Upholstered	AS7VC53NA AS7SC53NA				Polished: 41		Adjust 16-18"			

Seat Pan – Backrest Angle	Seat Pan Angle	Tilt Range	Lumbar Support	Armrest Clearance /Inside Distance	Base Diameter Outside	Armrest Height	Armrest Length
94/96/108°	-3/3/13°	91°/ 101°/117°	Fixed: 9.0" Adj: 4" range	16.5-19.7"	26.0"	6.7″-10.8″	6.4"-7.7"
94/96/108°	-3/3/13°	91°/ 101°/117°	Fixed: 9.0" Adj: 4" range	19.3"	26.0"	6.7″-10.8″	6.9″-7.5″
94/96/108°	-3/3/13°	91°/ 101°/117°	Fixed: 9.0" Adj: 4" range	19.1"	26.0"	9.4"	7.8"
94/96/108°	-3/3/13°	91°/ 101°/117°	Fixed: 9.0" Adj: 4" range	N/A	26.0"	N/A	N/A

Chair Descri	ption	Overall Height	Overall Width	Overall Depth	Weight (pounds)	Seat Height	Seat Depth	Seat Width	Backrest Height	Backres Width
Fully Adjus	table Arms									
	AS7VA52AF AS7SA52AF	51 ¾"	26.75"	26"	Polymer: 39.3	23.5″- 33.5″	Fixed 16"	18.25"	20.9″	16.9"
Suspension	AS7VA52AA AS7SA52AA				Polished: 42.6		Adjust 16-18"			
Mid-back	AS7VC52AF AS7SC52AF				Polymer: 40.8		Fixed 16"			17.1"
Upholstered	AS7VC52AA AS7SC52AA				Polished: 43.6		Adjust 16-18"			
Height Adj	ustable Arms									
	AS7VA52HF AS7SA52HF	51 ¾"	24.75″	26"	Polymer: 38.9	23.5″- 33.5″	Fixed 16"	18.25"	20.9"	16.9"
Suspension	AS7VA52HA AS7SA52HA				Polished: 41.7		Adjust 16-18"			
Mid-back	AS7VC52HF AS7SC52HF				Polymer: 39.9		Fixed 16"			17.1"
Upholstered	AS7VC52HA AS7SC52HA				Polished: 42.7		Adjust 16-18"			
Fixed Arms										
	AS7VA52PF AS7SA52PF	51 ¾"	24.75"	26"	Polymer: 38.9	23.5″- 33.5″	Fixed 16"	18.25"	20.9"	16.9″
Suspension	AS7VA52PA AS7SA52PA				Polished: 41.7		Adjust 16-18"			
Mid-back	AS7VC52PF AS7SC52PF				Polymer: 39.9		Fixed 16"			17.1"
Upholstered	AS7VC52PA AS7SC52PA				Polished: 42.7		Adjust 16-18"			
No Arms	1									
	AS7VA52NF AS7SA52NF	51 ¾"	23.5″	26"	Polymer: 37.2	23.5″- 33.5″	Fixed 16"	18.25"	20.9"	16.9"

Suspension	AS7VA52NA AS7SA52NA	Polished: 40	Adjust 16-18"	
Mid-back	AS7VC52NF AS7SC52NF	Polymer: 38.2	Fixed 16"	17.1"
Upholstered	AS7VC52NA AS7SC52NA	Polished: 41	Adjust 16-18"	

Seat Pan – Backrest Angle	Seat Pan Angle	Tilt Range	Lumbar Support	Armrest Clearance /Inside Distance	Base Diameter Outside	Armrest Height	Armrest Length
96/108°	3/13°	101°/117°	Fixed: 9.0" Adj: 4" range	16.5-19.7"	26.0"	6.7″-10.8″	6.4"-7.7"
96/108°	3/13°	101°/117°	Fixed: 9.0" Adj: 4" range	19.3″	26.0"	6.7″-10.8″	6.9"-7.5"
96/108°	3/13°	101°/117°	Fixed: 9.0" Adj: 4" range	19.1"	26.0"	9.4"	7.8"
96/108°	3/13°	101°/117°	Fixed: 9.0" Adj: 4" range	N/A	26.0"	N/A	N/A

Seating Measurements – Stools (High-back Upholstered)

Chair Descri	ntion	Overall	Overall	Overall	Weight	Seat	Seat	Seat	Backrest	Backrest
Chair Descri	ption	Height	Width	Depth	(pounds)	Height	Depth	Width	Height	Width
Fully Adjus	table Arms									
High-back	AS7VD53AF AS7SD53AF	54 1/4"	26.75"	26"	Polymer: 41.1	23.5″- 33.5″	Fixed 16"	18.25"	23.8"	17.1"
Upholstered	AS7VD53AA AS7SD53AA				Polished: 43.9		Adjust 16-18"			
Height Adj	ustable Arms									
High-back	AS7VD53HF AS7SD53HF	54 ¼"	24.75″	26"	Polymer: 40.2	23.5″- 33.5″	Fixed 16"	18.25"	23.8"	17.1"
Upholstered	AS7VD53HA AS7SD53HA				Polished: 43		Adjust 16-18"			
Fixed Arms	·									
High-back	AS7VD53PF AS7SD53PF	54 1/4"	24.75″	26"	Polymer: 40.2	23.5″- 33.5″	Fixed 16"	18.25"	23.8"	17.1"
Upholstered	AS7VD53PA AS7SD53PA				Polished: 43		Adjust 16-18"			
No Arms										
High-back	AS7VD53NF AS7SD53NF	54 1/4"	23.5"	26"	Polymer: 38.5	23.5″- 33.5″	Fixed 16"	18.25"	23.8"	17.1"
Upholstered	AS7VD53NA AS7SD53NA				Polished: 41.3		Adjust 16-18"			

Seat Pan – Backrest Angle	Seat Pan Angle	Tilt Range	Lumbar Support	Armrest Clearance /Inside Distance	Base Diameter Outside	Armrest Height	Armrest Length
94/96/108°	-3/3/13°	91°/ 101°/117°	Fixed: 9.0" Adj: 4" range	16.5-19.7"	26.0"	6.7″-10.8″	6.4"-7.7"
94/96/108°	-3/3/13°	91°/ 101°/117°	Fixed: 9.0" Adj: 4" range	19.3"	26.0"	6.7″-10.8″	6.9″-7.5″
94/96/108°	-3/3/13°	91°/ 101°/117°	Fixed: 9.0" Adj: 4" range	19.1"	26.0"	9.4"	7.8"
94/96/108°	-3/3/13°	91°/ 101°/117°	Fixed: 9.0" Adj: 4" range	N/A	26.0"	N/A	N/A

Chair Descri	ption	Overall Height	Overall Width	Overall Depth	Weight (pounds)	Seat Height	Seat Depth	Seat Width	Backrest Height	Backrest Width
Fully Adjus	table Arms									
High-back	AS7VD52AF AS7SD52AF	54 1/4"	26.75"	26" Polymer: 23.5"- 41.1 33.5"		Fixed 18.25" 23.		23.8″	23.8" 17.1"	
Upholstered	AS7VD52AA AS7SD52AA				Polished: 43.9		Adjust 16-18"			
Height Adj	ustable Arms									
High-back	AS7VD52HF AS7SD52HF	54 1/4"	24.75″	26"	Polymer: 40.2	23.5″- 33.5″	Fixed 16"	18.25"	23.8"	17.1"
Upholstered	AS7VD52HA AS7SD52HA				Polished: 43		Adjust 16-18"			
Fixed Arms	5									
High-back	AS7VD52PF AS7SD52PF	54 1/4"	24.75"	26"	Polymer: 40.2	23.5″- 33.5″	Fixed 16"	18.25"	23.8"	17.1"
Upholstered	AS7VD52PA AS7SD52PA				Polished: 43		Adjust 16-18"			
No Arms										
High-back	AS7VD52NF AS7SD52NF	54 1/4"	23.5″	26"	Polymer: 38.5	23.5″- 33.5″	Fixed 16"	18.25"	23.8"	17.1"
Upholstered	AS7VD52NA AS7SD52NA				Polished: 41.3		Adjust 16-18"			

Seat Pan – Backrest Angle	Seat Pan Angle	Tilt Range	Lumbar Support	Armrest Clearance /Inside Distance	Base Diameter Outside	Armrest Height	Armrest Length
96/111°	3/13°	101°/117°	Fixed: 9.0" Adj: 4" range	16.5-19.7"	26.0"	6.7"-10.8"	6.4"-7.7"
96/111°	3/13°	101°/117°	Fixed: 9.0" Adj: 4" range	19.3"	26.0"	6.7"-10.8"	6.9″-7.5″

96/111°	3/13°	101°/117°	Fixed: 9.0" Adj: 4" range	19.1"	26.0″	9.4"	7.8"
96/111°	3/13°	101°/117°	Fixed: 9.0" Adj: 4" range	N/A	26.0"	N/A	N/A

Stool

DESCRIPTION

This stool has a frameless 3D Intelligent™ Suspension back that allows freedom of movement, while providing targeted back support and moving heat away from the body. The suspension is supported by a Y Tower™ and anchored at the bottom by the ArcSpan™. The stool is also available with an upholstered back. The stool has an upholstered seat with foam padding and passive Posturefit® back support. The Harmonic™ tilt provides continuous balance and lets the body recline naturally, pivoting at the ankles, knees, and hips. The stool has a 5-star base and seat height adjustments. A user adjustable footrest assembly is included to provide a place for foot support. Stools are shipped fully assembled.

Tilt options include a tilt limiter and tilt limiter with seat angle. The tilt limiter allows the user to set the tilt range to limit the amount of recline. The tilt limiter with seat angle allows the user to set the tilt range and select a 5° forward seat angle.

Seat options include a fixed 16"seat depth, or an adjustable seat depth that allows the user to adjust the depth from 16" to 18".

Back-support options include a standard option with no additional support, and an adjustable lumbar support option. The standard option has passive Posturefit back support molded directly into the strands of the suspension material, providing targeted support at the base of the back, below the beltline, that helps achieve healthier posture and improved lower back comfort. The adjustable lumbar support option adds a user-adjustable lumbar that adjusts 4" in height.

Arm choices include a no arm option; a fixed, non-adjustable option; a height adjustable option that allows the arms to move 4" vertically; and a fully adjustable option that allows the arms to move 4" vertically, 1 3/8" horizontally, 2" front-to-back, with arm pads that pivot 11° inward and 11° outward.

CONSTRUCTION

Seat

The contoured seat shall be constructed of molded polypropylene insert with molded polyurethane foam. The foam shall have a nominal $\frac{1}{2}$ '- 1 $\frac{1}{2}$ " thickness and have waterfall edges. Fabric is applied non-bonded. When chairs are refurbished, the complete seat assembly can be replaced.

Back

Suspension

The suspension back shall be constructed of thermoplastic urethane (TPU), stretched and fastened onto a structural frame (ArcSpan) on the bottom and fastened at the top by a Y-Tower made of an injection-molded glass-filled nylon.

Upholstered

The upholstered back shall have a polypropylene insert with urethane foam ($\frac{1}{2}$ '- 1'' thick) with a stapled textile cover.

Lumbar Pad (optional)

Suspension Back Models

The suspension back lumbar pad is constructed of unfilled nylon. It attaches to and slides up and down on an acetal lumbar bow. This bow is attached to the suspension back by two translucent polycarbonate clips.

Upholstered Models

The lumbar adjustment shall be a polypropylene pad supported by a polypropylene insert and a glass-filled nylon lever.

See "Adjustments" for lumbar-support adjustments.

Arms (Optional)

Chairs shall be available with no arms, fixed arms, height-adjustable arms, and fully adjustable arms.

Each arm shall have an arm support stem of glass-filled nylon with self-skinning polyurethane arm pads. Fixed and height adjustable arm pads shall be 8 6/8" by 2 3/4". Fully adjustable arm pads shall be 9 1/2" by 3 3/4".

Arms are detachable without tools; they are field-replaceable.

Tilt

The tilt mechanism shall be 2 fiberglass leaf springs, a lead-screw-driven tension adjustment, and a stamped steel housing. The tilt mechanism shall be in a 4-piece, snap-together polypropylene cover.

The tilt tension adjustment control shall be a glass-filled polypropylene knob located to the side. The tilt tension adjustment shall have 18 full revolution turns.

A tilt limiter adjustment, constructed of an injection-molded glass-reinforced nylon tilt limiter lever shall come standard and extend from the side of the tilt. On chairs with an optional seat-angle adjustment, an injection-molded glass-reinforced lever shall extend out on the left side.

Base

The 5-star base shall be glass-filled nylon with a textured finish. An optional die-cast aluminum base shall be available for a polished aluminum finish. The chair shall swivel 360°.

The stool base shall house a unitized pneumatic cylinder seat height adjustment mechanism contained in 2 steel tubes. The inner tube shall slide and rotate in a bushing within an outer tube. The outer tube shall be coated black.

The seat height activator shall protrude from the back of the tilt tension knob. The activator shall be glass filled polypropylene.

A pneumatic cylinder is included to provide seat height ranges. Pneumatic cylinders can be replaced on site. See "Adjustments" for seat height ranges.

Casters

Chairs shall be furnished with interchangeable casters. The chair shall be available with 2 ½" diameter casters. Casters for use on carpet only shall have a steel stem and black nylon wheels and yoke. Casters for use on hard floors or carpet shall have a steel stem, black nylon wheels and yoke, and soft polyurethane tread. See the "casters and Glides" section for more information.

Footrest Assembly

Stools shall be furnished with a user adjustable footrest assembly. The footrest assembly is constructed of an aluminum die cast spoke, tubular steel foot ring with trivalent chrome finish, and integral locking mechanism.

ADJUSTMENTS

Seat Height

The seat height shall be adjusted by raising the seat-height lever, which is mounted to the right side of the seat. Raising the lever shall increase the seat height when the chair is unoccupied, and lower the seat height when the seat is occupied.

The approximate seat height range (with CMD) shall be 23.5" to 33.5".

Tilt

The tilt mechanism shall be a Harmonic[™] tilt. The tilt tension shall be adjusted by turning the tilt tension knob, which is located on the right side of the seat.

Back Recline

Stools with a standard tilt and tilt limiter shall have a nominal 16° of body-weight controlled recline (from horizontal). Stools with a tilt limiter shall allow users to limit the amount of back recline in 2 incremental adjustments. Stools with a tilt limiter and seat angle adjustment shall have a back recline range and a tilt limiter that allows users to limit the amount of back recline in 2 incremental positions. (3 positions with forward tilt)

Seat Angle

Stools with a tilt limiter and seat angle adjustment shall let the user select a $+3^{\circ}$ horizontal or -3° forward seat angle (6° from neutral angle).

Adjustable Arms (Optional)

The adjustable arms shall feature a height, width, pivot and fore/aft adjustment. They shall have a height range adjustment of 4". The arms width adjustment range shall be approximately 1 3/8"(each arm). The arm caps will pivot 11° in and 11° out. The arm caps will move front-to-back by 2".

Height Adjustable Arms (Optional)

The height adjustable arms shall have a height range adjustment of 4".

Lumbar Adjustment (Optional)

The lumbar support shall be height adjustable with a 4" range.

Footrest Assembly

The footrest assembly is height adjustable with a range of 4 1/2".

PERFORMANCE DATA

Stools shall be rated to support a maximum of 350 pounds. See the "Seating Measurements" chart for chair dimensions.

CASTERS

Casters	Size Diameter	Туре	Materials	Use
ВВ	2 1/2"	hard double wheels	black nylon wheels and yoke	carpet
C7	2 ½"	double wheels	black nylon wheels and yoke, soft polyurethane tread	hard floors or carpet
C9	2 1/2"	double wheels	black nylon wheels and yoke soft polyurethane tread internal brake	Hard floors or carpet
Glides	Size Diameter	Туре	Materials	Use
GF	2 ½"		Black nylon	hard floors or carpet