#### TOL0049



### Design By

Michele De Lucchi Giancarlo Fassina

#### Collection =

Design







### Colors & Finishes =



# Features & Accessories =

Specifications =

**Delivered lumens** 

Light output ratio

Life expectancy

Control type

Input Voltage

Packaging • 2 Boxes

Driver

Led type

**Power consumption** 

**CCT (Correlated Color Temperature)** 

CRI (Color Rendering Index)

- Fully adjustable, articulated arm structure
- Tiltable and rotatable diffuser (90 degrees in both directions)
- Interchangeable plug options accommodate most electrical outlets for global diversity

1 x 10-5/16" x 7-9/16" x 33-3/16" / 3.75 lbs - 26 cm x 19 cm x 84 cm / 1.702 kg 1 x 11-7/8" x 11-7/8" x 3-13/16" / 7.39 lbs - 30 cm x 30 cm x 9.5 cm / 3.35 kg

357lm

33.4lm/W

10.69W 10W Array\*

3000K

50000Hrs

DIMMABLE (On Head)

>80


120V

N/A

#### Materials •

- Arms and diffuser in aluminum
- Joints and tension control knobs in polished die-cast aluminum
- Tension cables in stainless steel
- Base in weighted steel with stamped aluminum cover

### Dimensions •



Direct

Light distribution

### Luminaire weight

8.12 lbs / 3.69 kg

## Warranty =

5 year limited warranty

Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane