

# **Safety Data Sheet**

# Section 1 Product and Company Identification

CFB., Inc. 1123 Commerce Dr. Bristol, IN 46507 United States of America Phone: 574-848-5288 Fax: 574-848-5963 Emergency Phone Numbers CFB 574-848-5288 Normal Business Hrs. USA Chemtrec 800-424-9300 24 Hours International Chemtrec 703-527-3887

**Recommended Usage:** Rust Preventive **Other Identifier:** Mixture

Product Name: GLOC 6510 HF Product Number: CF6510

Date Prepared: 01/06/2020

# **Section 2 Hazards Identification**

Classification of the Mixture: Clear amber liquid, bland odor. Hazard Classification: Aspiration Hazard Category 1 Skin Irritation Category 2 Systemic Toxicity Category 3 Hazard Statement: May be fatal if swallowed and enters airways. Causes Skin Irritation May cause drowsiness and dizziness.

Signal Word: Danger

**Pictograms:** 



#### **Precautionary Statements:**

If swallowed: Immediately call a poison center or physician. Do not induce vomiting.

Use only outdoors or in a well-ventilated area. Avoid breathing fumes, mists, vapors or spray. In case of fire use dry chemical or foam for extinction. Wear protective gloves. Wash thoroughly after handling. If on skin, wash with plenty of soap and water. If skin irritation occurs, seek medical attention. Take off contaminated clothing and wash before re-use.

Store container tightly closed in a cool well-ventilated place. Dispose of contents/container to appropriate waste site or reclaimer in accordance with local and national regulations. Keep out of reach of children. If inhaled, remove victim to fresh air and keep at rest in a position comfortable for breathing. Keep away from flames and hot surfaces.

Classification complies with OSHA Hazard Communication Standard(29 CFR 1910.1200) and is consistent with provisions of GHS. **Quantity of Ingredients with Unknown Acute Toxicity:** <1.0%

Section 3 Composition Infor	mation on Ingredie	nts
Ingredient	WT %	CAS #
Distillates (petroleum) hydrotreated heavy naphthenic	<25	64742-52-5
Distillates(petroleum) hydrotreated middle	70-90	64742-46-7

#### Section 4 First Aid Measures

Eyes: Flush eyes with running water for at least 15 minutes. If redness, blurred vision or irritation persists, transport to nearest medical facility for additional treatment.

Skin: Flush skin with water, wash with soap and water. Remove contaminated clothing. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility for additional treatment.

Ingestion: Do NOT induce vomiting and obtain medical attention. Have victim rinse mouth out with water. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.

#### **Section 5 Fire Fighting Measures**

#### Flammable Properties:

Flash point: 205°F (ASTM D56) Flammable limits in air: N/A Lower, N/A Upper 68°F Auto ignition temperature: N/A Extinguishing media: CO<sub>2</sub>, dry chemical, foam

#### Special firefighting measure:

Procedures for an oil fire should be followed. Use self-contained breathing apparatus. Use foam or dry chemical to extinguish fire. Water may be used only to keep surrounding containers cool. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

#### **Section 6 Accidental Release Measures**

Eliminate ignition sources and ventilate area. •

Absorb spillage with inert absorbent material.

- Advise EPA/state agency if required.
- Use proper personal protective equipment for clean-up.

- Contain spill and keep from entering waterways or sewers.

- Treat contaminated absorbent same as spilled product.

### **Section 7 Handling and Storage**

Handling and Storage Precautions: Avoid heat, open flames, including pilot lights, and strong oxidizing agents. Use general ventilation to prevent vapor accumulation. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Have appropriate fire extinguishers and spill clean-up equipment in or near storage area. Work/Hygienic Practices: Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet. Launder contaminated clothing before reuse. Properly dispose of contaminated leather articles such as shoes or belts that cannot be decontaminated. Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse.

# **Section 8 Personal Protection/ Exposure Controls**

Engineering Controls: Use adequate ventilation to keep vapors and mists of this material below applicable standards.

**Respiratory Protection:** If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910.134.

**Skin Protection:** Use protective clothing that is chemically resistant to this product. Acceptable materials for gloves and aprons are: neoprene, nitrile rubber or viton.

Eye Protection: Use safety glasses or goggles. Have suitable eye wash water available.

**Other/General Protection:** For mists and vapors: Air Purifying, organic vapor cartridge, NIOSH approved respirator. Use self-contained breathing apparatus for environments with unknown concentrations or emergency situations.

Chemical Name	OSHA TWA (mg/m <sup>3</sup> )	ACGIH TWA (mg/m <sup>3</sup> )
Distillates (petroleum) hydrotreated naphthenic	5mg/m <sup>3</sup> (Mist)	5mg/m <sup>3</sup>
Distillates(petroleum) hydrotreated middle	5mg/m <sup>3</sup> (Mist)	$5 mg/m^3$

Se	ection 9 Physic	cal and Chemica	al Properties		
Color:	Amber	Vapor Pressure:	N/A	Solubility in Water:	Insoluble
Appearance:	Clear Liquid	% Volatile by Volume:	85	Evaporation Rate	
Odor:	Characteristic	Vapor Density (air = 1):	N/A	(Butyl Acetate = 1):	<1
<b>Boiling Point:</b>	: >350° F	<b>Reactivity in Water:</b>	Non-reactive	Specific Gravity:	0.8222
рН@ 10%:	N/A	Viscosity @ 40C:	<14 Cst		

#### **Section 10 Stability and Reactivity**

Stability: StableConditions to avoid: Sources of ignition.Decomposition Products: Oxides of Carbon and Hydrogen .

**Incompatibility:** Strong oxidizing or reducing agents. **Hazardous Polymerization:** Will not occur.

# **Section 11 Toxicological Information**

Likely Routes of Exposure: Inhalation, skin, eyes and ingestion.

Potential Health Effects: Know chronic or acute health risks.

**Eye Effects:** This mixture can cause irritation, redness to the eyes.

Skin Effects: Prolonged and/or repeated skin contact may cause irritation/dermatitis.

**Oral Effects:** May be fatal if swallowed and enters airways. Aspiration hazard.

Inhalation Effects: Mists and vapors may cause respiratory irritation ,drowsiness and dizziness.

Chronic Health Effects: Not classified as specific target organ toxicant.

Mutagenicity: Negative

**Carcinogenicity:** This mixture does not contain any component that is listed as a carcinogenic or a potential carcinogen by the National Toxicology Program, by the I.A.R.C. monographs or by OSHA.

Teratogenicity: Negative.

Sensitization: Negative

Toxicological Data: No data available or estimated

# **Section 12 Ecological Information**

Not classified due to inadequate data available on this mixture. Recommend avoidance of release to the environment.

### **Section 13 Disposal Considerations**

Avoid release to the environment. Dispose in a safe manner in accordance with national, state and local regulations. Not a RCRA hazardous waste if uncontaminated. If "used" RCRA criteria must be determined. Dispose of container by recycling or if permitted incineration.

### **Section 14 Transportation Information**

Proper Shipping Name: Lubricating Oil
Shipping Class: 65
Dot Identification Number: N/A
Dot Shipping Label: Not regulated by DOT.
TDG Classification: Not controlled under TDG (Canada).

Sudden Release of Pressure Hazard: No

### **Section 15 Regulatory Information**

U.S. Federal Regulatory Information: SARA 302 Threshold Planning Quantity: N/A SARA 311 Categories: Acute Health Effects: Chronic Health Effects:

Fire Hazard:

Reactivity Hazard:

SARA 304 Reportable Quantity: N/A

**EPA/TSCA Inventory:** The components of this product are listed on the EPA/TSCA inventory of chemicals. **EPA Hazard Classification Code:** Not applicable **CERCLA:** No chemicals in this product are subject to the reporting requirements of CERCLA. **SARA Title III - Section 313 Supplier Notification:** No Chemicals in this product exceed the DE Minimus reporting level established by SARA Title III, Section 313 and 40 CFR 372.

Yes

No

No

None

WHMIS Classification: WHMIS controlled. Class D; Division 2, Subdivision B: otherwise causing toxic effects.

Other Regulations: All components of this formulation are listed on the CEPA-DSL (Domestic Substance List)

Section 16 Other Informati			
NFPA Hazard	Rating:		
	Health:	1	Slight
	Flammability:	1	Slight
	Reactivity:	0	Negligible
SDS Dated: 05	/18/15		
SDS Revision I	Date: 01/06/2020		
*Threshold Lin	nit Value/Personal Exp	osu	e Limit
N/A = Not App	licable		
N/E = Not Estat	blished		

#### **Disclaimer of Express or Implied Warranties**

The information contained herein is based upon data believed to be reliable and reflects our best professional judgment. Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy of completeness of the information contained therein and assume no responsibility regarding the suitability of this information for the user's intended purpose or for the consequence of its use. Each individual should make a determination as to the suitability of the information for his/her particular purpose(s).