



Series 7092/7093 | GST® II

Available color covers:

RED **BLK**

Inner Tube	Black EPDM; ARPM Class C oil resistance
Temperature	-40°F to +212°F (-40°C to +100°C)
Reinforcement	Multiple textile plies
Cover	EPDM; smooth finish

Part Number	Nom ID		Reinf Layers	Hose O.D.		Approx Weight		Min. Bend Radius		Max Working Pressure		Perm Cplg Rec	Nom Std Pack Qty	Package Type
	in	mm		in	mm	lbs/ft	kg/m	in	mm	psi	bar			
RED														
7092-75304	3/4	19.1	4	1.2	29.4	0.37	0.55	6	152	300	21	HY	400	Reel
7092-100304	1	25.4	4	1.4	36.5	0.51	0.76	8	203	300	21	HY	300	Reel
7092-125204	1-1/4	31.8	4	1.8	45.2	0.77	1.15	9	229	200	14	HY	250	Reel
7092-150204	1-1/2	38.1	4	2.0	51.6	0.84	1.25	10	254	200	14	43	200	Reel
7092-200154	2	50.8	4	2.6	64.8	1.13	1.68	14	356	200	14	43	250	Reel
BLACK														
7093-75304	3/4	19.1	4	1.2	29.4	0.37	0.55	6	152	300	21	HY	400	Reel
7093-100304	1	25.4	4	1.4	36.5	0.51	0.76	8	203	300	21	HY	300	Reel
7093-125204	1-1/4	31.8	4	1.8	45.2	0.77	1.15	9	229	200	14	HY	250	Reel
7093-150204	1-1/2	38.1	4	2.0	51.6	0.84	1.25	10	254	200	14	43	200	Reel
7093-200154	2	50.8	4	2.6	64.8	1.13	1.68	14	356	200	14	43	250	Reel



Series 7395 | E-Z Form™ GS

Inner Tube	Black EPDM
Temperature	-50°F to +257°F (-45°C to +125°C)
Reinforcement	Multiple textile braids or plies with wire helix
Cover	Black EPDM; Greek corrugated finish
Vacuum	29" Hg (737 mm Hg)

Part Number	Nom ID		Reinf Layers	Hose O.D.		Approx Weight		Min. Bend Radius		Max Working Pressure		Perm Cplg Rec	Nom Std Pack Qty	Package Type
	in	mm		in	mm	lbs/ft	kg/m	in	mm	psi	bar			
7395-0375300	3/8	9.5	2	0.8	20.8	0.24	0.36	0.9	24.1	150	11	HY	300	Reel
7395-0500300	1/2	12.7	2	0.9	23.8	0.27	0.40	0.9	24.1	75	5	HY	300	Reel
7395-0750300	3/4	19.1	2	1.2	30.0	0.35	0.52	1.4	36.3	75	5	HY	300	Reel
7395-1000300	1	25.4	2	1.4	36.0	0.41	0.61	1.4	36.3	75	5	HY	300	Reel
7395-1250130	1-1/4	31.8	2	1.7	43.0	0.50	0.75	2.2	56.7	75	5	HY	130	Coil
7395-1500130	1-1/2	38.1	2	1.9	49.0	0.58	0.86	2.9	74.1	75	5	43	130	Coil
7395-2000130	2	50.8	2	2.5	63.0	0.96	1.43	4.6	117.4	75	5	43	130	Coil

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource.

Note: for additional sizing and packaging please visit Parker.com/safehose



WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.