

Spiraflex® Gray Light Duty



Product Specifications

Application

This hose is for light-duty water discharge service.

Construction

> Tube

Black Pliovic® compound

> Cover

Gray Pliovic® compound

> Reinforcement

Synthetic fabric

Temperature Range

-10°F to 150°F (-23°C to 66°C)

Packaging

300' continuous one-piece, coiled and banded

Branding

Example: Continental Spiraflex® Gray 2"
(50.8 mm) 80 psi (0.55 MPa) Made in USA

Couplings

Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Order Codes

537-555

Spiraflex® Gray Light Duty

| SAP # | ID | | Nom. OD | | Max. WP | | Weight | |
|----------|-----|-------|---------|-------|---------|------|---------|------|
| | in. | mm | in. | mm | psi | MPa | lb./ft. | kg/m |
| 20012556 | 1½ | 38.1 | 1.72 | 43.7 | 90 | 0.62 | 0.18 | 0.27 |
| 20012562 | 2 | 50.8 | 2.22 | 56.4 | 80 | 0.55 | 0.24 | 0.35 |
| 20012567 | 2½ | 63.5 | 2.79 | 70.9 | 60 | 0.41 | 0.35 | 0.52 |
| 20012572 | 3 | 76.2 | 3.27 | 83.1 | 50 | 0.34 | 0.38 | 0.57 |
| 20012576 | 4 | 101.6 | 4.33 | 110.0 | 45 | 0.31 | 0.63 | 1.01 |
| 20012580 | 6 | 152.4 | 6.38 | 162.1 | 35 | 0.24 | 1.14 | 1.70 |

Hose design ratio (burst pressure) 3:1.

Note: Working pressures are rated at 72°F (22°C).

Air & Multipurpose

General Purpose
Heavy Duty
Push-on

Chemical Transfer

Cleaning Equipment

Food & Beverage
Transfer

Food Washdown

Marine

Material Handling

Abrasives
Bulk Transfer
Cement & Concrete

Mining

Petroleum

Aircraft Fueling
Dispensing
Dock
Rig Supply
Transfer Discharge
Transfer S&D

Specialty

Steam

Vacuum

Water

Discharge
Suction & Discharge
Washdown
Garden

Welding

Coupling Systems

Equipment

Appendix