# **Service Station Air**



## **Product Specifications**

#### **Application**

For general airline service stations, automobile repair shops, garages, etc.

#### Construction

#### > Tube

EPDM synthetic rubber, ARPM Class C (Limited Oil Resistance)

#### > Cover

EPDM synthetic rubber (red)

#### > Reinforcement

Spiral synthetic yarn

#### **Temperature Range**

-40°F to 210°F (-40°C to 99°C)

### **Packaging**

500' reels, maximum 3 pieces, 50' increments

#### Branding

Example: Service Station Air Made in USA Continental

#### Couplings

Contact fitting manufacturer for proper fitting recommendation and coupling procedure.



#### **Order Codes**

569-018

### **Service Station Air**

SAP#	ID		Nom. OD		Max. WP		Weight	
Red	in.	mm	in.	mm	psi	MPa	lb./ft.	kg/m
20026058	1/4	6.35	0.59	14.99	250	1.72	0.16	0.24
20026063	3/8	9.53	0.71	18.03	250	1.72	0.21	0.31

Hose design ratio (burst pressure) 4:1.

Air & Multipurpose General Purpose Heavy Duty Push-on

**Chemical Transfer** 

**Cleaning Equipment** 

Food & Beverage Transfer

Food Washdown

Marine

Material Handling
Abrasives

Bulk Transfer Cement & Concrete

Mining

Petroleum

Aircraft Fueling
Dispensing
Dock
Rig Supply
Transfer Discharge

Transfer S&D

Specialty

Steam

Vacuum

Water

Discharge Suction & Discharge Washdown Garden

Welding

Coupling Systems

Equipment

Appendix

