

# Con-Ag 150 Water S&D

**NEW**



## Product Specifications

### Application

A general purpose water suction and discharge hose for applications in medium- to heavy-duty operations such as construction or agriculture.

### Construction

#### > Tube

Black EPDM

#### > Cover

Black EPDM (wrapped impression)

#### > Reinforcement

Spiral-plyed fabrics with double wire helix

### Temperature Range

-40°F to 180°F (-40°C to 82°C)

### Branding

Continental CON-AG 150 WATER S&D  
150 psi WP ##### Made in Canada

### Couplings

Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

### Order Codes

542-657 (1"-6")

541-657 (8")

## Con-Ag 150 Water S&D

SAP #	ID	Nom. OD		Max. WP		Bend Radius		Vacuum HG		Weight		
		in.	mm	in.	mm	psi	MPa	in.	mm	in.	mm	lb./ft.
20957399	1	25.4	1.40	35.5	150	1.03	3	76	29	737	0.48	0.71
20957430	1¼	31.8	1.65	31.8	150	1.03	4	102	29	737	0.61	0.91
20957431	1½	38.1	1.90	38.1	150	1.03	5	127	29	737	0.72	1.07
20957432	2	50.8	2.44	50.8	150	1.03	7	178	29	737	1.02	1.52
20957433	2½	63.5	2.99	63.5	150	1.03	10	254	29	737	1.46	2.17
20957434	3	76.2	3.51	76.2	150	1.03	14	356	29	737	1.78	2.65
20957417	4	101.6	4.56	101.6	150	1.03	18	457	29	737	2.55	3.80
20927418	6	152.4	6.70	152.4	150	1.03	27	686	29	737	5.31	7.90
20957501	8	203.2	8.01	203.4	150	1.03	48	1219	29	737	9.13	13.59

Hose design ratio (burst pressure) 3:1.

**Air & Multipurpose**  
General Purpose  
Heavy Duty  
Push-on

Chemical Transfer

Cleaning Equipment

Food & Beverage  
Transfer

Food Washdown

Marine

**Material Handling**  
Abrasives  
Bulk Transfer  
Cement & Concrete

Mining

**Petroleum**  
Aircraft Fueling  
Dispensing  
Dock  
Rig Supply  
Transfer Discharge  
Transfer S&D

Specialty

Steam

Vacuum

**Water**  
Discharge  
Suction & Discharge  
Washdown  
Garden

Welding

Coupling Systems

Equipment

Appendix