



MANGUERAS INDUSTRIALES INDUSTRIAL HOSES

Manguera para Minería MINING HOSES

CONSTRUCCIÓN

Tubo Interno: Mezcla de goma sintética resistente al aceite Nitrilo-Butadieno
Refuerzo: Mallas textiles, **Cubierta:** Mezcla de goma sintética resistente al aceite y al ozono, **Aplicación:** Aire, Agua y fluidos hidráulicos a base de petróleo y agua,
Rango de Temperatura: -40°C + 100°C

CONSTRUCTION

Inner Tube: Oil resistant synthetic nitrile-butadiene rubber, **Reinforcement:** High tensile textile cords, **Cover:** Oil and weather resistant synthetic rubber,
Application: Petroleum and water base hydraulic fluids, air and water,
Temperature Range: -40°C + 100°C



SERVICIO GENERAL AIRE-AGUA-ACEITE MINERÍA
Mining General Service Air-Water-Oil **H02307**

Código Code	Diámetro Interno Hose I.D.		Diámetro Externo Hose O.D.		Presión Max. Trab. Working Pressure		Presión Min. Ruptura Burst Pressure		Radio de Curvatura Bending Radius		Rollo Roll	
	in	mm	mm	in	bar	psi	bar	psi	mm	in	mts	fts
H02307-250	1/4"	6.5	15.5	0.6	34.5	500	104	1500	70	2.76	50.00	164.04
H02307-380	3/8"	9.8	18.5	0.7	34.5	500	104	1500	80	3.15	50.00	164.04
H02307-500	1/2"	12.8	22.0	0.9	34.5	500	104	1500	110	4.33	50.00	164.04
H02307-630	5/8"	16.0	26.0	1.0	34.5	500	104	1500	130	5.12	50.00	164.04
H02307-750	3/4"	19.1	29.5	1.2	34.5	500	104	1500	170	6.69	50.00	164.04
H02307-1000	1"	25.4	36.5	1.4	34.5	500	104	1500	250	9.84	50.00	164.04
H02307-1250	1.1/4"	31.8	44.0	1.7	34.5	500	104	1500	265	10.43	40.00	131.23
H02307-1500	1.1/2"	38.1	50.0	2.0	34.5	500	104	1500	335	13.19	40.00	131.23
H02307-2000	2"	51.0	66.0	2.6	34.5	500	104	1500	610	24.02	40.00	131.23

CONSTRUCCIÓN

Tubo Interno: Mezcla de goma sintética NR/SBR, **Refuerzo:** Mallas textiles
Cubierta: Mezcla de goma sintética resistente al ozono, **Aplicación:** Aire comprimido para aplicaciones de trabajo pesado en minería, construcción e industrias
Rango de Temperatura: -25°C + 70°C

CONSTRUCTION

Inner Tube: Synthetic NR/SBR blended rubber, **Reinforcement:** High tensile textile cords
Cover: Weather resistant synthetic rubber, **Application:** Compressed air designed for heavy duty mining, industrial and construction applications
Temperature Range: -25°C + 70°C



SERVICIO GENERAL AIRE-AGUA MINERÍA
Mining General Service Air-Water **H02308**

Código Code	Diámetro Interno Hose I.D.		Diámetro Externo Hose O.D.		Presión Max. Trab. Working Pressure		Presión Min. Ruptura Burst Pressure		Radio de Curvatura Bending Radius		Rollo Roll	
	in	mm	mm	in	bar	psi	bar	psi	mm	in	mts	fts
H02308-500	1/2"	12.7	22.0	0.9	20	300	80	1160	140	5.51	50.00	164.04
H02308-750	3/4"	19.1	29.0	1.1	20	300	80	1160	210	8.27	50.00	164.04
H02308-1000	1"	25.5	35.5	1.4	20	300	80	1160	280	11.02	50.00	164.04
H02308-1250	1.1/4"	32.0	46.0	1.8	20	300	80	1160	350	13.78	40.00	131.23
H02308-1500	1.1/2"	38.0	53.0	2.1	20	300	80	1160	420	16.54	40.00	131.23
H02308-2000	2"	51.0	66.0	2.6	20	300	80	1160	610	24.02	40.00	131.23
H02308-3000	3"	76.0	93.0	3.7	20	300	80	1160	950	37.40	20.00	65.62
H02308-4000	4"	102.0	120.0	4.7	15	218	45	653	1200	47.24	20.00	65.62