

# PRO-FLOW

A lightweight, heat resistant, rubber covered hose that delivers superior flow every time, everywhere. Ozone and chemical resistant, the nitrile/PVC through-the-weave design allows the hose to expand under pressure — decreasing friction loss and increasing water flow. The ribbed rubber outer cover offers increased resistance to impact,

## HEAVY DUTY RUBBER COVERED HOSE

punctures and abrasion. Reliable, maintenance-free and requires no drying, makes this the ideal hose for dewatering, industrial fire fighting, large diameter supply hose and wash down on construction sites. NFPA compliant and UL Listed\*. Pro-Flow coupling options are as required by purchaser, expansion ring threaded, Storz clamp ring, etc.

### RUBBER COVERED INDUSTRIAL HOSE



Diameter	Part No.	Service Test	Proof Test	Burst Test	Bowl Size	Weight Uncoupled
*1½"	RC15-500	250 psi	500 psi	750 psi	1 <sup>13</sup> / <sub>16</sub> "	0.22 lbs/ft
1¾"	RC17-500	250 psi	500 psi	750 psi	1 <sup>15</sup> / <sub>16</sub> "	0.25 lbs/ft
*2"	RC20-500	250 psi	500 psi	750 psi	2¼"	0.30 lbs/ft
*2½"	RC25-500	250 psi	500 psi	750 psi	2 <sup>13</sup> / <sub>16</sub> "	0.40 lbs/ft
**3"	RC30-600	300 psi	600 psi	900 psi	3 <sup>3</sup> / <sub>8</sub> "	0.60 lbs/ft
***4"	RC40-500	250 psi	500 psi	750 psi	4¼"	0.74 lbs/ft
***5"	RC50-450	225 psi	450 psi	675 psi	5¼"	0.93 lbs/ft
6"	RC60-450	225 psi	450 psi	675 psi	6¼"	1.35 lbs/ft

\*UL Listed to 250 psi | \*\*UL Listed to 300 psi | \*\*\*UL Listed to 200 psi



Red Yellow

Other colors available upon request

