


PSD610



BANDSAW MACHINE





Semi-Automatic
Double Mitre



www.excision.com.au

Excision[®]
Dependable Precision

CUTTING CAPACITY

	0°	45°	60°	-45°
	400 mm	350m m	200 mm	350m m
	400 mm	350m m	200 mm	350m m
	400 x 610 mm	350 x 400 mm	200 x 400 mm	350 x 400 mm

TECHNICAL SPECIFICATIONS

Main Motor	: 4 kW
Gearbox	: Bevel Helical PKD 2390 High Efficiency
Hydraulic Motor	: 0,37 kW
Hydraulic Tank Capacity	: 8 Liter
Coolant Motor	: 0,12 kW
Coolant Tank Capacity	: 30 liters
Blade Speed	: 25-90 m/min
Blade Dimensions	: 4.650 x 34 x 1,1 mm
Machine Weight	: 1.350 kg
Machine Dimensions	: 1400 x 2350 x 1500 mm
Table Height	: 750 mm



BANDSAW MACHINE

FEATURES



Manual Control Panel

Only control panel with buttons.



Inverter

Provides to adjust blade speed up to workpiece diameter, thickness and hardness.




Hydraulic Vise

Pressure, clamping period and clamping time can be adjusted.




Swarf Brush

Removes swarfs to keep clean the wheels and blade.



Hydramechanical Blade Tensioning


Tensioning period and tensioning time can be adjusted. So blade does not relax and curve cutting gets prevented.




Blade Bedding with Carbide and Bearings

BANDSAW MACHINE

FEATURES



Rotating Table



Bevel Helical Gearbox



60 cm Long Material Stopper System



Moveable Guide Arms



www.excision.com.au

Excision
Dependable Precision

BANDSAW MACHINE


FEATURES



Adjustable Bow
Down Speed



Adjustable vise Tension



Easy Readable Angle Ruler

