

SUSTAIN MDF PRIMER (WB25)

Page: 1

Compilation date: 18/05/2012 Revision date: 24/07/20

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: SUSTAIN MDF PRIMER (WB25)Product code: M01275R3Synonyms: WB 25

SUSTAIN CARE 21

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: MDF Primer

1.3. Details of the supplier of the safety data sheet

Company name:	General Paints Ltd	
	Maynooth Road,	
	Celbridge	
	Co.Kildare	
	Ireland	
Tel:	00 353 1 6288224	
Fax:	00 353 1 6272205	
Email:	info@generalpaints.ie	

1.4. Emergency telephone number

Emergency tel: 00 353 1 6288224

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Γ		
		allergic reaction.
		[ec no 247-500-7] and 2-methyl-2h-isothiazol-3-one [ec no 220-239-6]. May produce an
	Most important adverse effects:	Contains 1,2-benzisothiazolin-3-one, a mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one
	Classification under CLP:	-: EUH208

2.2. Label elements

Label elements:	
Hazard statements:	EUH208: Contains 1,2-benzisothiazolin-3-one, a mixture of: 5-chloro-2-methyl-2h-
	isothiazol-3-one [ec no 247-500-7] and 2-methyl-2h-isothiazol-3-one [ec no 220-239-6].
	May produce an allergic reaction.

SUSTAIN MDF PRIMER (WB25)

Page: 2

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

TALC

EINECS	CAS	PBT / WEL	CLP Classification	Percent
238-877-9	14807-96-6	Substance with a Community workplace exposure limit.	-	10-30%

TITANIUM DIOXIDE

236-675-5	13463-67-7	Substance with a Community	-	10-30%
		workplace exposure limit.		

1,2-BENZISOTHIAZOLIN-3-ONE

220-120-9	2634-33-5	- Acute Tox. 4: H302; Skin Irrit. 2: H315;		<1%
			Eye Dam. 1: H318; Skin Sens. 1:	
			H317; Aquatic Acute 1: H400	

A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6]

-	55965-84-9	-	Acute Tox. 3: H331; Acute Tox. 3: H311;	<1%
			Acute Tox. 3: H301; Skin Corr. 1B:	
			H314; Skin Sens. 1: H317; Aquatic	
			Acute 1: H400; Aquatic Chronic 1:	
			H410	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

SUSTAIN MDF PRIMER (WB25)

Page: 3

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leakside up to prevent the escape of liquid. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

SUSTAIN MDF PRIMER (WB25)

Hazardous ingredients:

TALC

Respirable dust Workplace exposure limits: State 8 hour TWA 15 min. STEL 8 hour TWA 15 min. STEL IE 4mg/m3 10mg/m3 _ TITANIUM DIOXIDE IE 10mg/m3 inhalable 4mg/m3 _

DNEL/PNEC Values

Hazardous ingredients:

1,2-BENZISOTHIAZOLIN-3-ONE

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation (developmental tox)	111	Consumers	Systemic

8.2. Exposure controls

Engineering measures: The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Liquid
Colour:	White
Odour:	Barely perceptible odour
Solubility in water:	Miscible
Viscosity:	Viscous
Boiling point/range°C:	100
upper:	Not applicable.

Flammability limits %: lower: Not applicable.

Flash point°C: Not applicable.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

Page: 4

-

SUSTAIN MDF PRIMER (WB25)

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

1,2-BENZISOTHIAZOLIN-3-ONE

ORL	MUS	LD50	1150	mg/kg
ORL	RAT	LD50	1020	mg/kg

A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6]

ORL	MUS	LD50	60	mg/kg
ORL	RAT	LD50	53	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

SUSTAIN MDF PRIMER (WB25)

Page: 6

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

- company.
- **NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information:	according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation
	(EU) 2015/830
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	EUH208: Contains 1,2-benzisothiazolin-3-one, a mixture of: 5-chloro-2-methyl-2h-
	isothiazol-3-one [ec no 247-500-7] and 2-methyl-2h-isothiazol-3-one [ec no 220-239-6].
	May produce an allergic reaction.
	H301: Toxic if swallowed.
	H302: Harmful if swallowed.
	H311: Toxic in contact with skin.
	H314: Causes severe skin burns and eye damage.

SUSTAIN MDF PRIMER (WB25)

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H331: Toxic if inhaled.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. Page: 7