

Description: **Colourtrend Woodcoat** is an extremely durable exterior coating for use on wooden cladding and siding, fences, fascia's and soffits, outdoor furniture, railings and cement patios, steps and walkways. This innovative formula resists scuffing. **Colourtrend Woodcoat** is ideal for use on most types of timber including red deal, cedar, teak, mahogany, cypress, pine and fir, as well as pressure treated wood. Suitable for interior and exterior use.

Special Features:

- Acrylic resin
- Excellent colour retention
- Mould & mildew resistant
- Fast drying
- Excellent sheen retention
- Excellent flow & levelling properties
- Low VOC
- Very low odour
- Good block resistance
- Easy clean up with soapy water
- Compatible with oil or waterbased undercoats
- Non-hazardous under EU legislation

Solids: 52 ± 2% by weight
37 ± 2% by volume

Specific Gravity: 1.30 ± 0.2 g/cm³

Theoretical Coverage: 10 - 15m²/L

Recommended Film Thickness: Wet: 80 microns

Dry: 30 microns

VOC: EU limit for this product (Cat A/e): 150g/L (2010). This product contains max **50 g/L**.

Thinning: Up to 15 % water may be used for spray application.

Drying Conditions: At ambient temperature (20-23 ° C) :

Touch dry: 1-2 hours depending on film thickness and drying conditions.

Re-coat after 4-6 hours.

Full paint properties do not develop for a minimum of 7 to 10 days after application (depending on drying conditions).

NOTE: Do not apply if surfaces are wet or in poor drying conditions. Do not apply at temperatures below 10°C or relative humidity above 80%

Finish: Low sheen finish, 12.5% ± 2.5%

Colour Range: Wide Variety of Colours including **Colourtrend** RAL & BS.

Viscosity: 110 ± 10 KU

Storage: Store in dry, cool conditions and protect from frost.

Application Method: Brush, roller or spray.

Spray Suggestion: **Spray Application:** Airless or air assisted airless, pressure pot.

Clean Up:

Clean equipment with water immediately after use. Replace lid on can and stir thoroughly before re-use.

Surface Preparation:

Ensure surface is clean, dry and free from dirt and grease. For unpainted hardwoods such as teak, mahogany or cedar 2 coats of **Colourtrend Prime 1/Prime 3** are recommended to prevent the bleed of oils and tannins through the coating. Allow new wood to weather for about 6 weeks before first application, but no more than 8 weeks. Wood that is weather for longer requires sanding before application to remove loose wood fibres

Safety, Health and Environmental Information

Not classified as hazardous for health.
Handle with care.

Avoid prolonged contact with skin and breathing of spray mist.
A Material Health & Safety Data Sheet is available on request.

IMPORTANT NOTE:

The information contained in this Data Sheet is not intended to be conclusive, and any person using this product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from General Paints as to the suitability of this product for the intended purpose, does so at his or her own risk. Whilst we attempt to ensure that all advice we give about this product (whether in the sheet or otherwise) is correct, we have no control over the quality or condition of the substrate or the many factors affecting the use and application of this product. Therefore, unless we specifically agree in writing to do so, we do not accept liability whatsoever, or howsoever arising, for the performance of this product or from any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of this product. The information contained in this sheet is likely to change from time to time in the light of experience and our policy of on-going product updates.

HEALTH & SAFETY INFORMATION:

This product should not be used without reference to the relevant Health and Safety Data Sheet, which General Paints Ltd. has provided for its customers. If for any reason a copy of this Data Sheet is not available the user should contact General Paints Ltd. to obtain a copy before using this product.