

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Quick Drying Clear Varnish Matt

Revision Date 07.05.2020

Version 3.0

Print Date 07.05.2020



BUILDING TRUST



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : Everbuild Quick Drying Clear Varnish Matt

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Surfaces protection

### 1.3 Details of the supplier of the safety data sheet

Company : Everbuild – A Sika Company  
Site 41  
Knowsthorpe Way  
Cross Green Industrial Estate  
Leeds  
West Yorkshire LS9 0SW  
United Kingdom

Telephone : 0113 240 3456

E-mail address : everbuild.sds@uk.sika.com

### 1.4 Emergency telephone number

Emergency telephone number : 0044 113 240 3456 (office hours only)

---

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

#### Additional Labelling

||| EUH208 Contains 1,2-benzisothiazol-3(2H)-one (BIT), 2-methyl-2H-isothiazol-3-one (MIT), mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Quick Drying Clear Varnish Matt

Revision Date 07.05.2020



BUILDING TRUST



Version 3.0

Print Date 07.05.2020

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
2-(2-butoxyethoxy)ethanol	112-34-5 203-961-6 01-2119475104-44-XXXX	Eye Irrit. 2; H319	>= 2,5 - < 5
1,2-benzisothiazol-3(2H)-one (BIT)	2634-33-5 220-120-9 01-2120761540-60-XXXX	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 0,025 - < 0,05
2-methyl-2H-isothiazol-3-one (MIT)	2682-20-4 220-239-6 01-2120764690-50-XXXX	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,0002 - < 0,0015
mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	55965-84-9 911-418-6 01-2120764691-48-XXXX	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,0002 - < 0,0015
Substances with a workplace exposure limit :			
propane-1,2-diol	57-55-6 200-338-0 01-2119456809-23-XXXX		>= 1 - < 2,5

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Quick Drying Clear Varnish Matt

Revision Date 07.05.2020

Version 3.0

Print Date 07.05.2020



BUILDING TRUST



---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : No hazards which require special first aid measures.
- If inhaled : Move to fresh air.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : See Section 11 for more detailed information on health effects and symptoms.
- Risks : No known significant effects or hazards.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

#### 5.2 Special hazards arising from the substance or mixture

- Hazardous combustion products : No hazardous combustion products are known

#### 5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Standard procedure for chemical fires.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : For personal protection see section 8.

### 6.2 Environmental precautions

Environmental precautions : No special environmental precautions required.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.  
No special handling advice required.  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.

Advice on common storage : No special restrictions on storage with other products.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
2-(2-butoxyethoxy)ethanol	112-34-5	STEL	15 ppm	2006/15/EC

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Quick Drying Clear Varnish Matt

Revision Date 07.05.2020

Version 3.0

Print Date 07.05.2020



BUILDING TRUST



			101,2 mg/m <sup>3</sup>	
	Further information: Indicative			
		TWA	10 ppm 67,5 mg/m <sup>3</sup>	2006/15/EC
		TWA	10 ppm 67,5 mg/m <sup>3</sup>	GB EH40
		STEL	15 ppm 101,2 mg/m <sup>3</sup>	GB EH40
propane-1,2-diol	57-55-6	TWA (particles)	10 mg/m <sup>3</sup>	GB EH40
	Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Total vapour and particles)	150 ppm 474 mg/m <sup>3</sup>	GB EH40

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

## 8.2 Exposure controls

### Personal protective equipment

- Eye protection : Safety glasses
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Butyl rubber/nitrile rubber gloves (0,4 mm)  
Recommended: Butyl rubber/nitrile rubber gloves.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### Environmental exposure controls

- General advice : No special environmental precautions required.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : white

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Quick Drying Clear Varnish Matt

Revision Date 07.05.2020

Version 3.0



BUILDING TRUST



Print Date 07.05.2020

Odour	:	slight
Odour Threshold	:	No data available
pH	:	ca. 8 - 9 (20 °C)
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	> 101 °C Method: closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	23 hPa
Relative vapour density	:	No data available
Density	:	ca. 1 g/cm <sup>3</sup> (20 °C)
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20,5 mm <sup>2</sup> /s (40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available

### 9.2 Other information

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Quick Drying Clear Varnish Matt

Revision Date 07.05.2020

Version 3.0



BUILDING TRUST



Print Date 07.05.2020

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

#### 10.4 Conditions to avoid

Conditions to avoid : No data available

#### 10.5 Incompatible materials

Materials to avoid : No data available

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Not classified based on available information.

##### Components:

##### || 2-(2-butoxyethoxy)ethanol:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): ca. 2.700 mg/kg

##### || 1,2-benzisothiazol-3(2H)-one (BIT):

Acute oral toxicity : LD50 Oral (Rat): 597 mg/kg

Acute inhalation toxicity : LC50: 0,4 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

##### || 2-methyl-2H-isothiazol-3-one (MIT):

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

|| mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)):

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Quick Drying Clear Varnish Matt

Revision Date 07.05.2020

Version 3.0



BUILDING TRUST



Print Date 07.05.2020

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

### Skin corrosion/irritation

Not classified based on available information.

### Serious eye damage/eye irritation

Not classified based on available information.

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

1,2-benzisothiazol-3(2H)-one (BIT):

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 3 mg/l  
Exposure time: 48 h

2-methyl-2H-isothiazol-3-one (MIT):

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)):

M-Factor (Acute aquatic toxicity) : 100



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Quick Drying Clear Varnish Matt

Revision Date 07.05.2020

Version 3.0

Print Date 07.05.2020



BUILDING TRUST



M-Factor (Chronic aquatic toxicity) : 100

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

#### Product:

Additional ecological information : There is no data available for this product.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

---

## SECTION 14: Transport information

### 14.1 UN number

Not regulated as a dangerous good

### 14.2 UN proper shipping name

Not regulated as a dangerous good

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Quick Drying Clear Varnish Matt

Revision Date 07.05.2020

Version 3.0

Print Date 07.05.2020



BUILDING TRUST



### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

### 14.4 Packing group

Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : None of the components are listed (= > 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH Information: All substances contained in our Products are  
- registered by our upstream suppliers, and/or  
- registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

|| Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 3,28 %

|| Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 5,77 %

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Quick Drying Clear Varnish Matt

Revision Date 07.05.2020

Version 3.0

Print Date 07.05.2020



BUILDING TRUST



If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations  
Health and Safety at Work Act 1974 & Subsidiary Regulations  
Control of Substances Hazardous to Health Regulations (COSHH)  
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

---

## SECTION 16: Other information

### Full text of H-Statements

H301 : Toxic if swallowed.  
H302 : Harmful if swallowed.  
H310 : Fatal in contact with skin.  
H311 : Toxic in contact with skin.  
H314 : Causes severe skin burns and eye damage.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H330 : Fatal if inhaled.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H411 : Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Skin Corr. : Skin corrosion  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
2006/15/EC : Europe. Indicative occupational exposure limit values  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
2006/15/EC / TWA : Limit Value - eight hours  
2006/15/EC / STEL : Short term exposure limit  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)  
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
CAS : Chemical Abstracts Service  
DNEL : Derived no-effect level  
EC50 : Half maximal effective concentration

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Everbuild Quick Drying Clear Varnish Matt

Revision Date 07.05.2020

Version 3.0

Print Date 07.05.2020



BUILDING TRUST



GHS	: Globally Harmonized System
IATA	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

### Further information

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

GB / EN