

**Safety data sheet**  
according to 1907/2006/EC, Article 31

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name:** MONTANA TECH Metal Primer
- **Article number:** 376320
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Sector of Use**  
SU21 Consumer uses: Private households / general public / consumers  
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Process category**  
PROC7 Industrial spraying  
PROC11 Non industrial spraying
- **Application of the substance / the mixture**  
Anticorrosion additive  
Priming
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
MONTANA CANS  
Häusserstr. 36  
D-69115 Heidelberg  
Tel. +49-6221-36333-30  
Fax +49-6221-36333-33  
info@montana-cans.de  
www.montana-cans.com
- **Further information obtainable from:** Department Product Safety
- **1.4 Emergency telephone number:**  
Tel.: +49 6266-75-310  
Fax +49 6266-75-362  
(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.  
STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 22.04.2020

Version number 5

Revision: 22.04.2020

**Trade name: MONTANA TECH Metal Primer**

(Contd. of page 1)

**· Hazard pictograms**

GHS02 GHS07

**· Signal word Danger****· Hazard-determining components of labelling:**

acetone  
n-butyl acetate  
2-methoxy-1-methylethyl acetate

**· Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

**· Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe spray.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents / container in accordance with regional regulations.

**· Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.  
EUH208 Contains maleic anhydride, 4-morpholinecarbaldehyde. May produce an allergic reaction.  
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.  
Buildup of explosive mixtures possible without sufficient ventilation.

**· 2.3 Other hazards****· Results of PBT and vPvB assessment**

· **PBT:** Not applicable.  
· **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**· 3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

**· Dangerous components:**

|   |   |           |
|---|---|-----------|
| CAS: 67-64-1<br>EINECS: 200-662-2<br>Index number: 606-001-00-8<br>Reg.nr.: 01-2119471330-49  | acetone<br>-----<br>⚠ Flam. Liq. 2, H225<br>⚠ Eye Irrit. 2, H319; STOT SE 3, H336 | 25-<50%   |
| CAS: 123-86-4<br>EINECS: 204-658-1<br>Index number: 607-025-00-1<br>Reg.nr.: 01-2119485493-29 | n-butyl acetate<br>-----<br>⚠ Flam. Liq. 3, H226<br>⚠ STOT SE 3, H336             | 10-<12.5% |

(Contd. on page 3)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 22.04.2020

Version number 5

Revision: 22.04.2020

**Trade name: MONTANA TECH Metal Primer**

(Contd. of page 2)

|   |   |           |
|---|---|-----------|
| CAS: 74-98-6<br>EINECS: 200-827-9<br>Index number: 601-003-00-5<br>Reg.nr.: 01-2119486944-21    | propane<br>⚠ Flam. Gas 1A, H220<br>⚠ Press. Gas (Comp.), H280   | 10-<12.5% |
| CAS: 106-97-8<br>EINECS: 203-448-7<br>Index number: 601-004-00-0<br>Reg.nr.: 01-2119474691-32   | butane<br>⚠ Flam. Gas 1A, H220<br>⚠ Press. Gas (Comp.), H280  | 5-<10%    |
| CAS: 9004-70-0  | cellulose nitrate<br>⚠ Flam. Sol. 1, H228   | 2.5-<5%   |
| CAS: 75-28-5<br>EINECS: 200-857-2<br>Index number: 601-004-00-0<br>Reg.nr.: 01-2119485395-27    | isobutane<br>⚠ Flam. Gas 1A, H220<br>⚠ Press. Gas (Comp.), H280   | 2.5-<5%   |
| EC number: 905-588-0<br>Index number: 601-022-00-9<br>Reg.nr.: 01-2119488216-32                 | xylene<br>⚠ Flam. Liq. 3, H226<br>⚠ STOT RE 2, H373; Asp. Tox. 1, H304<br>⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315;<br>Eye Irrit. 2, H319; STOT SE 3, H335 | <2.5%     |
| CAS: 7779-90-0<br>EINECS: 231-944-3<br>Index number: 030-011-00-6<br>Reg.nr.: 01-2119485044-40  | trizinc bis(orthophosphate)<br>⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410   | <2.5%     |
| CAS: 64-17-5<br>EINECS: 200-578-6<br>Index number: 603-002-00-5<br>Reg.nr.: 01-2119457610-43    | ethanol<br>⚠ Flam. Liq. 2, H225<br>⚠ Eye Irrit. 2, H319   | <2.5%     |
| CAS: 108-65-6<br>EINECS: 203-603-9<br>Index number: 607-195-00-7<br>Reg.nr.: 01-2119475791-29   | 2-methoxy-1-methylethyl acetate<br>⚠ Flam. Liq. 3, H226<br>⚠ STOT SE 3, H336  | <2.5%     |
| CAS: 13463-67-7<br>EINECS: 236-675-5<br>Index number: 022-006-00-2<br>Reg.nr.: 01-2119489379-17 | titanium dioxide<br>⚠ Carc. 2, H351   | <2.5%     |
| CAS: 4394-85-8<br>EINECS: 224-518-3<br>Reg.nr.: 01-2119987993-12                                | 4-morpholinecarbaldehyde<br>⚠ Skin Sens. 1, H317  | ≤0.5%     |

**Additional information:**

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex IA 1272/2008 EU), so the classification as carcinogen need not to apply.

xylene: Contains ethylbenzene CAS 100-41-4

For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

• **General information:** Take affected persons out into the fresh air.

• **After inhalation:** Supply fresh air; consult doctor in case of complaints.

• **After skin contact:** Generally the product does not irritate the skin.

• **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 22.04.2020

Version number 5

Revision: 22.04.2020

**Trade name: MONTANA TECH Metal Primer**

(Contd. of page 3)

- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.  
Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters -**
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Do not inhale explosion gases or combustion gases.  
Mouth respiratory protective device.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Keep away from ignition sources.  
Ensure adequate ventilation  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Keep away from heat and direct sunlight.  
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).  
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Fumes can combine with air to form an explosive mixture.  
Keep ignition sources away - Do not smoke.  
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 22.04.2020

Version number 5

Revision: 22.04.2020

Trade name: **MONTANA TECH Metal Primer**

(Contd. of page 4)

### SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

#### · 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

##### 67-64-1 acetone

WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm  
Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

##### 123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

##### 106-97-8 butane

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm  
Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm  
Carc (if more than 0.1% of buta-1.3-diene)

##### xylene

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; BMGV

##### 64-17-5 ethanol

WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm

##### 108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 274 mg/m<sup>3</sup>, 50 ppm  
Sk

· **Ingredients with biological limit values:**

##### xylene

BMGV 650 mmol/mol creatinine  
Medium: urine  
Sampling time: post shift  
Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

##### · Personal protective equipment:

##### · General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.  
Avoid contact with the eyes.

##### · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

(Contd. on page 6)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 22.04.2020

Version number 5

Revision: 22.04.2020

**Trade name: MONTANA TECH Metal Primer**

(Contd. of page 5)

· **Protection of hands:**

Protective gloves

· **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· **Eye protection:**

Tightly sealed goggles

· **Body protection:** Light weight protective clothing

## SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form: Aerosol

Colour: Grey

· **Odour:** Characteristic· **Odour threshold:** Not determined.· **pH-value:** Not determined.· **Change in condition**

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.· **Flammability (solid, gas):** Not applicable.· **Ignition temperature:** 365 °C (689 °F)· **Decomposition temperature:** Not determined.· **Explosive properties:** Not determined.· **Explosion limits:**

Lower: 1.2 Vol %

Upper: 13 Vol %

· **Vapour pressure at 20 °C (68 °F):** 8300 hPa (6225.5 mm Hg)· **Density at 20 °C (68 °F):** 0.8 g/cm<sup>3</sup> (6.7 lbs/gal)· **Relative density** Not determined.· **Vapour density** Not determined.

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 22.04.2020

Version number 5

Revision: 22.04.2020

**Trade name: MONTANA TECH Metal Primer**

(Contd. of page 6)

|  |  |
|--|--|
| · <b>Evaporation rate</b>                        | Not applicable.                            |
| · <b>Solubility in / Miscibility with water:</b> | Not miscible or difficult to mix.          |
| · <b>Partition coefficient: n-octanol/water:</b> | Not determined.                            |
| · <b>Viscosity:</b>                              |  |
| <b>Dynamic:</b>                                  | Not determined.                            |
| <b>Kinematic:</b>                                | Not determined.                            |
| · <b>Solvent content:</b>                        |  |
| <b>Organic solvents:</b>                         | 83.5 %                                     |
| <b>Water:</b>                                    | 0.1 %                                      |
| <b>VOC (EC)</b>                                  | ---  |
|  | 679.0 g/l                                  |
| · <b>VOC-EU%</b>                                 | 87.00 %                                    |
| · <b>Solids content:</b>                         | 14.5 %                                     |
| · <b>9.2 Other information</b>                   | No further relevant information available. |

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

**67-64-1 acetone**

|            |           |                       |
|------------|-----------|-----------------------|
| Oral       | LD50      | 5800 mg/kg (rat)      |
| Dermal     | LD50      | >15800 mg/kg (rabbit) |
| Inhalative | LC50 / 4h | 76 mg/l (rat)         |

**123-86-4 n-butyl acetate**

|            |            |                              |
|------------|------------|------------------------------|
| Oral       | LD50       | 10800 mg/kg (rat) (OECD 401) |
| Dermal     | LD50       | >17600 mg/kg (rabbit)        |
| Inhalative | LC50 / 4 h | >21 mg/m <sup>3</sup> (rat)  |

**xylene**

|            |            |                               |
|------------|------------|-------------------------------|
| Oral       | LD50       | 3523 mg/kg (rat)              |
| Dermal     | LD50       | 2000 mg/kg (rabbit)           |
| Inhalative | LC50 / 4 h | 29000 mg/m <sup>3</sup> (rat) |

**64-17-5 ethanol**

|            |           |                   |
|------------|-----------|-------------------|
| Oral       | LD50      | 10470 mg/kg (rat) |
| Dermal     | LD50      | >2000 mg/kg (rat) |
| Inhalative | LC50 / 4h | 120 mg/l (rat)    |

(Contd. on page 8)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 22.04.2020

Version number 5

Revision: 22.04.2020

**Trade name: MONTANA TECH Metal Primer**

(Contd. of page 7)

**108-65-6 2-methoxy-1-methylethyl acetate**

|            |            |                                |
|------------|------------|--------------------------------|
| Oral       | LD50       | 8530 mg/kg (rat)               |
| Dermal     | LD50       | >5000 mg/kg (rabbit)           |
| Inhalative | LC50 / 4 h | >10000 mg/m <sup>3</sup> (rat) |

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information**· **12.1 Toxicity**· **Aquatic toxicity:****67-64-1 acetone**

|             |                                     |
|-------------|-------------------------------------|
| LC50/96h    | 8300 mg/l (fish)                    |
| EC50/96h    | 7200 mg/l (algae)                   |
| LC50 / 48 h | 8450 mg/l (crustacean (water flea)) |

**xylene**

|             |                          |
|-------------|--------------------------|
| EC50 / 48 h | 7.4 mg/l (daphnia magna) |
| LC50 / 96 h | 13.5 mg/l (fish)         |

**64-17-5 ethanol**

|             |  |
|-------------|--|
| LC50/96h    | 13000 mg/l (oncorhynchus mykiss / Regenbogenforelle) |
| EC50 / 48 h | 12900 mg/l (algae)                                   |
| LC50 / 48 h | 12340 mg/l (daphnia magna)                           |

**108-65-6 2-methoxy-1-methylethyl acetate**

|             |  |
|-------------|--|
| EC50 / 48 h | >500 mg/l (daphnia magna)                              |
| LC50 / 96 h | 100-180 mg/l (oncorhynchus mykiss / Regenbogenforelle) |

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**· **Remark:** Harmful to fish· **Additional ecological information:**· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms

· **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 9)

GB



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 22.04.2020

Version number 5

Revision: 22.04.2020

Trade name: **MONTANA TECH Metal Primer**

(Contd. of page 8)

· **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

|           |   |
|-----------|---|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances |
| 15 01 04  | metallic packaging  |
| 15 01 10* | packaging containing residues of or contaminated by hazardous substances          |

· **Uncleaned packaging:**· **Recommendation:**

Dispose of packaging according to regulations on the disposal of packagings.

Non contaminated packagings may be recycled.

### SECTION 14: Transport information

· **14.1 UN-Number**· **ADR, IMDG, IATA**

UN1950

· **14.2 UN proper shipping name**· **ADR**

1950 AEROSOLS

· **IMDG**

AEROSOLS

· **IATA**

AEROSOLS, flammable

· **14.3 Transport hazard class(es)**· **ADR**· **Class**

2.5F Gases.

· **Label**

2.1

· **IMDG, IATA**· **Class**

2.1

· **Label**

2.1

· **14.4 Packing group**· **ADR, IMDG, IATA**

not regulated

· **14.5 Environmental hazards:**

Not applicable.

· **14.6 Special precautions for user**

Warning: Gases.

· **Hazard identification number (Kemler code):**

-

· **EMS Number:**

F-D,S-U

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 22.04.2020

Version number 5

Revision: 22.04.2020

**Trade name: MONTANA TECH Metal Primer**

(Contd. of page 9)

|  |  |
|--|--|
| · <b>Stowage Code</b>  | SW1 Protected from sources of heat.<br>SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.   |
| · <b>Segregation Code</b>  | SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.<br>For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2.<br>For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. |
| · <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b> | Not applicable.  |
| · <b>Transport/Additional information:</b>                                       |  |
| · <b>ADR</b>   |  |
| · <b>Limited quantities (LQ)</b>   | 1L   |
| · <b>Excepted quantities (EQ)</b>  | Code: E0<br>Not permitted as Excepted Quantity   |
| · <b>Transport category</b>  | 2  |
| · <b>Tunnel restriction code</b>   | D  |
| · <b>IMDG</b>  |  |
| · <b>Limited quantities (LQ)</b>   | 1L   |
| · <b>Excepted quantities (EQ)</b>  | Code: E0<br>Not permitted as Excepted Quantity   |
| · <b>UN "Model Regulation":</b>  | UN 1950 AEROSOLS, 2.1  |

\* **SECTION 15: Regulatory information**

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a FLAMMABLE AEROSOLS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**
- **Information about limitation of use:** Employment restrictions concerning juveniles must be observed.
- **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

\* **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.

(Contd. on page 11)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 22.04.2020

Version number 5

Revision: 22.04.2020

**Trade name: MONTANA TECH Metal Primer**

(Contd. of page 10)

H228 Flammable solid.  
 H280 Contains gas under pressure; may explode if heated.  
 H304 May be fatal if swallowed and enters airways.  
 H312 Harmful in contact with skin.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H351 Suspected of causing cancer. Route of exposure: Inhalation.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H400 Very toxic to aquatic life.  
 H410 Very toxic to aquatic life with long lasting effects.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
 ICAO: International Civil Aviation Organisation  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 SVHC: Substances of Very High Concern  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Gas 1A: Flammable gases – Category 1A  
 Aerosol 1: Aerosols – Category 1  
 Press. Gas (Comp.): Gases under pressure – Compressed gas  
 Flam. Liq. 2: Flammable liquids – Category 2  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Flam. Sol. 1: Flammable solids – Category 1  
 Acute Tox. 4: Acute toxicity - dermal – Category 4  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Skin Sens. 1: Skin sensitisation – Category 1  
 Carc. 2: Carcinogenicity – Category 2  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
 Asp. Tox. 1: Aspiration hazard – Category 1  
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **\* Data compared to the previous version altered.**

GB